







Rectangular Connectors GDM Series

Technical Information

| RMC 480 RMCB 480 | | | |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|-----------|
| | Description | Order Designation | Order No. |
|  | Crimping flat contact (blade), suitable for GSC series connectors, cable cross-section: 0.5 to 1.5 mm ² (B crimping) RMC 480: Pack size 100 RMCB 480: 3000 items on a reel | RMC 480 | 731470021 |
| | | RMCB 480 | 731468001 |
| XZC 0702 | | | |
| | Description | Order Designation | Order No. |
|  | Crimping tool for GDM and G series contacts, color: red Cable cross-section for contact: RMC 280, 0.5 to 1 mm ² , profile I, Order No. 731 991-021 RMC 480, 0.5 to 1.5 mm ² , profile II, Order No. 731 470-021 | XZC 0702 | 932507003 |
| | | | |
| GDM 3-7 NBR pale brown GDM 3-17 VMQ red GDM 3-21 EPDM | | | |
| | Description | Order Designation | Order No. |
|  | Flat gasket for GDM series rectangular connectors (type A) NBR: -30 °C to +90 °C VMQ (silicone): -40 °C to +125 °C EPDM (LABS -free): -40 °C to +125 °C Pack size: 50 | GDM 3-7 NBR pale brown | 730801002 |
| | | GDM 3-17 MPQ red | 731740002 |
| | | GDM 3-21 EPDM brown | 731739004 |
| GDM 3-16 NBR black GDM 3-19 VMQ coral red | | | |
| | Description | Order Designation | Order No. |
|  | Profile gasket for GDM series rectangular connectors (type A) NBR: -30 °C to +90 °C VMQ (silicone): -40 °C to +125 °C Pack size: 50 | GDM 3-16 NBR black | 731531002 |
| | | GDM 3-19 VMQ coral red | 731532002 |
| GSE 2000-2 NBR pale brown GSE 2000-3 EPDM | | | |
| | Description | Order Designation | Order No. |
|  | Flat gasket for appliance connector GSE... (type A) NBR: -30 °C to +90 °C EPDM (silicone-free): -40 °C to +125 °C Pack size: 50 | GSE 2000-2 NBR pale brown | 733973002 |
| | | GSE 2000-3 EPDM | 733846003 |
| GSAZ 35/43 NBR black GSAZ 40/62 NBR black GSAZ 60/120 NBR black | | | |
| | Description | Order Designation | Order No. |
|  | Cylinder profile gasket for appliance male connector GSAZ - 35 to 43 mm diameter - 40 to 62 mm diameter - 60 to 120 mm diameter (type A) NBR: -30 °C to +90 °C Pack size: 50 | GSAZ 35/43 NBR black | 733262002 |
| | | GSAZ 40/62 NBR black | 733264002 |
| | | GSAZ 60/120 NBR black | 733266002 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Sensor Cables / Actuator Cables](#) category:

Click to view products by [Hirschmann](#) manufacturer:

Other Similar products are found below :

[60963](#) [60964](#) [703000D02F2002](#) [703001D02F0602](#) [703001D02F1201](#) [703001D02F300](#) [704000D02F120](#) [MDM21SH001F](#) [773032K02F030](#)
[802027107404-1](#) [802027213811-1](#) [804001A09M150](#) [805001A09M0502](#) [84914-0235](#) [84914-0237](#) [885030A09M010](#) [8R4006A18M010](#)
[8R4J30E03C3003](#) [1200651713](#) [1200660844](#) [1200660845](#) [1200661173](#) [1200680071](#) [1200720053](#) [1200720081](#) [1200720094](#) [1200720099](#)
[1200720217](#) [1200800231](#) [1200860125](#) [1200870123](#) [1200660183](#) [1200660782](#) [1200660849](#) [1200661295](#) [1200661297](#) [1200661342](#)
[1200661343](#) [1200670080](#) [1200680331](#) [1200720252](#) [1200720255](#) [1200720597](#) [1200730184](#) [1200860344](#) [1200870359](#) [1200870643](#)
[1200980008](#) [1200980031](#) [1210502211](#)