



Sockets

KUN 30



((

Product	KUN 30						
description	Shatter-proof, flexible, insulated coupling for a 4 mm diameter plug and solder connection up to a cable cross-section of 2.5 mm². Nickel-plated brass socket.						
operating instruction	BA405						
article-no. / *colour	9318041xx						
	00 black	01 red	02 blue	03 yellow	04 green	07 white	
						Ni	
drawing							
technical data		-	4,2	8	1.5		
connection	solder connection						
rated voltage ⁽¹⁾	30 VAC / 60 VDC						
measurement cat. acc. to IEC 61010	O ⁽³⁾						
rated current ⁽¹⁾ (consider derating curve)	16 A						
material socket	brass, nickel plated						
housing material	PVC-P	PVC-P					
temperature range acc. To IEC61010 ⁽²⁾	-25 °C to +70 °C						
standard	IEC 61010						

⁽¹⁾ for normal environmental conditions -5°C to +40°C

 $[\]ensuremath{^{(2)}}$ contact the manufacturer for applications at deviating temperature ranges

⁽³⁾ without rated measurement category, for other circuits that are not directly connected to mains stand: 17.09.2018

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Control Switches category:

Click to view products by Hirschmann manufacturer:

Other Similar products are found below:

80887-99 80932-99 86855-00 88814-30 1424293-1 HW4S-2TC10 89721-12 89804-08 SSN RL01801 ASD2L20N-LVO 50051857-17 50099156-001-05 51.155R-15200 50058920-26 CP-FA51 CP-FA49 ACCU-SC/L-3000 PP9M PP87G PP86GA PP71G PP70G PP6G PP62G PP58BL PP56G PP86GB PP77GA PP76G PP4M PP47G PP46G PP41M PP40G PP32G RD-20 PP23M PP12G PORTAPRO POM-2708 PNB-2005 3057.0012 CV-075 CV-140SB CV-150 CV-150S 214X20XK CV-180 CV-200MB