

深圳市华宇创精密电子有限公司



TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.X ±2 X.X ±0.5

UNIT: mm [inch] SCALE: 1:1 SIZE: A4

DRAWN BY: 陈一鸣 DATE: 2014-02-23 PART NAME: MICRO SIM 6PIN 掀盖式1.8H

CHECKED BY: 马跃 DATE: 2014-02-23 PART NO.: HYC02-SIM06-180

APPROVED BY: 邱国美 DATE: 2014-02-23 SHEET NO.: 1 OF 1


二、技术参数:

接触电阻: 100mΩ Max
绝缘阻抗: 1000MΩ Min(500DC)
额定电流: 每个接插件1A Max
额定电压: 30V Max(DC)
耐压: 500V r.m.s/min
使用温度: -40℃~85℃
湿度: 90%~95%
寿命: >3000次

一、材质和镀层:

- 1、板芯: LCP, UL 94 V - 0, 黑色
- 2、端子: 磷铜(S210-H, T=0.15, 镀层镀金)
- 3、外壳: 不锈钢 SUS304 T=0.2

PIN NO.	NAME	PIN NO.	NAME
C3	RST	C6	IO
C2	GND	C5	CLK
C1	VCC	C4	VPP



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Standard Card Edge Connectors](#) category:

Click to view products by [HOAUC](#) manufacturer:

Other Similar products are found below :

[6565204-6](#) [PKC-156](#) [1437274-4](#) [147889-1](#) [1489165-4](#) [EBT156-12B1X](#) [EBT15622B2X](#) [EBT156-22R2W](#) [1-582587-1](#) [1-582589-1](#) [2-6437275-9](#) [284-0102-12100](#) [306022901000000](#) [307-012-502-202](#) [307-024-526-201](#) [307-056-520-300](#) [307-080-526-208](#) [1926088-2](#) [245-062-520-350](#) [287-0032-12101](#) [306-010-500-112](#) [306-028-525-102](#) [306-240-318](#) [307-036-502-202](#) [307-036-521-301](#) [307-072-526-202](#) [345-060-559-303](#) [368-004-520-201](#) [392-008-559-201](#) [534671-1](#) [5-530501-5](#) [341-240-317](#) [345-029-520-300](#) [345-030-500-301](#) [345-044-500-300](#) [345-220-058](#) [346-240-318](#) [357-030-526-201](#) [387-012-523-300](#) [395-044-520-300](#) [395-100-524-300](#) [50-12B-10](#) [50-6SN-5](#) [09-07-2032](#) [10035388-106LF](#) [10035388-802LF](#) [10115859-011LF](#) [10122859-009LF](#) [101269333204245CLF](#) [10127905-B04B24BLF](#)