



SCALE:1:1	SIZE: A4
UNIT: mm [inch]	
X: ±2	X.X' ±0.5
X.XX ±0.15	
X.XX ±0.25	
X.X ±0.30	
TOLERANCE:	



DRAWN BY: 陈一鸣	DATE: 2014-02-23	PART NAME: HDMI A TYPE 公座盖板1.6
CHECKED BY: 马跃	DATE: 2014-02-23	PART NO.: HXC109-HDMI A19-160
APPROVED BY:	DATE:	DRAW NO.: HXC-HDMI17071840
	2014-02-23	SHEET NO.: 1 OF 1

深圳市华宇创精密电子有限公司

NOTE :  
 1. SPECIFICATION:  
 1.1. CURRENT RATING: 0.5 Amp Max.  
 1.2. VOLTAGE RATING: 40 V ac(r.m.s) Max.  
 1.3. CONTACT RESISTANCE: 10m ohms Max. mated  
 1.4. INSULATION RESISTANCE: 100M ohms Min.  
 1.5. DIELECTRIC WITHSTANDING VOLTAGE:  
 AC 500V Min. (for 1 minute)  
 1.6. OPERATION TEMPERATURE RANGE:-25° C~85° C  
 2. MECHANICAL  
 2.1. INSERTION FORCE:4.5KGf MAXIMUM  
 2.1. WITHDRAWAL FORCE:1.0KGf MINIMUM;4.0KGf  
 MAXIMUM  
 2.3. DURABILITY:10000 CYCLES AT 100±50 CYCLES  
 PERHOUR, CONTACT CHANCE FROM INITIAL  
 VALUE:30MINI Ohms MAX

▲"为品管重点管控尺寸"

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [HDMI, Displayport & DVI Connectors](#) category:*

*Click to view products by [HOAUC](#) manufacturer:*

Other Similar products are found below :

[1775247-3](#) [2-1932649-5](#) [30-1231](#) [30-528](#) [2069485-1](#) [30-504](#) [30-519](#) [30-542](#) [47648-2000](#) [2002-400](#) [TC142X](#) [1453G1](#) [769-103/021-000](#)  
[1932649-1](#) [233-368NFG6-17NH](#) [G45A19071083HR](#) [233-360NF00-17NH](#) [CP30200GM3B](#) [HYC02-DVI29-371](#) [P136-06NHDV4KBP](#)  
[CP30116](#) [LTWDID-29PFFS-SL8001](#) [46765-1301](#) [1211-0010-201-001](#) [47271-1004](#) [32-1121-BU](#) [DS1117-BN0-TME-002](#) [MHDR2A11004BP](#)  
[EHHDMI2PKG](#) [1903015-3](#) [DS1114-BN0](#) [WPUSBAF](#) [500254-1931](#) [HDMR-19-01-F-SM](#) [47151-1071](#) [1747981-1](#) [0480372000](#) [0482580001](#)  
[D121073-19](#) [472710111](#) [HDMI-S-RA6-SMT-MF-15](#) [P142-000-UP](#) [P134-003](#) [P120-08N](#) [KDMIX-FS1V-WS-B](#) [P142-000-UD](#) [10029449-](#)  
[101RLF](#) [P132-000](#) [P130-000](#) [P142-06N-MICRO](#)