


NOTES:

- 1) ELECTRICAL SPECIFICATIONS:
 - 1-1. VOLTAGE RATING: 125V/AC
 - 1-2. CURRENT RATING: 1.5A
 - 1-3. INSULATION RESISTANCE: 500MEG.OHM MIN
 - 1-4. CONTACT RESISTANCE: 30 MILL.OHM MAX
 - 1-5. WITHSTANDING VOLTAGE: 1000V AC
 - 1-6. OPERATION TEMPERATURE: -40° TO +85°
 - 1-7. DURABILITY: 3000 CYCLES



RJ45 Pin Assignment:

Pin No.	Name
1	Tranceive Data+
2	Tranceive Data-
3	Receive Data+
4	Not connected
5	Not connected
6	Receive Data-
7	Not connected
8	Not connected

ITEM	NAME	Q'TY	MATERIAL	FINISH	REMARK
3	SHELL	1	COPPER ALLOY	Ni: 50 μ "Min.Overall Sn: 10~20 μ "	T=0.20
2	CONTACT	8	COPPER ALLOY	Ni: 50 μ "Min.Overall Au: 5 μ " Sn: Matte Pure Sn 100~120 μ "	T=0.30
1	HOUSING	1	THERMOPLASTIC	UL 94V-0, COLOR:BLACK	+G.F 30%



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X' $\pm 2'$ X.X' $\pm 0.5'$	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: RJ45 沉板上8.6
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO.: HYCW114-RJ45-086B
UNIT: mm [inch] SCALE: 1:1 SIZE: A4	APPROVED BY:	DATE : 2014-02-23	DRAW NO.: HYC-RJ16061218
			SHEET NO.: 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Modular Connectors](#) / [Ethernet Connectors](#) category:

Click to view products by [HOAUC](#) manufacturer:

Other Similar products are found below :

[8949-H88/06BLKA/SN](#) [74441-0010/BKN](#) [PHP-6P6C-5](#) [GAX-3-66](#) [GAX-8-62](#) [GDCX-PN-66](#) [GLX-A-44](#) [GLX-N-1010M-BLK](#) [GMX-SMT4-N-88](#) [GSGX-N-2-88](#) [GSGX-N-4-88](#) [GSX-NS2-88-3.05](#) [GSX-NS-88-3.68](#) [PT-108A-8C-UL](#) [PTS-J531-8CS-50UL](#) [A-2014-0-4](#) [GWLX-S9-88-YG](#) [DC-1021-8-WH-6](#) [1300530003](#) [1324640-4](#) [RJ11FTVC2G](#) [RJ11FTVC2N](#) [RJFTVX2SA1G](#) [132764-001](#) [1413235](#) [MPS88RX-5000](#) [E5288-S000K3-L](#) [155302-001](#) [AX101050](#) [AX101063](#) [AX101065](#) [AX101072](#) [AX101307](#) [AX101315](#) [AX101318](#) [AX102271](#) [AX102282](#) [AX102288](#) [AX102651](#) [AX102660](#) [AX103259](#) [AX104024](#) [J0012D21NL](#) [J0026D01ENL](#) [PC4D0018P](#) [8949-B88/6](#) [2-6609208-5](#) [937-SP-3088-2PC-A192](#) [303066VFL](#) [303068V](#)