

## PRODUCT INFORMATION SHEET

### Grease pump








#### Product description

Foot operated grease pump can be used in heavy industry, agriculture, construction, as well as automotive to service industrial machines, combine harvesters, construction machines, as well as cars, vans and trucks. Intended for professional use.

#### Charakteristics

- 6 L capacity;
- steel tank;
- maximum pressure 3600 PSI / 250 BAR;
- grease delivery volume per stroke 3 cm<sup>3</sup>;
- M10x1 threads;
- 1.8 m long hose with 4-jaw coupler and steel, conical tip included in a set;
- a foot-operated piston, additionally sealed;
- vent valve;
- 2 wheels enable quick and convenient transport of tool to the workplace.

#### Technical data

				
HT8G912	5902801358975	6 L	1	1



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Hand Tools](#) category:*

*Click to view products by [Hogert Technik](#) manufacturer:*

Other Similar products are found below :

[58284-1](#) [59773-1](#) [662908-1](#) [68764-0001](#) [690619-6](#) [7-354778-7](#) [768531-1](#) [810131](#) [81541-16](#) [854183-1](#) [854358-1](#) [90855-1](#) [992258-1](#) [1-21046-3](#) [121073-0047](#) [1-22278-0](#) [1-22278-2](#) [1-24954-2](#) [125529-5](#) [126513-1](#) [1-305579-8](#) [1-306027-0](#) [1320846-1](#) [1338968-2](#) [1-354779-0](#) [1-354779-2](#) [1-354779-4](#) [1424443-1](#) [1424266-1](#) [1424289-1](#) [1424444-1](#) [1532195-2](#) [1538773-2](#) [1-692134-3](#) [HT-920A-124-HTELE-RPL-KIT](#) [1976923-1](#) [1976969-1](#) [2063795-1](#) [2-21002-1](#) [2-21002-4](#) [2-21002-7](#) [2-21002-9](#) [2-21004-0](#) [229707-1](#) [911737-2](#) [91348-2](#) [925980-R](#) [301185-9](#) [983533-1](#) [1-694433-7](#)