



Φ5.2x20mm IEC STANDARD FUSE RoHS Compliant & Pb-Free
HIGH BREAKING CAPACITY CERAMIC
TUBE FUSE (TIME-LAG)
瓷质保险丝 (慢断型)




BREAKING CAPACITY/ 分断能力:
1,500 amperes at 250V AC


Dimensions/ 尺寸:

Unit 单位: mm

50CT



50CT(P)



Standards/ 标准: IEC 60127 GB 9364


Operating Temperature/ 工作温度: -55°C ~125°C

Storing Temperature/ 储存温度: -55°C ~85°C

Resistance to soldering heat/ 耐焊接热性: 260°C, 10s Max
Solderability/ 可焊性: 245°C ±5°C, 5s ±0.5s

50CT AVERAGE I-T CHARACTERISTICS CURVE
(FOR REFERENCE ONLY)

50CT 平均 I-T 曲线图 (仅供参考)



TECHNICAL PARAMETERS/ 技术参数:

CATALOG NO. 目录编号	CURRENT RATING 额定电流	MAX. VOLTAGE DROP 最大电压降 (mV)	SAFETY APPROVALS 安全认证									REFERENCE (A°.Sec.) (RoHS) I-T 参考值
			CCC	CQC	SEKO	VDE	BSI	UR/CUR	PSE	KC	TUV	
50CT-0200H	200mA	2100								●		0.0480
50CT-0250H	250mA	1500								●		0.0570
50CT-0315H	315mA	1100								●		0.0960
50CT-0400H	400mA	1000								●		0.1610
50CT-0500H	500mA	850								●		0.2570
50CT-0630H	630mA	650								●		0.4510
50CT-0800H	800mA	500								●		0.5532
50CT-010H	1A	350	●	●	●	●	●	●	●	●	●	1.014
50CT-013H	1.25A	300	●	●	●	●	●	●	●	●	●	2.115
50CT-016H	1.6A	200	●	●	●	●	●	●	●	●	●	4.238
50CT-020H	2A	190	●	●	●	●	●	●	●	●	●	7.120
50CT-025H	2.5A	180	●	●	●	●	●	●	●	●	●	7.781
50CT-032H	3.15A	140	●	●	●	●	●	●	●	●	●	15.46
50CT-040H	4A	100	●	●	●	●	●	●	●	●	●	37.60
50CT-050H	5A	100	●	●	●	●	●	●	●	●	●	60.95
50CT-063H	6.3A	100	●	●	●	●	●	●	●	●	●	101.3
50CT-080H	8A	100	●	●	●	●	●	●	●	●	●	188.7
50CT-100H	10A	100	●	●	●	●	●	●	●	●	●	323.4
50CT-120H	12A	80	●	●	●	●	●	●	●	●	●	539.2
50CT-125H	12.5A	80	●	●	●	●	●	●	●	●	●	585.1
50CT-150H	15A	80	●	●	●	●	●	●	●	●	●	934.1
50CT-160H	16A	80	●	●	●	●	●	●	●	●	●	1055

H DENOTES FOR 250V

H 表示 250V

● DENOTES FOR APPROVED

● 表示已取得安全认证

REMARK 备注:

50CT(P)-125H WITHOUT VDE APPROVAL

50CT(P)-125H 产品无 VDE 认证

50CT(P)-160H WITHOUT CQC/VDE APPROVAL

50CT(P)-160H 产品无 CQC/VDE 认证

ELECTRICAL CHARACTERISTICS/ 电气特性:

RATING 额定		BLOWING TIME 熔断时间			
		200mA-800mA	1A-3.15A	4A-10A	>10A
2.1In	Max. 最慢	30 minutes	30 minutes	30 minutes	30 minutes
	Min. 最快	250 ms	750ms	750 ms	1 second
2.75In	Max. 最慢	80 seconds	80 seconds	80 seconds	80 seconds
	Min. 最快	50 ms	95 ms	150 ms	150 ms
4In	Max. 最慢	5 seconds	5 seconds	5 seconds	8 seconds
	Min. 最快	5 ms	10 ms	10 ms	20 ms
10In	Max. 最慢	150 ms	150 ms	150 ms	150 ms

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cartridge Fuses](#) category:

Click to view products by [HOLLY](#) manufacturer:

Other Similar products are found below :

[5ST250MA-R](#) [5TT3A-R](#) [5TT8A-R](#) [MBO-20](#) [MDM-4/10](#) [MDQ-V-15/100](#) [MDX-1-6/10](#) [MDX-2](#) [MDX-3-2/10](#) [MDX-6-1/4](#) [FLSR-15](#)
[FLSR-30](#) [FRS-1-1/4](#) [FRS-1-6/10](#) [FRS-4/10](#) [H362003](#) [ABC-2](#) [1/2A](#) [12C10X38GI](#) [AGC-15EX](#) [AGC-V-3-12-R](#) [AGY-50](#) [15019-G](#) [MSL-1-](#)
[1/2](#) [MSL-1-1/4](#) [MSL-1/2](#) [MSL-1/4](#) [MSL-3](#) [MSL-3/4](#) [MSL-4](#) [MSL-5](#) [BK1/C436-2A](#) [BK1-GMA-1-6-R](#) [BK1-S505-1-R](#) [BK1-S506-3-15-R](#)
[BK/C515S-250-R](#) [S501-V-10A](#) [301030](#) [303030](#) [FLA10](#) [FLA-4/10](#) [FLNR-5](#) [20.0M6.3X32F](#) [GBB-17-1/2](#) [301001](#) [301020](#) [311008](#)
[31301.5H-XP](#) [313.25](#) [313.75](#)