

## 1. Scope

This specification is applied to Multilayer Ceramic Chip Capacitor (MLCC) for use in electric equipment for the voltage is ranging from 4V to 50V.

The series suitable for general electrics circuit, telecommunications, personal computers and peripheral, power circuit and mobile application. **(This product is compliant with the RoHS.)**

## 2. Parts Number Code

|     |      |     |     |     |     |     |
|-----|------|-----|-----|-----|-----|-----|
| C   | 0805 | B   | 475 | K   | 050 | T   |
| (1) | (2)  | (3) | (4) | (5) | (6) | (7) |

### (1)Product

| Product Code |                                   |
|--------------|-----------------------------------|
| C            | Multilayer Ceramic Chip Capacitor |

### (2)Chip Size

| Code | Length×Width | unit : mm(inch) |
|------|--------------|-----------------|
| 0805 | 2.00× 1.25   | (.079× .049)    |

### (3)Temperature Characteristics

| Code | Temperature Characteristic | Temperature Range | Temperature Coefficient |
|------|----------------------------|-------------------|-------------------------|
| B    | X5R                        | -55℃ ~+85℃        | ± 15%                   |

### (4)Capacitance

unit :pico farads(pF)

| Code | Nominal Capacitance (pF) |
|------|--------------------------|
| 475  | 4,700,000.0              |

※. If there is a decimal point, it shall be expressed by an English capital letter R

### (5)Capacitance Tolerance

| Code | Tolerance | Nominal Capacitance |
|------|-----------|---------------------|
| K    | ± 10.0 %  | More Than 10 pF     |

### (6)Rated Voltage

| Code | Rated Voltage (Vdc) |
|------|---------------------|
| 050  | 50                  |

### (7)Tapping

| Code | Type        |
|------|-------------|
| T    | Tape & Reel |

## 3. Nominal Capacitance and Tolerance

### 3.1 Standard Combination of Nominal Capacitance and Tolerance

| Class | Characteristic | Tolerance    | Nominal Capacitance |
|-------|----------------|--------------|---------------------|
| II    | X5R            | K (± 10.0 %) | E-3, E-6 series     |

### 3.2 E series(standard Number)

| Standard No. | Application Capacitance |     |     |     |     |     |     |     |     |     |     |     |
|--------------|-------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
|              | 1.0                     |     |     | 2.2 |     |     | 4.7 |     |     | 6.8 |     |     |
| E-3          | 1.0                     |     |     | 2.2 |     |     | 4.7 |     |     | 6.8 |     |     |
| E-6          | 1.0                     | 1.5 | 2.2 | 3.3 | 4.7 | 6.8 | 1.0 | 1.5 | 2.2 | 3.3 | 4.7 |     |
| E-12         | 1.0                     | 1.2 | 1.5 | 1.8 | 2.2 | 2.7 | 3.3 | 3.9 | 4.7 | 5.6 | 6.8 | 8.2 |
| E-24         | 1.0                     | 1.2 | 1.5 | 1.8 | 2.2 | 2.7 | 3.3 | 3.9 | 4.7 | 5.6 | 6.8 | 8.2 |
|              | 1.1                     | 1.3 | 1.6 | 2.0 | 2.4 | 3.0 | 3.6 | 4.3 | 5.1 | 6.2 | 7.5 | 9.1 |

## 4. Operation Temperature Range


| Class | Characteristic | Temperature Range | Reference Temp. |
|-------|----------------|-------------------|-----------------|
| II    | X5R (B)        | -55℃ ~ +85℃       | 25℃             |

## 5. Storage Condition

Storage Temperature : 5 to 40℃


Relative Humidity : 20 to 70 %

Storage Time : 12 months max.



**6. Dimensions**
**6.1 Configuration and Dimension :**



Unit:mm

| TYPE | L          | W          | T          | B (min) | BW (min) |
|------|------------|------------|------------|---------|----------|
| 0805 | 2.00± 0.20 | 1.25± 0.20 | 1.25± 0.20 | 0.70    | 0.20     |

**6.2 Termination Type :**


## 7. Performance

| No. | Item                                |             | Specification   |              |                | Test Condition  |          |
|-----|-------------------------------------|-------------|---|--------------|----------------|---|----------|
| 1   | Visual                              |             | No abnormal exterior appearance   |              |                | Visual Inspection   |          |
| 2   | Dimension                           |             | See Page 2  |              |                | Visual Inspection   |          |
| 3   | Insulation Resistance               |             | 500/C Ω min.  |              |                | Applied Voltage: Rated Voltage<br>Charge Time : 60±5 sec.<br>Charge-Discharge current shall be less than 50mA current.  |          |
| 4   | Capacitance                         |             | Within The Specified Tolerance  |              |                | Class II :  |          |
| 5   | Tan δ                               | Class II    | X5R: 10% max.   |              |                | Frequency   | Voltage  |
|     |                                     |             |   |              |                | X5R   | 1KHz±10% |
|     |                                     |             |   |              |                | Perform a heat temperature at 150±5°C for 30min then place room temp. for 24±2hr.   |          |
| 6   | Withstanding Voltage                |             | No dielectric breakdown or mechanical breakdown                           |              |                | 250% of the rated voltage for 1~5 sec.<br>charge/discharge Current is less than 50mA.   |          |
| 7   | Temperature Capacitance Coefficient | Class II    | Char.   | Temp. Range  | Cap. Change(%) | Class II :<br>$\frac{C2 - C1}{C1} \times 100\%$<br>C1:Capacitance At Standard Temperature(25°C)<br>C2: Capacitance At Test Temperature (T2)<br>0.2Vrms shall be applied.                        |          |
|     |                                     |             | X5R   | -55°C ~+85°C | ± 15%          |   |          |
| 8   | Adhesive Strength Of Termination    |             | No indication of peeling shall occur on the terminal electrode.           |              |                | Pull force shall be applied for 10± 1 second.<br>≤ 0603----5N(≒ 0.5 Kg·f)<br>> 0603----10N(≒ 1.0 Kg·f)<br> |          |
| 9   | Resistance to Flexure of Substrate  | Appear-ance | No mechanical damage or capacitance change more than the following table. |              |                | The board shall be bend 1.0mm with a rate of 1.0 mm/sec.<br>  |          |
|     |                                     | C-Meter     | Capacitance Change  |              |                |   |          |
|     |                                     | Char.       | Cap. Change   |              |                |   |          |
|     |                                     | X5R (B)     | ≤ ± 12.5% of initial value  |              |                |   |          |


| No.  | Item                         | Specification  | Test Condition  |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
|--|------------------------------|--|---|------|----------|-----------|---|-----------------------|----|---|----|---|---|-----------------------|----|---|----|---|
| 10   | Solderability                | More than 90% of the terminal surface is to be soldered newly, so metal part does not come out or dissolve. <div style="text-align: center; margin-top: 10px;">  </div> | Solder Temperature : 245± 5℃<br>Dip Time : 5 ± 0.5sec<br>Immersing Speed : 25±10% mm/s<br>Solder : Lead Free Solder<br>Flux : Rosin<br>Preheat : At 80~120 °C for 10~30sec. |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| 11   | Resistance To Soldering Heat | Appearance   | No mechanical damage shall occur.   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| Capacitance  |                              | Class II X5R   | ≤ ±7.5% of initial value  |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| Tan δ Class II   |                              | X5R: 10% max.  |   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| Insulation Resistance  |                              | To satisfy the specified initial value   |   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| Class II capacitor shall be set for 48±4 hours at room temperature after one hour heat treatment at 150 +0/-10℃ before initial measure.<br><br>Preheat : at 150± 10℃ for 60~120sec.<br>Dip : solder temperature of 260± 5℃<br>Dip Time : 10 ± 1sec.<br>Immersing Speed : 25±10% mm/s<br>Flux : Rosin<br><br>Measure at room temperature after cooling for Class II : 48 ± 4 Hours  |                              |  |   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| 12   | Temperature Cycle            | Appearance   | No mechanical damage shall occur.   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| Capacitance  |                              | Class II X5R   | ≤ ±7.5% of initial value  |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| Tan δ Class II   |                              | X5R:10% max.   |   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| Insulation Resistance  |                              | To satisfy the specified initial value   |   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| Class II capacitor shall be set for 48±4 hours at room temperature after one hour heat treatment at 150 +0/-10℃ before initial measure.<br><br>Capacitor shall be subjected to five cycles of the temperature cycle as following: <table border="1" style="margin: 10px auto; border-collapse: collapse;"> <thead> <tr> <th style="width: 5%;">Step</th> <th style="width: 20%;">Temp.(℃)</th> <th style="width: 15%;">Time(min)</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">Min Rated Temp. +0/-3</td> <td style="text-align: center;">30</td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">25</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="text-align: center;">3</td> <td style="text-align: center;">Max Rated Temp. +3/-0</td> <td style="text-align: center;">30</td> </tr> <tr> <td style="text-align: center;">4</td> <td style="text-align: center;">25</td> <td style="text-align: center;">3</td> </tr> </tbody> </table> Measure at room temperature after cooling for Class II : 48 ± 4 Hours |                              |  |   | Step | Temp.(℃) | Time(min) | 1 | Min Rated Temp. +0/-3 | 30 | 2 | 25 | 3 | 3 | Max Rated Temp. +3/-0 | 30 | 4 | 25 | 3 |
| Step   | Temp.(℃)                     | Time(min)  |   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| 1  | Min Rated Temp. +0/-3        | 30   |   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| 2  | 25                           | 3  |   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| 3  | Max Rated Temp. +3/-0        | 30   |   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| 4  | 25                           | 3  |   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| 13   | Humidity                     | Appearance   | No mechanical damage shall occur.   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| Capacitance  |                              | Characteristic   | Cap. Change   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
|  |                              | Class II X5R   | ≤ ±12.5% of initial value   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| Tan δ Class II   |                              | X5R: 20% max.  |   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
|  | Insulation Resistance        | 50/C Ω min.  |   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |
| Class II capacitor shall be set for 48± 4 hours at room temperature after one hour heat treatment at 150 +0/-10 °C before initial measure.<br><br>Temperature : 40± 2℃<br>Relative Humidity : 90 ~ 95%RH<br>Test Time : 500 Hrs Max<br><br>Measure at room temperature after cooling for Class II : 48 ± 4 Hours   |                              |  |   |      |          |           |   |                       |    |   |    |   |   |                       |    |   |    |   |

| No.  | Item                              | Specification         | Test Condition                         |                                    |
|--|-----------------------------------|-----------------------|--|------------------------------------|
| 14   | Humidity Load                     | Appearance            | No mechanical damage shall occur.      |                                    |
|  |                                   | Capacitance           | Characteristic                         | Cap. Change                        |
|  |                                   |                       | Class II X5R                           | $\leq \pm 12.5\%$ of initial value |
|  |                                   | Tan $\delta$ Class II | X5R:20% max.                           |                                    |
| Insulation Resistance  | 25/C $\Omega$ min.                |                       |  |                                    |
| Class II capacitors applied DC voltage of the rated voltage is applied for one hour at maximum operation temperature $\pm 3^\circ\text{C}$ then shall be set for $48 \pm 4$ hours at room temperature and the initial measurement shall be conducted.<br>Applied Voltage : Rated Voltage<br>Temperature : $40 \pm 2^\circ\text{C}$<br>Relative Humidity : 90 ~ 95%RH<br>Test Time : 500 Hrs Max<br>Current Applied : 50 mA Max.<br><br>Measure at room temperature after cooling for Class II : $48 \pm 4$ Hours |                                   |                       |  |                                    |
| 15   | High Temperature Load (Life Test) | Appearance            | No mechanical damage shall occur.      |                                    |
|  |                                   | Capacitance           | Characteristic                         | Cap. Change                        |
|  |                                   |                       | Class II X5R                           | $\leq \pm 12.5\%$ of initial value |
|  |                                   | Tan $\delta$ Class II | X5R:20% max.                           |                                    |
| Insulation Resistance  | 50/C $\Omega$ min.                |                       |  |                                    |
| The capacitors applied DC testing voltage is applied for one hour at maximum operation temperature $\pm 3^\circ\text{C}$ then shall be set for $48 \pm 4$ hours at room temperature and the initial measurement shall be conducted.<br>Applied Voltage: Rated Voltage<br>Temperature: max. operation temperature<br>Test Time : 1000 Hrs Max<br>Current Applied : 50mA Max<br>Measure at room temperature after cooling for Class II : $48 \pm 4$ Hours  |                                   |                       |  |                                    |
| 16   | Vibration                         | Appearance            | No mechanical damage shall occur       |                                    |
|  |                                   | Capacitance           | Within the specified tolerance         |                                    |
|  |                                   | Tan $\delta$ Class II | To satisfy the specified initial value |                                    |
|  |                                   | Insulation Resistance | To satisfy the specified initial value |                                    |
| Solder the capacitor on P.C. board.<br><br>Vibrate the capacitor with amplitude of 1.5mm P-P changing the frequencies from 10Hz to 55Hz and back to 10Hz in about 1 min.<br><br>Repeat this for 2 hours each in 3 perpendicular directions.  |                                   |                       |  |                                    |


Note:

|                           | OUR STANDARD MEASURING INSTRUMENT  |
|---------------------------|--|
| MEASURING INSTRUMENT      | $*C \leq 10\mu\text{f}$<br>4278A 1KHZ/1MHZ CAPACITANCE METER (Agilent)<br>$*C > 10\mu\text{f}$<br>4284A 120HZ/1KHZ CAPACITANCE METER (Agilent) |
| MEASURING MODE            | PARALLEL MODE  |
| RECOMMENDED MEASURING JIG | HP 16334E TEST FIXTURE (Agilent)   |
| STANDARD ENVIRONMENT      | Temperature $25^\circ\text{C}$<br>Relative Humidity $50 \pm 2\%$   |

**Fig.1**  
**P.C. Board for Bending Strength Test**



**Fig.2**  
**Test Substrate**



Unit:mm


| Type | A   | B   | C   |
|------|-----|-----|-----|
| 0201 | 0.2 | 0.9 | 0.4 |
| 0402 | 0.5 | 1.5 | 0.6 |
| 0603 | 1.0 | 3.0 | 1.0 |
| 0805 | 1.2 | 4.0 | 1.6 |
| 1206 | 2.2 | 5.0 | 2.0 |
| 1210 | 2.2 | 5.0 | 2.9 |
| 1808 | 3.5 | 7.0 | 2.5 |
| 1812 | 3.5 | 7.0 | 3.7 |
| 2208 | 4.5 | 8.0 | 2.5 |
| 2211 | 4.5 | 8.0 | 3.0 |
| 2220 | 4.5 | 8.0 | 5.6 |

## 8. Packing

### 8.1 Bulk Packing

According to customer request.

### 8.2 Chip Capacitors Tape Packing



### 8.3 Material And Quantity

| Tape     | 0201                   | 0402                   | 0603/0805              |                     |
|----------|------------------------|------------------------|------------------------|---------------------|
| Material | $T \leq 0.33\text{mm}$ | $T \leq 0.55\text{mm}$ | $T \leq 0.90\text{mm}$ | $T > 0.90\text{mm}$ |
| Paper    | 15,000 pcs/Reel        | 10,000 pcs/Reel        | 4,000 pcs/Reel         | NA                  |
| Plastic  | NA                     | NA                     | NA                     | 3,000 pcs/Reel      |

| Tape     | 1206                   |  |                     |
|----------|------------------------|--|---------------------|
| Material | $T \leq 0.90\text{mm}$ | $0.90\text{mm} < T \leq 1.25\text{mm}$ | $T > 1.25\text{mm}$ |
| Paper    | 4,000 pcs/Reel         | NA                                     | NA                  |
| Plastic  | NA                     | 3,000 pcs/Reel                         | 2,000 pcs/Reel      |

| Tape     | 1808/1210              |  |                     |
|----------|------------------------|--|---------------------|
| Material | $T \leq 1.25\text{mm}$ | $1.25\text{mm} < T \leq 2.40\text{mm}$ | $T > 2.40\text{mm}$ |
| Paper    | NA                     | NA                                     | NA                  |
| Plastic  | 3000 pcs/Reel          | 2000 pcs/Reel                          | 500/1,000 pcs/Reel  |

| Tape     | 1812/2211/2220         |                     | 1825/2225              |                     | 2208                   |
|----------|------------------------|---------------------|------------------------|---------------------|------------------------|
| Material | $T \leq 2.20\text{mm}$ | $T > 2.20\text{mm}$ | $T \leq 2.20\text{mm}$ | $T > 2.20\text{mm}$ | $T \leq 2.20\text{mm}$ |
| Paper    | NA                     | NA                  | NA                     | NA                  | NA                     |
| Plastic  | 1000 pcs/Reel          | 700 pcs/Reel        | 700 pcs/Reel           | 400 pcs/Reel        | 1000 pcs/Reel          |


NA : Not Available


### 8.4 Cover Tape Reel Off Force

#### 8.4.1 Peel-Off Force

$$5 \text{ g}\cdot\text{f} \leq \text{Peel-Off Force} \leq 70 \text{ g}\cdot\text{f}$$

#### 8.4.2 Measure Method




**8.5 Paper Tape**


Unit:mm

| TYPE | A         | B         | C         | D          | E         |
|------|-----------|-----------|-----------|------------|-----------|
| 0201 | 0.37± 0.1 | 0.67± 0.1 | 4.00± 0.1 | 2.00± 0.05 | 2.00± 0.1 |
| 0402 | 0.61± 0.1 | 1.20± 0.1 |           |            | 4.00± 0.1 |
| 0603 | 1.10± 0.2 | 1.90± 0.2 |           |            | 4.00± 0.1 |
| 0805 | 1.50± 0.2 | 2.30± 0.2 |           |            | 4.00± 0.1 |
| 1206 | 1.90± 0.2 | 3.50± 0.2 |           |            | 4.00± 0.1 |
| 1210 | 2.90± 0.2 | 3.60± 0.2 |           |            | 4.00± 0.1 |

| TYPE | F          | G          | H         | I               | t         |
|------|------------|------------|-----------|-----------------|-----------|
| 0201 | 1.75± 0.10 | 3.50± 0.05 | 8.0± 0.30 | φ 1.50 +0.10/-0 | 1.10 max. |
| 0402 |            |            |           |                 |           |
| 0603 |            |            |           |                 |           |
| 0805 |            |            |           |                 |           |
| 1206 |            |            |           |                 |           |
| 1210 |            |            |           |                 |           |

**8.6 Plastic Tape**


Unit:mm


| Type | A       | B       | C        | D         | E        | F         |
|------|---------|---------|----------|-----------|----------|-----------|
| 0805 | 1.5±0.2 | 2.3±0.2 | 4.0± 0.1 | 2.0± 0.05 | 4.0± 0.1 | 1.75± 0.1 |
| 1206 | 1.9±0.2 | 3.5±0.2 |          |           | 4.0± 0.1 |           |
| 1210 | 2.9±0.2 | 3.6±0.2 |          |           | 4.0± 0.1 |           |
| 1808 | 2.5±0.2 | 4.9±0.2 |          |           | 4.0± 0.1 |           |
| 1812 | 3.6±0.2 | 4.9±0.2 |          |           | 8.0± 0.1 |           |
| 1825 | 6.9±0.2 | 4.9±0.2 |          |           | 8.0± 0.1 |           |
| 2208 | 2.5±0.2 | 6.1±0.2 |          |           | 8.0± 0.1 |           |
| 2211 | 3.2±0.2 | 6.1±0.2 |          |           | 8.0± 0.1 |           |
| 2220 | 5.4±0.2 | 6.1±0.2 |          |           | 8.0± 0.1 |           |
| 2225 | 6.9±0.2 | 6.1±0.2 |          |           | 8.0± 0.1 |           |



| Type | G         | H          | I                    | J        | t        | O        |
|------|-----------|------------|----------------------|----------|----------|----------|
| 0805 | 3.5± 0.05 | 8.0± 0.3   | $\varphi$ 1.5+0.1/-0 | 3.0 max. | 0.3 max. | 1.0± 0.1 |
| 1206 |           |            |                      |          |          |          |
| 1210 |           |            |                      |          |          |          |
| 1808 | 5.5± 0.05 | 12.0 ± 0.3 |                      | 4.0 max. |          | 1.5± 0.1 |
| 1812 |           |            |                      |          |          |          |
| 1825 |           |            |                      |          |          |          |
| 2208 |           |            |                      |          |          |          |
| 2211 |           |            |                      |          |          |          |
| 2220 |           |            |                      |          |          |          |
| 2225 |           |            |                      |          |          |          |

### 8.7 Reel Dimensions

Reel Material : Polystyrene



Unit:mm

| Type | A                 | B                | C                 | D                 | E       | W        |
|------|-------------------|------------------|-------------------|-------------------|---------|----------|
| 0201 | $\varphi$ 382 max | $\varphi$ 50 min | $\varphi$ 13± 0.5 | $\varphi$ 21± 0.8 | 2.0±0.5 | 10± 0.15 |
| 0402 |                   |                  |                   |                   |         |          |
| 0603 |                   |                  |                   |                   |         |          |
| 0805 |                   |                  |                   |                   |         |          |
| 1206 |                   |                  |                   |                   |         |          |
| 1210 |                   |                  |                   |                   |         |          |
| 1808 | $\varphi$ 178±0.2 | $\varphi$ 60±0.2 |                   |                   |         | 13±0.3   |
| 1812 |                   |                  |                   |                   |         |          |
| 1825 |                   |                  |                   |                   |         |          |
| 2208 |                   |                  |                   |                   |         |          |
| 2211 |                   |                  |                   |                   |         |          |
| 2220 |                   |                  |                   |                   |         |          |
| 2225 |                   |                  |                   |                   |         |          |

## Precautionary Notes:


### 1. Storage

Store the capacitors where the temperature and relative humidity don't exceed 40°C and 70%RH. We recommend that the capacitors be used within 12 months from the date of manufacturing. Store the products in the original package and do not open the outer wrapped, polyethylene bag, till just before usage. If it is open, seal it as soon as possible or keep it in a desiccant with a desiccation agent.

### 2. Construction of Board Pattern

Improper circuit layout and pad/land size may cause excessive or not enough solder amount on the PC board. Not enough solder may create weak joint, and excessive solder may increase the potential of mechanical or thermal cracks on the ceramic capacitor. Therefore we recommend the land size to be as shown in the following table: 2.1

Size and recommend land dimensions for reflow soldering




| EIA Code | Chip (mm) |      | Land (mm) |         |         |         |         |
|----------|-----------|------|-----------|---------|---------|---------|---------|
|          | L         | W    | A         | B       | C       | D       | E       |
| 0201     | 0.60      | 0.30 | 0.2~0.3   | 0.2~0.4 | 0.2~0.4 | --      | --      |
| 0402     | 1.00      | 0.50 | 0.3~0.5   | 0.3~0.5 | 0.4~0.6 | --      | --      |
| 0603     | 1.60      | 0.80 | 0.4~0.6   | 0.6~0.7 | 0.6~0.8 | --      | --      |
| 0805     | 2.00      | 1.25 | 0.7~0.9   | 0.6~0.8 | 0.8~1.1 | --      | --      |
| 1206     | 3.20      | 1.60 | 2.2~2.4   | 0.8~0.9 | 1.0~1.4 | 1.0~2.0 | 3.2~3.7 |
| 1210     | 3.20      | 2.50 | 2.2~2.4   | 1.0~1.2 | 1.8~2.3 | 1.0~2.0 | 4.1~4.6 |
| 1808     | 4.60      | 2.00 | 2.8~3.4   | 1.8~2.0 | 1.5~1.8 | 1.0~2.8 | 3.6~4.1 |
| 1812     | 4.60      | 3.20 | 2.8~3.4   | 1.8~2.0 | 2.3~3.0 | 1.0~2.8 | 4.8~5.3 |
| 1825     | 4.60      | 6.35 | 2.8~3.4   | 1.8~2.0 | 5.1~5.8 | 1.0~4.0 | 7.1~8.3 |
| 2208     | 5.70      | 2.00 | 4.0~4.6   | 2.0~2.2 | 1.5~1.8 | 1.0~4.0 | 3.6~4.1 |
| 2211     | 5.70      | 2.80 | 4.0~4.6   | 2.0~2.2 | 2.0~2.6 | 1.0~4.0 | 4.4~4.9 |
| 2220     | 5.70      | 5.00 | 4.0~4.6   | 2.0~2.2 | 3.5~4.8 | 1.0~4.0 | 6.6~7.1 |
| 2225     | 5.70      | 6.35 | 4.0~4.6   | 2.0~2.2 | 5.1~5.8 | 1.0~4.0 | 7.1~8.3 |

### 2.2 Mechanical strength varies according to location of chip capacitors on the P.C. board.







Design layout of components on the PC board such a way to minimize the stress imposed on the components, upon flexure of the boards in depanelization or other processes.

Component layout close to the edge of the board or the "depanelization line" is not recommended.

Susceptibility to stress is in the order of: a>b>c and d>e





**2.3 Layout Recommendation**

| Example        | Use of Common Solder Land   | Solder With Chassis  | Use of Common Solder Land With Other SMD  |
|----------------|---|--|---|
| Need to Avoid  |  |  |  |
| Recommendation |  |  |  |

**3. Mounting**

3.1 Sometimes crack is caused by the impact load due to suction nozzle in pick and place operation.

In pick and place operation, if the low dead point is too low, excessive stress is applied to component. This may cause cracks in the ceramic capacitor, therefore it is required to move low dead point of a suction nozzle to the higher level to minimize the board warp age and stress on the components. Nozzle pressure is typically adjusted to 1N to 3N (static load) during the pick and place operation.


**3.2 Amount of Adhesive**


Example : 0805 & 1206


|   |                              |
|---|------------------------------|
| a | 0.2mm min.                   |
| b | 70 ~ 100 μm                  |
| c | Do not touch the solder land |

## 4. Soldering

### 4.1. Wave Soldering

Most of components are wave soldered with solder at 230 to 250°C. Adequate care must be taken to prevent the potential of thermal cracks on the ceramic capacitors. Refer to the soldering methods below for optimum soldering benefits.

#### Recommend flow soldering temperature Profile



| Soldering Method | Change in Temp.( °C) |
|------------------|----------------------|
| 1206 and Under   | Δ T ≤ 100~130 max.   |

To optimize the result of soldering, proper preheating is essential:

- 1) Preheat temperature is too low
  - a. Flux flows to easily
  - b. Possibility of thermal cracks
- 2) Preheat temperature is too high
  - a. Flux deteriorates even when oxide film is removed
  - b. Causes warping of circuit board
  - c. Loss of reliability in chip and other components


#### Cooling Condition:

Natural cooling using air is recommended. If the chips are dipped into a solvent for cleaning, the temperature difference (Δ T) between the solvent and the chips must be less than 100°C.

### 4.2 Reflow Soldering

Preheat and gradual increase in temperature to the reflow temperature is recommended to decrease the potential of thermal crack on the components. The recommended heating rate depends on the size of component, however it should not exceed 3°C/Sec.

#### Recommend reflow profile for Lead-Free soldering temperature Profile (MIL-STD-202G #210F)




#### ※ The cycles of soldering : Twice (max.)

| Soldering Method | Change in Temp.( °C) |
|------------------|----------------------|
| 1206 and Under   | Δ T ≤ 190 °C         |
| 1210 and Over    | Δ T ≤ 130 °C         |

## 4.3 Hand Soldering

Sudden temperature change in components, results in a temperature gradient recommended in the following table, and therefore may cause internal thermal cracks in the components. In general a hand soldering method is not recommended unless proper preheating and handling practices have been taken. Care must also be taken not to touch the ceramic body of the capacitor with the tip of solder iron.




| Soldering Method | Change in Temp.( °C)                        |
|------------------|---|
| 1206 and Under   | $\Delta T \leq 150\text{ }^{\circ}\text{C}$ |
| 1210 and Over    | $\Delta T \leq 130\text{ }^{\circ}\text{C}$ |

### How to Solder Repair by Solder Iron


- 1) Selection of the soldering iron tip
  - The required temperature of solder iron for any type of repair depends on the type of the tip, the substrate material, and the solder land size.
- 2) recommended solder iron condition
  - a.) Preheating Condition : Board and components should be preheated sufficiently at 150°C or over, and soldering should be conducted with soldering iron as boards and components are maintained at sufficient temperatures.
  - b.) Soldering iron power shall not exceed 30 W.
  - c.) Soldering iron tip diameter shall not exceed 3mm.
  - d.) Temperature of iron tip shall not exceed 350°C to perform the process within 5 seconds. (refer to MIL-STD-202G)
  - f.) Do not touch the ceramic body with the tip of solder iron. Direct contact of the soldering iron tip to ceramic body may cause thermal cracks.
  - g.) After soldering operation, let the products cool down gradually in the room temperature.

## 5. Handling after chip mounted

5.1 Proper handling is recommended, since excessive bending and twist of the board, depends on the orientation of the chip on the board, may induce mechanical stress and cause internal crack in the capacitor.



5.2 There is a potential of crack if board is warped due to excessive load by check pin




5.3 Mechanical stress due to warping and torsion.



- (a) Crack occurrence ratio will be increased by manual separation.
- (b) Crack occurrence ratio will be increased by tensile force , rather than compressive force.

× :Tensile Stress

○ :Compressive Stress




Capacitor Stress Analysis




**6. Handling of Loose Chip Capacitor**

6.1 If dropped the chip capacitor may crack.



6.2 In piling and stacking of the P.C. boards after mounting for storage or handling, the corner of the P.C. board may hit the chip capacitor mounted on another board to cause crack.



**7. Safekeeping condition and period**

For safekeeping of the products, we recommend to keep the storage temperature between +5 to +40°C and under humidity of 20 to 70% RH. The shelf life of capacitors is 12 months.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Multilayer Ceramic Capacitors MLCC - SMD/SMT](#) category:*

*Click to view products by [Holy Stone](#) manufacturer:*

Other Similar products are found below :

[M39014/02-1225V](#) [M39014/22-0631](#) [D55342E07B523DR-T/R](#) [NCA1206X7R103K50TRPF](#) [NCA1206X7R104K16TRPF](#) [NIN-FB391JTRF](#)  
[NIN-FC2R7JTRF](#) [NMC0201X5R474K4TRPF](#) [NMC0402NPO220J50TRPF](#) [NMC0402X5R105K6.3TRPF](#) [NMC0402X5R224K6.3TRPF](#)  
[NMC0402X7R103J25TRPF](#) [NMC0402X7R153K16TRPF](#) [NMC0603NPO1R8C50TRPF](#) [NMC0603NPO201J50TRPF](#)  
[NMC0603NPO330G50TRPF](#) [NMC0603X5R475M6.3TRPF](#) [NMC0805NPO270J50TRPF](#) [NMC0805NPO820J50TRPF](#)  
[NMC0805X7R224K25TRPF](#) [NMC1206X7R102K50TRPF](#) [NMC-H0805X7R472K250TRPF](#) [NMC-L0402NPO7R0C50TRPF](#) [NMC-](#)  
[L0603NPO2R2B50TRPF](#) [NMC-P0805NPO221J500TRPLPF](#) [NMC-Q0402NPO8R2D200TRPF](#) [C1206C101J1GAC](#) [C1608C0G2A221J](#)  
[C1608X7R1E334K](#) [C2012C0G2A472J](#) [2220J2K00562KXT](#) [1812J2K00332KXT](#) [CDR31BX103AKWR](#) [CDR33BX104AKUR](#)  
[CDR33BX683AKUS](#) [CGA2B2C0G1H010C](#) [CGA2B2C0G1H040C](#) [CGA2B2C0G1H050C](#) [CGA2B2C0G1H060D](#) [CGA2B2C0G1H070D](#)  
[CGA2B2C0G1H120J](#) [CGA2B2C0G1H151J](#) [CGA2B2C0G1H181JT0Y0F](#) [CGA2B2C0G1H1R5C](#) [CGA2B2C0G1H2R2C](#)  
[CGA2B2C0G1H390J](#) [CGA2B2C0G1H391J](#) [CGA2B2C0G1H3R3C](#) [CGA2B2C0G1H680J](#) [CGA2B2C0G1H6R8D](#)