

BASIC, TOGGLE & ROCKER SWITCHES

Product Range Guide

Honeywell

FOR INNOVATION THAT'S WELL APART, THERE'S ONLY HONEYWELL.

With more than 50,000 products ranging from snap-action, limit, toggle, and pressure switches to position, speed, pressure, and airflow sensors, Honeywell has one of the broadest sensing and switching portfolios.

Honeywell sensor, switch, and control components are tailored to exact specifications for stronger performance, longer productivity, and increased safety. Enhanced accuracy and durability are built into every part, improving output and endurance. For our customers, this can reduce expenditures and operational costs. Our global footprint and channels help to competitively price such components for your chosen application and provide immediate technical support.

While Honeywell's switch and sensor solutions are suitable for a wide array of basic and complex applications, our custom-engineered solutions offer enhanced precision, repeatability, and ruggedness. We offer domain knowledge and technology resources, along with a close working relationship, to develop and deliver cost-effective, individually tailored solutions. Whether clean-slate development or simple modifications to an existing design are needed, our expertly engineered solutions help to meet the most stringent requirements with world-class product designs, technology integration, and customer-specific manufacturing.

Global service, sourcing, and manufacturing. Industry-leading engineers. Value-added assemblies and solutions. A one-stop, full-service, globally competitive supplier.

TABLE OF CONTENTS

Subminiature Sealed Basic Switches	3
Subminiature Unsealed Basic Switches	4-5
Miniature Sealed and Unsealed Basic Switches	6-7
Large Basic & Specialty Switches	8-9
Speciality Aerospace Basic Switches	10
Unlit and Lit Pushbuttons	11
Sealed and Standard Toggles and Rockers	12-13



SUBMINIATURE SEALED BASIC SWITCHES

Although small in size, the HD, HD1, ZD and ZW Series are rated for controlling electrical loads ranging from logic-level to power-duty switching. When provided with integral wire leads, switches are sealed to IP67 and suitable for applications where the switch assembly would be exposed to liquids or environmental particulate contaminants from indoor or outdoor use.



SERIES	HD	HD1	ZD	ZW
Type	standard sealed	standard sealed	standard sealed	standard sealed
Amp rating	0.1 A & 3 A	0.1 A	0.1 A, 3 A	0.1 A, 6 A
Circuitry	SPDT, SPST-NO, SPST-NC	SPNC, SPNO	SPDT	SPDT, SPNO, SPNC
Operating force	130 gf max.	100 gf max., 130 gf max., 200 gf max.	130 gf to 195 gf	1.94 oz to 7.16 oz
Terminations	wired: straight, right, left solder: 2,5 mm x 2,5 mm with 1,3 mm dia. hole pcb: 0,6 mm x 3,5 mm pcb: left corner, right corner long solder: with 1,3 mm dia. hole straight solder: 2,0 mm x 2,5 mm	wired: downward, side pcb: straight, angle long solder clips special	solder, pcb straight, pcb left angle, pcb right angle, pre-wired	quick connect, solder, cable bottom/end, cable side exit
Actuators/levers	pin plunger, lever, simulated roller lever, formed lever	pin plunger, special	pin plunger, straight, sim. roller	pin plunger, straight, roller, sim. roller
Voltage	125 Vac, 12 Vdc	12 Vdc	125 Vac, 12 Vdc	125 Vac, 250 Vac
Approvals	UL, cUL, ENEC, CQC	UL, cUL, ENEC, CQC	UL, cUL, CE, ENEC	UL, cUL, CE, ENEC
Operating temperature range	terminal type S: -40°C to 125°C [-40°F to 257°F] wired type S (UL 1007/UL 1061): -20°C to 80°C [-4°F to 176°F] wired type S (UL 1430): -20°C to 85°C [-4°F to 185°F] wired type S (AVSS): -40°C to 85°C [-40°F to 185°F]	terminal type: -40°C to 85°C [-40°F to 185°F] wired type (UL 1007/UL 1061): -20°C to 80°C [-4°F to 176°F] wired type (UL 1430): -20°C to 85°C [-4°F to 185°F] wired type (AVSS): -40°C to 85°C [-40°F to 185°F]	-40°C to 85°C [-40°F to 185°F]	-25°C to 70°C [-13°F to 158°F] (with wires) -25°C to 120°C [-13°F to 248°F] (without wires)
Contacts	silver alloy	silver-plated copper alloy	silver, gold-plated silver	silver, gold-plated silver
Housing material	nylon	PBT	PBT polyester	PBT (polyester)
Measurements	Various: 14,70 mm W x 5,40 mm D [0.579 in W x 0.213 in D]	Various: 8,30 mm W x 5,30 mm D [0.327 in W x 0.209 in D]	10,6 mm H x 6,35 mm W x 19,8 mm L [0.42 in H x 0.25 in W x 0.78 in L]	9,0 mm H x 6,4 mm W x 19,8 mm L [0.36 in H x 0.25 in W x 0.78 in L]
Features	>500K mechanical operations; integrated pillars and mounting holes in switch housing; wiring, molding, and connector value-added capabilities available	slow-acting switching mechanism; integrated pillars and mounting holes in switch housing; wiring, molding, and connector value-added capabilities available	low energy or power-duty electrical ratings; gold-plated or silver contacts; PBT polyester housing material	IP67 available; low energy or power-duty electrical ratings; gold-plated or silver contacts; BT polyester housing material

SUBMINIATURE UNSEALED BASIC SWITCHES

The package size of the subminiature switch is ideal for applications where space on the equipment is at a premium. The overall length is approximately 20 mm [0.78 in]. As with all snap-action switches, the audible click when actuated promotes ease of installation and set-up of the switches. A wide variety of integral stainless steel levers are available and when combined with the subminiature package size, may adapt the switch to a wide variety of applications.



SERIES	SM	SX	ZM
Type	premium	premium	standard (coil internal spring)
Amp rating	0.1 A to 11 A	1 A to 7 A	0.1 A, 5 A, 10.1 A
Circuitry	SPDT	SPDT, SPNO	SPST, SPDT, SPNO
Operating force	0.04 oz to 2 oz	0.71 oz to 6 oz	0.18 oz to 8.78 oz
Terminations	quick connect, solder, pcb	quick connect, solder, pcb	quick connect, solder, pcb
Actuators/levers	pin plunger, straight, roller, sim. roller, paddle	pin plunger, straight, roller, sim. roller, offset flag, crossed roller	pin plunger, straight, roller, sim. roller
Voltage	115 Vac, 125 Vac, 250 Vac, 30 Vdc	125 Vac, 250 Vac, 28 Vdc	125 Vac, 250 Vac, 30 Vdc
Approvals	UL, CSA, ENEC, CE	UL, CSA, ENEC, CE	UL, CSA, CE
Operating temperature range	-55°C to 121°C [-67°F to 250°F] high temperature options to 204°C [400°F]	-55°C to 121°C [-67°F to 250°F] high temperature options to 204°C [400°F]	-40°C to 120°C [-40°F to 248°F]
Contacts	silver, gold	silver, gold	silver, gold-plated silver, silver-tin-indium oxide
Housing material	phenolic	phenolic	polyamide (nylon)
Measurements	12,7 mm H x 6,35 mm W x 20,3 mm L [0.5 in H x 0.25 in W x 0.8 in L]	12,7 mm H x 6,35 mm W x 20,3 mm L [0.5 in H x 0.25 in W x 0.8 in L]	10,6 mm H x 6,4 mm W x 19,0 mm L [0.42 in H x 0.25 in W x 0.75 in L]
Features	extended operating life; elongated mounting holes; MIL-PRF-8805 qualified listings available	extended operating life; elongated mounting holes; MIL-PRF-8805 qualified listings available	low energy or power-duty electrical contacts

MINIATURE SEALED AND UNSEALED BASIC SWITCHES


Honeywell's premium miniature sealed and unsealed basic switches have been designed for long-term reliability, up to 10 million cycles. These switches incorporate a snap-spring mechanism with more than 60 years of proven service and a high strength thermoplastic housing for durability. Available with custom-engineered solutions and multiple lever/termination options, Honeywell also makes available switches with RAST connectors.



SERIES	V15W WATERTIGHT	V15W2 EXPLOSION-PROOF	V7
Sealing	sealed	sealed	unsealed
Type	watertight	zone 2 hazardous area rated	premium
Amp rating	0.1 A, 5 A, 10 A	5 A, 1/10 HP @ 125 Vac/250 Vac	0.1 A to 25 A
Circuitry	SPDT, SPNO, SPNC	SPDT, SPNO, SPNC	SPDT, SPNO, SPNC
Operating force	15 g, 25 g, 50 g, 100 g, 200 g	100 g, 200 g	0.7 oz max. to 14.6 oz max.
Terminations	preleaded; terminals: 4,8 mm x 0,8 mm or 4,8 mm x 0,5 mm	quick connect: 4,8 mm x 0,5 mm	quick connect, pc board, pcb str
Actuators/levers	pin plunger, straight, roller, sim. roller	pin plunger, roller plunger; other actuators/levers available for special order	pin plunger, straight, roller, sim.
Voltage	125 Vac, 250 Vac, 30 Vdc, 48 Vdc	125 Vac, 250 Vac	125 Vac, 250 Vac, 277 Vac
Approvals	UL, cUL, ENEC, CQC	UL, cUL, ENEC, CQC, IEC Ex	UL, CSA, ENEC
Operating temperature range	-40°C to 85°C [-40°F to 185°F]	-25 °C to 85 °C [-13 °F to 185 °F]	-40°C to 150°C [-40°F to 302°F]
Contacts	silver nickel, gold-plated option	silver alloy, gold-plated thermal alloy	silver, silver cadmium oxide, gold
Housing material	PBT polyester thermoplastic	PBT polyester thermoplastic	PCT polyester thermoplastic
Measurements	15,9 mm H x 10,3 mm W x 33 mm L [0.63 in H x 0.41 in W x 1.3 in L]	15,9 mm H x 10,3 mm W x 33 mm L [0.63 in H x 0.41 in W x 1.3 in L]	15,9 mm H x 10,2 mm W x 28,8 mm L [0.63 in H x 0.4 in W x 1.14 in L]
Features	designed for harsh-duty, wash down areas; high sealing capability with an IP67 rating (pre-leaded only)	approved for use in Zone 2 hazardous locations with an IP67 rating (pre-leaded only)	extended mechanical and electrical life; wide operating temperature range; custom engineered solutions

LARGE BASIC & SPECIALTY SWITCHES AND ACCESSORIES

Often ideal for high cost-of-failure applications. Low operating force and differential travel. Current ratings from 10 A to 25 A. Designed to withstand 100K operations at full load or 10M for mechanical life. Have been used in a variety of applications including irrigation, transportation, medical/dental, valves, office equipment, presses, machine tools, and HVAC.




SERIES	BZ/BA/BM/BE	DT	MT	3
Type	premium large basic	specialty	specialty	sp
Amp rating	15 A (BZ), 22 A (BM), 20 A (BA), 25 A (BE)	10 A	10 A	15
Circuitry	SPDT	DPDT	SPDT	tw
Operating force	1.0 oz to 28 oz	7.0 oz to 10.0 oz	2.0 oz to 18 oz	7.
Terminations	quick connect, solder, screw	screw	screw	sc
Actuators/levers	pin plunger, overtravel plunger, straight, roller, flexible roller leaf, flexible leaf	pin plunger, straight, roller	pin plunger, straight, roller	pin
Voltage	115 Vac, 125 Vac, 250 Vac	250 Vac, 28 Vdc	125 Vac, 125 Vdc	48
Approvals	UL, CSA, ENEC, CE (varies by model)	UL, CSA	UL, CSA	UL
Operating temp. range	-55°C to 85°C [-67°F to 185°F] 121°C [250°F] and 204°C [400°F] options available	-55°C to 85°C [-67°F to 185°F]	-55°C to 82°C [-67°F to 180°F]	-5 [-6
Contacts	silver, silver cadmium oxide	silver	silver	sil
Housing material	general purpose phenolic	general purpose phenolic	arc resistant melamine	ge
Measurements	25,4 mm H x 17,8 mm W x 50,8 mm L [1.0 in H x 0.7 in W x 2.0 in L]	25,4 mm H x 17,8 mm W x 50,8 mm L [1.0 in H x 0.7 in W x 2.0 in L]	25,4 mm H x 17,8 mm W x 50,8 mm L [1.0 in H x 0.7 in W x 2.0 in L]	25 x C
Features	worldwide standard "large basic" switch; low operating force and travel; extended mechanical life; momentary or maintained actions	mounting interchangeability with BZ Series switches; permits several wiring combinations	mounting interchangeability with BZ/BA Series switches; arc-extinguishing design in contact area; arc-resistant case	do life of



SERIES	8MA1	8MA2	17MA1-B	3F
Type	adjustable mounting bracket	adjustable mounting bracket	conversion mounting bracket	die- (sid
Description	adjustment slot on the left	adjustment slot on the right	-	mo side [0.1 25, [1.0
Housing material	steel	steel	corrosion-resistant metal	die-
Measurements	60,2 mm W x 21,3 mm H x 7,4 mm D [2.37 in W x 0.84 in H x 0.29 in D]	60,2 mm W x 21,3 mm H x 7,4 mm D [2.37 in W x 0.84 in H x 0.29 in D]	66,8 mm W x 19,0 mm D [2.63 in W x 0.75 in D]	74, x 25 1.6
Features	sturdy plated steel construction; fast, easy screwdriver adjustment; can be used with all standard basic switches		converts standard basic switches from side to top mount; snaps into mounting holes without tools	prot term

SPECIALTY AEROSPACE BASIC SWITCHES

Sealed switches are snap-action precision switches enclosed within a corrosion-resistant housing that seals the switch contacts from contamination. These sealed switches have often been used in aerospace, ordnance, industrial, marine, and transportation applications.



SERIES	SE/XE	HM	HS
Type	anodized aluminum	stainless steel	stainless steel, phenolic
Sealing	MIL-PRF-8805, symbol 3, watertight	MIL-PRF-8805, symbol 5, hermetic	MIL-PRF-8805, symbol 5, hermetic
Operating temperature range	-53°C to 105°C [-65°F to 221°F]	-65°C to 121°C [-85°F to 250°F] high temp available: 500°F	-54°C to 121°C [-65°F to 250°F]
Actuators/levers	auxiliary actuators available	integral lever; aux. actuators: leaf, roller leaf, straight, roller lever	integral lever
Termination	solder, leadwire	solder, leadwire	screw, leadwire
Circuitry	SPDT	SPDT	SPDT
Contacts	silver, gold, bifurcated gold	silver, gold, bifurcated gold	silver
Amp rating	0.5 A to 7 A	0.5 A to 3 A	1 A to 25 A
Approvals	CE, UL/CSA, MIL-PRF-8805 (selected listings)	MIL-PRF-8805 (select listings qualified)	UL, CSA, MIL-PRF-8805 (select listings qualified)
Measurements	SE: 19,05 mm H x 8,64 mm W x 22,35 mm L [0.75 in H x 0.34 in W x 0.88 in L] XE: 19,05 mm H x 8,13 mm W x 15,75 mm L [0.75 in H x 0.32 in W x 0.62 in L]	12,7 mm H x 6,35 mm W x 20,3 mm L [0.5 in H x 0.25 in W x 0.8 in L]	25,4 mm H x 17,8 mm W x 50,8 mm L [1.0 in H x 0.7 in W x 2.0 in L]
Features	watertight and military standard construction per MIL-PRF-8805; corrosion-resistant aluminum housing	hermetically sealed per MIL-PRF-8805; high temperature construction; reduced sensitivity to changes in altitude or pressure	hermetically sealed per MIL-PRF-8805; high temperature construction; reduced sensitivity to changes in altitude or pressure

LIT & UNLIT PUSHBUTTON SWITCHES



Lighted or unlighted, pushbuttons are designed to enhance manual operation with a flexible and attractive interface. Snap-in surface products are easy to apply, operate, and maintain. Potential applications include control boards and panels found in industrial machinery, instrumentation, flight decks, and test equipment.

SERIES	PB
Panel area	20,32 mm x 35,56 mm [0.8 in x 1.4 in] max. (behind panel)
Display	8,1 mm [0.32 in] and other button sizes
Colored buttons	available
Mounting	threaded bushing
Termination	solder, H58, quick connect
Sealing	panel-sealed and hermetic-sealed switches available
Electrical	0.5 A to 5 A; 125/250 Vac, 28 Vdc
Approvals	UL, CSA, some meet MIL-PRF-8805/23
Features	up to four poles - double throw; compact size




SERIES	AML	MML
Panel area	20,5 mm [0.80 in] square; 20,5 mm x 30,5 mm [0.80 in x 1.20 in] rectangular	15 mm x 9,9 mm [0.59 in x 0.39 in] rectangular; 17,8 mm x 12,7 mm [0.70 in x 0.50 in] rectangular; 9,9 mm [0.39 in] square
Display	15,0 mm [0.59 in] square; 15 mm x 25 mm [0.59 in x 0.99 in] buttons	13 mm x 6,6 mm [0.51 in x 0.26 in] rectangular; 6,8 mm [0.27 in] square
Illumination	incandescent T-1-3/4 lamps – 6 V, 14 V, 28 V; LEDs – 2 V, 4 V, 5 V, 10 V, 15 V; neon lamps – 125 V, 250 V	T-1 – 5 V, 28 V; incandescent T-1-3/4 LEDs – 2 V, 2.5 V, 3 V
Behind panel	43,1 mm [1.7 in]	17,0 mm [0.67 in]
Mounting	snap-in individual, strip, matrix, sub-panel, pcb	snap-in individual, strip, sub-panel, pcb, bezel
Termination	solder, quick connect, pc board, push-on	solder, quick connect, printed wiring board
Sealing	optional panel seal	–
Electrical	electronic control: up to 3 A, 125 Vac	silver contacts: up to 1 A, 125 Vac; 6 A @ 125 Vac, 250 Vac; 2 A @ 30 Vdc; 1 A @ 125 Vdc; 1/10 hp @ 125 Vac; gold contacts: up to 0.25 A, 30 Vdc; UL rating 0.10 A
Approvals	UL, CSA, VDE, CE (selected products)	UL, CSA
Features	silver or gold contacts; full guard bezel option; lamp circuit independent of switch circuit	silver or gold contacts; pwb or panel-mount switches; multi-unit strip mounting available

SEALED & STANDARD TOGGLE & ROCKER SWITCHES

Hermetic and environmentally sealed toggle switches offer enhanced reliability with MICRO SWITCH technology. Can be used in a variety of applications where a panel-mount switch with an environment-proof rating is needed, including industrial equipment, military and commercial aviation, agriculture, process control, and medical.



SERIES	AT	TS	TW	E
Type	stainless steel toggle	stainless steel, phenolic toggle	miniature stainless steel toggle	ma
Sealing	MIL-PRF-8805/26/98	-	qualified to MIL-DTL-83781	mo
Operating temp.	various	-54°C to 71°C [-65°F to 160°F]	-65°C to 71°C [-85°F to 160°F]	-6
Actuator/lever	standard, locking, tab, special design	standard	standard, locking, special design, tab	sta
Action	2-position, momentary & maintained	2- or 3-position, momentary & maintained	2- or 3-position, momentary & maintained	2-
Mounting	15/32 in bushing, 1/4 in bushing, 3-hole, above panel	15/32 in bushing	bushing 15/32 in or 1/4 in	bu
Termination	solder, solder T2, screw, quick connect, leadwire, H58	solder, screw, quick connect	IWTS, solder, screw, quick connect, H58, T2	scr
Circuitry	SPDT, DPDT, DPNO, 3PDT, 4PDT, 6PDT, 8PDT, 10PDT	SPDT, DPDT	SPST, SPDT, DPST, DPDT	SP
Contacts	silver, gold, bifurcated gold	silver tin oxide and indium oxide	fine silver, gold-plated	fin
Amp rating	0.01 A to 5 A (resistive)	0.4 A to 10 A @ 126 Vac to 277 Vac 0.4 A to 20 A @ 0.5 Vac to 125 Vac	0.1 A to 5.0 A @ 0.5 Vdc to 28 Vdc; 0.1 A to 5.0 A @ 0.5 Vac to 115 Vac	7 A
Measurements	various	various	49,78 mm H x 14,61 mm W x 14,61 mm D [1.96 in H x 0.575 in W x 0.575 in D]	51 x 1
Approvals	qualified to MIL-PRF-8805/26/98	UL, CSA, CE	UL, qualified to MIL-DTL-83781	qu
Features	choice of sealed bushing; short behind panel depth	optional step-case design provides added space between terminals to prevent shorting	saves space and weight; sealed bushing versions	ho me



SERIES	AML	TP
Housing type	non-lighted, rectangle; 1 lamp circuit, rectangle; 2 lamp circuits, rectangle	non-lighted, rectangle
Circuitry	SPST, SPDT, DPST, DPST, 4PDT	SPST, SPDT, DPDT, 4PDT
Action	2 position, 3 position	2 position, 3 position
Mounting	snap-in panel	flush mount; above panel mount
Termination	solder, quick connect, printed circuit, push-on	screw
Ampere/voltage range	0.4 A to 2 A @ 0.5 Vdc to 30 Vdc; 0.4 A to 3 A @ 0.5 Vac to 125 Vac; 0.4 A to 2 A @ 0.5 Vac to 250 Vac	silver alloy
Light	no lamp installed; incandescent 6 V, 14 V, 28 V; neon	-
LED/neon color	red, yellow, green	-
Measurements	various	various
Approvals	-	UL recognized, CSA certified, CE approved
Features	silver and gold contacts; available with or without diode protection for LEDs; lamp circuit independent of switch circuit	2- or 3-position operating action; various button colors; dust and splash-proof sealed; silver or gold contacts available; can be provided with or without buttons

WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship during the applicable warranty period. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgment or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items that Honeywell, in its sole discretion, finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While Honeywell may provide application assistance personally, through our literature and the Honeywell web site, it is buyer's sole responsibility to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this writing. However, Honeywell assumes no responsibility for its use.

FOR MORE INFORMATION

Honeywell Sensing and Internet of Things services its customers through a worldwide network of sales offices and distributors. For application assistance, current specifications, pricing, or the nearest Authorized Distributor, visit sensing.honeywell.com or call:

USA/Canada	+302 613 4491
Latin America	+1 305 805 8188
Europe	+44 1344 238258
Japan	+81 (0) 3-6730-7152
Singapore	+65 6355 2828
Greater China	+86 4006396841

Honeywell Sensing and Internet of Things

830 East Arapaho Road
Richardson, TX 75081
sensing.honeywell.com

001032-14-EN | 14 | 09/20
© 2020 Honeywell International Inc. All rights reserved.

Honeywell

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Basic / Snap Action Switches](#) category:

Click to view products by [Honeywell](#) manufacturer:

Other Similar products are found below :

[5SM901-S12](#) [5SM9-S12N195](#) [602EN532](#) [602EN535-RB](#) [602HE5-RB1](#) [604HE162](#) [604HE223-6B](#) [624HE17-RB](#) [6HM82](#) [6HM89](#) [6SE1](#)
[6SX1-H58](#) [70500216](#) [70599106](#) [MBD5B1](#) [MBH2731](#) [73-316-0012](#) [EXD-AR20](#) [79211923](#) [79218589](#) [7AS12](#)
[MIL30126AB6BBMD4A12XAU](#) [ML-1155](#) [ML-1376](#) [831010C3.0](#) [831090C2.EL](#) [83131904](#) [84212012](#) [8AS239](#) [8HM73-3](#) [8SX26-H33](#)
[914CE1-6G](#) [PL-100](#) [11SM1077-H4](#) [11SM1077-H58](#) [11SM1-TN107](#) [11SM405](#) [11SM8423-H2](#) [11SX37-T](#) [11SX48-H58](#) [11SM2442-T](#)
[11SM76-T](#) [11SM77-H58](#) [11SM77-T](#) [11SM863-T](#) [11SM866](#) [A7CN-1M-1-LEFT](#) [A831700C7.0](#) [121EN187-R](#) [121EN188-R](#)