Manual Switches

Pushbutton Switches

FEATURES

- Compact size
- Up to 4-poles
- Sealed versions

TOUCH FEEDBACK SWITCHES



ORDER GUIDE

Momentary and alternate action switches.

Button Color	2 Mom. Action	No. of SPDT Circuits 2 Alt. Action	4 Mom. Action
Black	2PB11-T2	82PB19-T2	_
	2PB732-T2 (M8805/23-001)	_	4PB714-T2 (M8805/23-003)
Red	2PB12-T2	_	_
	2PB717-T2 (M8805/23-002)	_	_
Green	2PB273-T2	_	_

SHORT TRAVEL SWITCHES



ORDER GUIDE

Momentary action switches.

Button	No. of SPI	OT Circuits 3
Black	2PB7	3PB7

These switches resemble the touch-feedback design, but have a flexible leaf actuator for lower operating force and shorter button travel.

PANEL SEALED SWITCHES





An elastomer seal is bonded between actuating plunger and button collar. An Oring seals the button assembly to the panel front.

Two-piece design enables button to be mounted separately. After switch unit is wired, it snaps into place from behind panel.

ORDER GUIDE

Momentary action switches.

Button Color	Collar Type	No. of SPE 1	OT Circuits 2
Black	Hex	1PB4	2PB4
Black	Round	1PB42	_
Red	Round	1PB43	_

ELECTRICAL RATINGS

(Except 15PB and 700PB)

30 VDC: 5 amps, res., sea level or 50,000 ft.; 3 amps, ind., sea level; 2.5 amps ind., 50,000 ft; 24 amps, max. inrush.

UL and CSA rating for basic switches: 5 amps, 125 or 250 VAC.

Manual Switches

Pushbutton Switches

WATERTIGHT SWITCH



ORDER GUIDE

Momentary action switches.

Has knurled chrome-finished facenut.

Button Color	No. of SPDT Circuits
Black	2PB901-T2

Facenut-to-panel, button-to-facenut, and bushing-to-facenut, sealing helps prevent entry of water from behind panel, up and over bushing wall. Switch units potted in corrosion resistant metal enclosure. Meets submergence requirements of MIL-STD-108 (up to 10 PSI water pressure for one hour).

HERMETICALLY SEALED SWITCHES



These pushbuttons are equipped with HM hermetically sealed switch units, which have metal-to-metal fusion around the cover, actuator base, and mounting holes. Terminals are sealed glass-to-metal.

Vapor-proof construction enables use in damp locations without condensation on contacts. External parts corrosion resistant per MIL-S-8805. Meets explosion-proof requirements of MIL-S-8805.

ORDER GUIDE

Momentary action switches.

Button	No. of SPDT Circuits		
Color	2	4	
Black	702PB1	704PB1	

MINIATURE SIZE SWITCHES





ORDER GUIDE

Momentary action switches.

	No. of SPDT Circuits		
Button	1	2	
Steel*	1PB5	_	
White Plastic	_	15PB2	

^{*} Steel button enables use under hinged plates or paddle levers, in addition to manual operation.

ELECTRICAL RATINGS — 700PB and 15PB

700PB (With hermetically sealed switch units):

28 VDC and 115 VAC, 400 HZ: 3 amps, ind., 5 amps, res.

15PB:

30 VDC and 115 VAC: 2 amps, ind., 5 amps. res.; 1.0 amp, lamp load.

1PB5

250 VAC: 5 amps.


30 VDC: 5 amps, res., sea level or 50,000 ft.; 3 amps, ind., sea level; 2.5 amps ind., 50,000 ft.; 24 amps, max. inrush.

ushbuttons

Pushbutton Switches


MOUNTING DIMENSIONS (For reference only)


Touch Feedback Switches




		2-Pole	4-Pole
Dim. "A"	Mom.	16,8/.66	30,0/1.18
(max.)	Alt. Act.	17,3/.68	30,5/1.20
Dim. "B"	Mom.	26,7/1.05	26,7/1.05
	Alt. Act.	33,0/1.34	33,0/1.34

Panel Sealed Switches





Short Travel Switches



	2-Pole	3-Pole
Dim. "A" (max.)	17,0/.67	23,8/.94

	1-Pole	2-Pole
Dim. "A" (max.)	11,7/.46	17,0/.67


Key:
$$\frac{0.00 = mm}{0.00 = inches}$$

PB Series


Pushbutton Switches

MOUNTING DIMENSIONS (For reference only)

Watertight Switch





Hermetically Sealed Switches



	2-Pole	4-Pole
Dim. "A" (max.)	16,8/.66	30,0/1.18

Miniature Size Switches





Key:
$$\frac{0.00 = mm}{0.00 = inches}$$

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Fixings category:

Click to view products by Honeywell manufacturer:

Other Similar products are found below:

893102000 00-5150 LZZ1A 0098.9234 M2PA-5011 630155 635401 6PA113 6PA147-E6 6PA148-E6 6PA32 6PA9 700106 700109
700303A56 700C1GRY 700C2GRN 704-6001 704.960.9 704.965.2 704.965.6 704.966.0 7089-3 710082-B11 71M1048 757200264
764300000 MHU35 MHU37 807039-1 825.003.011 825.005.011 825.053.011 825.055.011 826.000.071 827.020.011 827.400.021
835.900.023 MML52C10C MML52E10C MML92HGH MML93K 84211M02CNNS 84212M02CNNS 842.500.011 843.000.011 843187-000 843487-000 84-901 84-902