

1 kOhm

± 10 %

± 5 %

Standard

Plain round

9,53 mm [0.375 in] x 32 NEF-2A

9,53 mm [0.375 in]

6,35 mm [0.25 in]

50,80 mm [2.0 in]

Resistance Value

Bushing Thread

Bushing Length

Shaft Diameter

Bushing Type

Shaft Length

Shaft Ending

Linearity

Resistance Tolerance

Body	27.8 mm [1.094 in] diameter max. except at terminal standoff
Electrical Taper	Linear
Operating Temperature	-55 °C to 120 °C [-67 °F to 248 °F]
Working Voltage (Max.)	500 V
Rotational Life	25000 cycles
Mechanical Rotation	312°
Availability	Global
Series Name	53
UNSPSC Code	4111363300
UNSPSC Commodity	4111363300 Potentiometers

Terms & Conditions | Privacy Statement | Site Map

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Potentiometers category:

Click to view products by Honeywell manufacturer:

Other Similar products are found below :

58C2-2 590SX1N32F103SS 591SXJ48S252SC 591SXP56S252SC 591SXP56S503SC D31409 70B1G048K502X-A 70B1M032S502W 70B1N056S202W 70B8N056F502W 70J8N048S104U 70L1N040P103W 70L1N048P103X 70L1N048S103W GA2L040S102UC GA2L040S103UC GS1G044P103UA GS1N048P103UA GS1T032S103UA A43-1500 A43-20K A47-200K A4720K RA20LASD251A 132-2-0-202 RK14K1220-F25-C0-A103 RK14K1220F25C0C104 RK14K1220-F25-C1-B103 14910FAGJSX10102KA 14910FBGLFY00103KA 14910AABHSX10103KA 14910FAGJSX10104KA 152-01031 C0342008 5K P270-109A J97589 23M728 248BBHS0XB25104MA RV170F-10-15R1-B500K-0021 RV8NAYSB104A 917523A A43-40 A43-750 A438-5 A47-15K A4750K SPPG048S103U SPPG056P103U SWE-10 GA2G040F103BA