943-F4Y-2D-002-180E

(Home : Products : Sensors : Position Sensors : Ultrasonic Sensors : 943)



Series 943, software programmable, 200 mm to 2000 mm [7.9 in to 78.5 in.] scan distance, M18 plastic housing, switching 2 x NPN, 2 m [78.74]

Actual product appearance may vary.

	Product Specifications
Sensing Range	200 mm to 2000 mm [7.9 in to 78.5 in.]
Range Type	Middle range 1,0 m to 2,0 m [39.0 in to 79.0 in]
Min. Sensing Distance of Test Target	200 mm [7.87]
Supply Voltage	12 Vdc to 30 Vdc
Beam Angle	8°
Oscillating Frequency	180 KHz
Integrated Temperature Compensation	Yes
Repeatability	0.2 %/2 mm
Output Type	Sw itching 2 x NPN
Sw itching Output Type	2 Outputs - Configure for Normally Open/Normally Closed
Max. Sw itching Frequency	1.2 Hz
Adjustment Method	Teach-in
Analog Output Slope Selection	Teach-in
Operating Temperature	-15 °C to 70 °C [5 °F to 158 °F]
Storage Temperature	-25 °C to 70 °C [-13 °F to 158 °F]
Maximum Output Current	500 mA
Hysteresis	0.01
Indicators	3 LED
Memory	EEPROM (non-volatile)
Current Consumption	< 80 mA
Circuit Protection	Reverse Polarity, voltage spikes on supply and output lines, short circuit on sw itching output
Housing Style	M18 plastic
Housing Material	Polyethylenterephtalat
Sealing	IP67
Mounting	2 x M18 plastic nuts 24 mm
Sensing Face Material	Ероху
Termination Type	Pre-w ired 2 m [78.74]
Availability	Global

Product Specifications		
Normally Open/Normally Closed selection	Teach-in	
UNSPSC Code	41111960	
UNSPSC Commodity	41111960 Ultrasonic sensor	
Series Name	943	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Proximity Sensors category:

Click to view products by Honeywell manufacturer:

Other Similar products are found below:

01.001.5653.1 70.340.1028.0 70.360.2428.0 70.364.4828.0 70.810.1053.0 72.360.1628.0 73.363.6428.0 8027AL20NL2CPXX FYCC8E1-2 9221350022 922AA2W-A9P-L PLS2 GL-12F-C2.5X10(LOT3) 972AB2XM-A3N-L 972AB3XM-A3P-L PS3251 980659-1 QT-12 E2E2-X5M41-M4 E2E-X14MD1-G E2E-X2D1-G E2EX2ME2N E2EX3D1SM1N E2E-X4MD1-G E2E-X5E1-5M-N E2E-X5Y2-N E2E-X7D1-M1J-T-0.3M-N E2FMX1R5D12M E2K-F10MC1 5M EH-302 EI3010TBOP EI5515NPAP MS605AU EP175-32000 BSA-08-25-08 IFRM04N35B1/L IFRM04P1513/S35L IFRM06P1703/S35L IFRM08P1501/S35L IFRM12N17G3/L IFRM12P17G3/L IFRM12P3502/L IFRM12P37G1/S14L ILFK12E9189/I02 ILFK12E9193/I02 IMM2582C OISN-013 25.161.3253.0 25.332.0653.1 25.352.0653.0