## **INCANDESCENT OR NON-LIGHTED DISPLAY**



Buttons ordered separately.



Α

Β

Electrical Data	page 19
Buttons	page 43
Lamps and LEDs	page 58
Accessories	pages 56, 57
Mounting Dimensions	pages 59, 62

# FEATURES

- 1, 2, or 4 poles.
- Silver or gold contacts.
- Full guard bezel option.Momentary or 2-level alternate action (push-on, push-off).
- ÜL recognized, CSA certified. •
- Lamps can be furnished installed or
- ordered separately.
- Lamp circuit independent of switch circuit.

AA



2

#### AML21 ORDER GUIDE AML21 B

<u></u>	Ť	Ť	Ŧ	-	T	
Housing Type	Bezel Color	Incandescent Lamp Type	Terminal Type	Circuitry Codes (Each pole has double-throw)		
Standard Bezel:        AML21B      Square Non-Lighted        AML21C      Square 1 Lamp Ckt.        AML21E      Rect. Non-Lighted	<b>B</b> Black	<b>A</b> No Lamp Installed	<b>2</b> .110 × .020 (Solder or Quick-Connect)	Silver Contacts	Mom. Action AA 1-Pole AC 2-Pole CC 4-Pole	
AML21F Rect. 1 Lamp Ckt. AML21G Rect. 2 Lamp Ckts. Full Guard Bezel: AML21H Square Non-Lighted	IL21G  Rect. 2 Lamp Ckts.  6 V Lamp*  .025    Full Guard Bezel:  C  (Printe	<b>3</b> .025 × .025 (Printed Ckt. or Push-On)		Alt. Action AB 1-Pole AD 2-Pole CD 4-Pole		
AML21J Square 1 Lamp Ckt. AML21K Rect. Non-Lighted	E 28 V Lamp*		Gold Contacts	Mom. Action BA 1-Pole BC 2-Pole DC 4-Pole		
					Alt. Action BB 1-Pole BD 2-Pole DD 4-Pole	
				Gold-Plated Silver Contacts	Mom. Action EA 1-Pole EC 2-Pole	
					Alt. Action EB 1-Pole ED 2-Pole	
* Lamps will be installed per each lamp circuit specified in the Housing Type.						

#### Example: AML21BBA2AA

Square pushbutton switch housing nonlighted; black bezel; .110 × .020 termination; momentary action; 1-pole, doublethrow; silver contacts.

Honeywell ● Sensing and Control ● 1-800-537-6945 USA ● + 1-815-235-6847 International ● 1-800-737-3360 Canada 26

# **Manual Switches**

# **Electronic Control Pushbutton**

# LED DISPLAY



Buttons with LED "window" ordered separately. LEDs are not replaceable.

## FEATURES

- Identical to AML21 switches, except furnished with high efficiency LED display.
- Rectangular LED's are flush with button surface, providing wide angle indication.
- Optional diode protection for LED's.
  5 thru 24 VDC LED devices have an
- 5 thru 24 VDC LED devices have an internal resistor to maintain current at nominal 20 mA.
- UL recognized, CSA certified.
- LED circuit independent of switch circuit.

Electrical Data	page 19
Buttons	pages 42, 43
Lamps and LEDs	page 58
Accessories	pages 56, 57
Mounting Dimensions	pages 59, 62



	0.	- Cont.			
AML22 ORDER GUIDE AML22 C	B	<b>B</b> T	<b>2</b>	A	<b>A</b>
Housing Type	Bezel Color	LED Color/ Voltage	Terminal Type		y Codes double-throw)
Standard Bezel: AML22C Square 1 LED AML22H Square 1 High- Profile LED (For use with	<b>B</b> Black	Red        B      V*        C      5V        D      10V	2 .110 × .020 (Solder or Quick-Connect)	Silver Contacts	Mom. Action AA 1-Pole AC 2-Pole CC 4-Pole
AML52-A buttons) Full Guard Bezel: AML22J Square 1 LED		E 15V F 24V Yellow H V* J 5V K 10V L 15V M 24V Green R V* S 5V T 10V W 15V X 24V	3 .025 × .025 (Printed Ckt., or Push-On) 8 .110 × .020 With Diode Protection for LED		Alt. Action AB 1-Pole AD 2-Pole CD 4-Pole
				Gold Contacts	Mom. Action BA 1-Pole BC 2-Pole DC 4-Pole
					Alt. Action BB 1-Pole BD 2-Pole DD 4-Pole
				Gold-Plated Silver Contacts	Mom. Action EA 1-Pole EC 2-Pole
					Alt. Action EB 1-Pole

Manuals


ED 2-Pole

\* See LED information for devices without current limiting resistor, page 58.

### Example: AML22CBB2AA

Square pushbutton switch housing with one LED, black bezel; red LED (without resistor); .110  $\times$  .020 termination; momentary action, 1-pole, double-throw; silver contacts.

### **CONTACT ARRANGEMENT**





# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by Honeywell manufacturer:

Other Similar products are found below :

LW1L-M1C10V-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M7E-HRN2 67021K512 67081K512X 701PB580 719-5504-000 MDPSSGLFS 810KSV30B MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8646AB6X718UL 8646ABUL FSDWH 9001KXRK 9001T8BK 9533CD4+U574+U4922 1203MRA A22EM01S A595 1202A6 12037A2ULCSA 1203A2UL ABD122N-B 1211390004 ABN111-Y 1211500044 1211580012 1212MRA 1232A6NF RA3CSH6A 1241.1183.7047 1241.2511 1241.3428 1223A2ULCSA 1223MRA 1232AX2119 1241.1183.8000 1241.1183.8029 1241.2506 1241.2606 12MA6 1301940184 RELBARF6X10(PLASTIC) 13435AG 13440AD2G25X822+U4546 13445A4GX768