

CLSXB4T

([Home](#) : [Products](#) : [Machine Safety](#) : [MICRO SWITCH™ Safety Sw itches](#) : [Cable Pull](#) : [CLSX](#))



CLSX Series, Explosion-proof Cable Pull Safety Switch, 1NC/1NO Direct Opening, Slow Action, Explosion-proof, 1/2 NPT, Silver Contacts

Actual product appearance may vary.

Product Specifications

Product Type	Cable Pull Safety Sw itch
Actuator	Cable, Maintained
Switch Type	1NC/1NO Direct Opening, Slow Action
Contact Material	Silver
Termination Type	1/2 NPT
Ampere Rating	100 mA to 10 A (Thermal)
Voltage	600 Vac and 250 Vdc max.
Housing Material	Zinc Die-Cast
Housing Type	Explosion-proof
Series Name	CLSX
Sealing	IP67; NEMA 1, 3, 4, 13
CSA File #	LR57326
UL File #	E37138, E157416
Agency Approvals and Standards	UL, CSA
Operating Temperature	-25 °C to 40 °C [-13 °F to 104 °F]
Availability	Global
UNSPSC Code	39122205
UNSPSC Commodity	39122205 Safety Sw itches
Indicator	None
Comment	IEC 947-5-1, EN60947-5-1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Basic / Snap Action Switches](#) category:

Click to view products by [Honeywell](#) manufacturer:

Other Similar products are found below :

[5SM901-S12](#) [5SM9-S12N195](#) [602EN532](#) [602EN535-RB](#) [602HE5-RB1](#) [604HE162](#) [604HE223-6B](#) [624HE17-RB](#) [6HM82](#) [6HM89](#) [6SE1](#)
[6SX1-H58](#) [70500216](#) [70599106](#) [MBD5B1](#) [MBH2731](#) [73-316-0012](#) [EXD-AR20](#) [79211923](#) [79218589](#) [7AS12](#)
[MIL30126AB6BBMD4A12XAU](#) [ML-1155](#) [ML-1376](#) [831010C3.0](#) [831090C2.EL](#) [83131904](#) [84212012](#) [8AS239](#) [8HM73-3](#) [8SX26-H33](#)
[914CE1-6G](#) [PL-100](#) [11SM1077-H4](#) [11SM1077-H58](#) [11SM1-TN107](#) [11SM405](#) [11SM8423-H2](#) [11SX37-T](#) [11SX48-H58](#) [11SM2442-T](#)
[11SM76-T](#) [11SM77-H58](#) [11SM77-T](#) [11SM863-T](#) [11SM866](#) [A7CN-1M-1-LEFT](#) [A831700C7.0](#) [121EN187-R](#) [121EN188-R](#)