CSNE151-104

(Home : Products : Sensors : Current Sensors : Closed Loop : CSN)



CSN Series closed loop current sensor, measures ac, dc or impulse current, 25 amp-turns nominal, ±56 amp-turns range, miniature housing, 2000 turn

Actual product appearance may vary.

Product Type	Product Specifications Closed Loop Linear	
Sensed Current Type	ac or dc	
Sensed Current Range	±56 A	
Package Type	Series Connect PCB Mount	
Output Type	Current	
Continuous Current	±40 A	
Operate Current	25 A RMS @ 25 °C	
Supply Current	±12 mA + Output	
Supply Voltage	±15.0 Vdc	
Offset Current	< ±0.3 mA	
Offset Current Drift	< ±0.6 mA	
Coil Resistance	190 Ohm	
Response Time	< 1 µs	
Coil Turns	2000	
Output Nominal	12.5 mA	
Operating Temperature	-40 °C to 75 °C [-40 °F to 167 °F]	
Storage Temperature	-40 °C to 90 °C [-40 °F to 194 °F]	
Measuring Resistance	193 Ohm min., 722 Ohm max.	
Housing Material	Glass-filled PBT (UL94-V0)	
Mounting	PCB on 9 Pins	
Pinout Style	3 Pin	
Accuracy	±1.0 %	
Availability	Global	
Comment	Low cost miniature 25 A sensor.	
UNSPSC Code	41111928	
UNSPSC Commodity	41111928 Current Sensors	
Series Name	CSN	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Board Mount Current Sensors category:

Click to view products by Honeywell manufacturer:

Other Similar products are found below:

CSDD1FR CSLA2ELI CSNP661-007 SCL15 10006 ACS723LLCTR-05AB-T L18P003S05 T60404-B4658-X030 LA02P021S03

LA01M041S05 LA03P054S05 CSNE151-003 L08P150D15IPV L18P050D15-OP SIC830AED-T1-GE3 CT-05 CT-07-100 CT-07-50 MR-1

MR-1-P5 T60404-N4646-X662 T60404-N4646-X664 DRV421RTJT CSNR161005 T60404-N4646-X651 MR-3 MR-2 MR-4 CT-06-100

CT-06-50 T60404-N4646-X410 T60404-N4646-X663 CT-06-75 CSDA1BA CSDA1BA-S CSDA1DA CSDC1DA CSDD1EC CSLA1DE

CSLA1DG CSLA1DK CSLA1EL CSLA1GE CSLA1GF CSLA2CDI CSLA2DE CSLA2DG CSLA2DH CSLA2DJI CSLA2EL