

High Temperature Industrial VRS Magnetic Speed Sensors



DESCRIPTION

High Temperature VRS sensors are designed for use in applications where the sensor is exposed to temperatures up to 260 °C [450 °F]. Sealed Front-End versions are available for applications where the sensor is exposed to fluids, lubricants or adverse environmental conditions.

Passive VRS (Variable Reluctance Speed) Magnetic Speed sensors are simple, rugged devices that do not require an external voltage source for operation.

A permanent magnet in the sensor establishes a fixed magnetic field. The approach and passing of a ferrous metal target near the sensor's pole piece (sensing area) changes the flux of the magnetic field, dynamically changing its strength. This change in magnetic field strength induces a current into a coil winding which is attached to the output terminals.

FEATURES

- Self-powered operation
- Direct conversion of actuator speed to output frequency
- Simple installation
- No moving parts
- Designed for use over a wide range of speeds
- Adaptable to a wide variety of configurations
- Customized VRS products for unique speed sensing applications
- Housing diameters: 5/8 in (M16), 3/8 in (M12), 1/4 in (8M)
- Housing material/style: stainless steel threaded
- Terminations: MS3106 connector, preleaded
- Output voltages: 4.7 Vp-p to 125 Vp-p

The output signal of a VRS sensor is an ac voltage that varies in amplitude and wave frequency as the speed of the monitored device changes, and is usually expressed in peak to peak voltage (Vp-p).

One complete waveform (cycle) occurs as each target passes the sensor's pole piece. If a standard gear were used as a target, this output signal would resemble a sine wave if viewed on an oscilloscope.

Honeywell also offers VRS sensors for general purpose, high output, power output, high resolution and hazardous location applications, as well as low-cost molded OEM versions.

POTENTIAL APPLICATIONS

- Engine RPM (revolutions per minute) measurement on aircraft, automobiles, boats, buses, trucks and rail vehicles
- Motor RPM measurement on drills, grinders, lathes and automatic screw machines
- Motor RPM measurement on precision camera, tape recording and motion picture equipment
- Process speed measurement on food, textile, paper, woodworking, printing, tobacco and pharmaceutical industry machinery
- Motor speed measurement of electrical generating equipment
- Speed measurement of pumps, blowers, mixers, exhaust and ventilating fans
- Flow measurement on turbine meters
- Wheel-slip measurement on autos and locomotives
- Gear speed measurement

High Temperature

5/8 INCH (M16*) SENSORS (All dimensions for reference only. mm/[in])

*Contact Honeywell for availability of metric mounting thread versions.

LOW RESISTANCE COILS FOR HIGH FREQUENCY APPLICATIONS

General Specifications

| Parameter | Characteristic | Parameter | Characteristic |
|-----------------------|--|--------------------------|--------------------------------|
| Min. output voltage | 25 Vp-p | Inductance | 30 mH max. |
| Coil resistance | 65 Ohm typ. | Gear pitch range | 24 DP (module 1.06) or coarser |
| Pole piece diameter | 2,69 mm [0.106 in] | Optimum actuator | 20 DP (module 1.27) |
| Min. surface speed | 0,50 m/s [20 in/s] typ. | Max. operating frequency | 50 kHz typ. |
| Operating temp. range | -55 °C to 230 °C [-67 °F to 450 °F] | Vibration | N/A |
| Mounting thread | 5/8-18 UNF-2A | Termination | MS3106 connector |

Test Condition Specifications

| Parameter | Characteristic |
|-----------------|------------------------|
| Surface speed | 25 m/s [1000 in/s] |
| Gear | 20 DP (module 1.27) |
| Air gap | 0,127 mm [0.005 in] |
| Load resistance | 100 kOhm |

| Catalog Listing | Weight | |
|-----------------|---------------|--|
| 3010HTB | 70 g [2.5 oz] | |

HIGH RESISTANCE COILS FOR MAXIMUM OUTPUT VOLTAGE APPLICATIONS

General Specifications

| Parameter | Characteristic | Parameter | Characteristic |
|-----------------------|--|--------------------------|--------------------------------|
| Min. output voltage | 125 Vp-p | Inductance | 450 mH max. |
| Coil resistance | 1055 Ohm typ. | Gear pitch range | 24 DP (module 1.06) or coarser |
| Pole piece diameter | 2,69 mm [0.106 in] | Optimum actuator | 20 DP (module 1.27) |
| Min. surface speed | 0,25 m/s [10 in/s] typ. | Max. operating frequency | 15 kHz typ. |
| Operating temp. range | -55 °C to 230 °C [-67 °F to 450 °F] | Vibration | N/A |
| Mounting thread | 5/8-18 UNF-2A | Termination | MS3106 connector |

Test Condition Specifications

| Parameter | Characteristic |
|-----------------|------------------------|
| Surface speed | 25 m/s [1000 in/s] |
| Gear | 20 DP (module 1.27) |
| Air gap | 0,127 mm [0.005 in] |
| Load resistance | 100 kOhm |

| Catalog Listing | Thread Length (A) | Weight | |
|-----------------|-------------------|---------------|--|
| 3030HTB | 28 mm [1.1 in] | 70 g [2.5 oz] | |
| 3030HTB25 | 63 mm [2.5 in] | 84 g [3.0 oz] | |

Industrial VRS Magnetic Speed Sensors

5/8 INCH (M16*) SENSORS CONTINUED (All dimensions for reference only. mm/[in])

*Contact Honeywell for availability of metric mounting thread versions.

NOMINAL RESISTANCE COILS FOR LOW IMPEDANCE LOAD APPLICATIONS

General Specifications

| Parameter | Characteristic | Parameter | Characteristic |
|-----------------------|--|--------------------------|-----------------------------------|
| Min. output voltage | 45 Vp-p | Inductance | 85 mH max. |
| Coil resistance | 141 Ohm typ. | Gear pitch range | 12 DP (module 2.11) or coarser |
| Pole piece diameter | 4,75 mm [0.187 in] | Optimum actuator | 8 DP (module 3.17) |
| Min. surface speed | 0,38 m/s [15 in/s] typ. | Max. operating frequency | 40 kHz typ. |
| Operating temp. range | -55 °C to 230 °C [-67 °F to 450 °F] | Vibration | N/A |
| Mounting Thread | 5/8-18 UNF-2A | Termination | MS3106 Connector |

Test Condition Specifications

| Parameter | Characteristic |
|-----------------|------------------------|
| Surface speed | 25 m/s [1000 in/s] |
| Gear | 8 DP (module 3.17) |
| Air gap | 0,127 mm [0.005 in] |
| Load resistance | 1.25 kOhm |

| Catalog Listing | Thread Length (A) | Weight | |
|-----------------|-------------------|---------------|--|
| 3040HTB | 28 mm [1.1 in] | 70 g [2.5 oz] | |
| 3040HTB25 | 63 mm [2.5 in] | 84 g [3.0 oz] | |

High Temperature

5/8 INCH SEALED FRONT-END SENSORS (All dimensions for reference only. mm/[in])

(No metric available.)

NOMINAL RESISTANCE COILS FOR LOW IMPEDANCE LOADS APPLICATIONS

General Specifications

| Parameter | Characteristic | Parameter | Characteristic |
|-----------------------|--|--------------------------|--------------------------------|
| Min. output voltage | 60 Vp-p | Inductance | 85 mH max. |
| Coil resistance | 120 Ohm to 162 Ohm | Gear pitch range | 12 DP (module 2.11) or coarser |
| Pole piece diameter | 4,39 mm [0.173 in] | Optimum actuator | 8 DP (module 3.17) |
| Min. surface speed | 0,38 m/s [15 in/s] typ. | Max. operating frequency | 40 kHz typ. |
| Operating temp. range | -54 °C to 220 °C [-65 °F to 428 °F] | Vibration | N/A |
| Mounting Thread | 5/8-18 UNF-2A | Termination | MS3106 connector |

Test Condition Specifications

| Parameter | Characteristic |
|-----------------|------------------------|
| Surface speed | 25 m/s [1000 in/s] |
| Gear | 8 DP (module 3.17) |
| Air gap | 0,127 mm [0.005 in] |
| Load resistance | 1.25 kOhm |

| Catalog Listing | Weight | |
|-----------------|---------------|---|
| MA243HT | 98 g [3.5 oz] | <p>Technical drawing of the MA243HT sensor. It includes a side view with dimensions: 19,05 [0.750] for the pole piece diameter, 76 [3.0] for the total length, and 28,12 [1.107] for the gear length. A diameter of Ø19,05 [0.750] is also indicated. A cross-section view shows the gear teeth and pole piece with labels A and B. A note points to the gear teeth: 'BRAZED THROUGH POLE PIECE'.</p> |

Industrial VRS Magnetic Speed Sensors

3/8 INCH (M12*) SENSORS (All dimensions for reference only. mm/[in])

*Contact Honeywell for availability of metric mounting thread versions.

General Specifications

| Parameter | Characteristic | Parameter | Characteristic |
|-----------------------|-------------------------------------|--------------------------|--|
| Min. output voltage | 15 Vp-p | Inductance | 31 mH max. |
| Coil resistance | 110 Ohm max. | Gear pitch range | 26 DP (module 0.98) or coarser |
| Pole piece diameter | 2,36 mm [0.093 in] | Optimum actuator | 24 DP (module 1.06) ferrous metal gear |
| Min. surface speed | 0,75 m/s [20 in/s] typ. | Max. operating frequency | 50 kHz typ. |
| Operating temp. range | -40 °C to 205 °C [-40 °F to 400 °F] | Vibration | N/A |
| Mounting thread | 3/8-24 UNF-2A | Termination | 24 AWG Teflon-insulated leads |

Test Condition Specifications

| Parameter | Characteristic |
|-----------------|---------------------|
| Surface speed | 25 m/s [1000 in/s] |
| Gear | 20 DP (module 1.27) |
| Air gap | 0,127 mm [0.005 in] |
| Load resistance | 100 kOhm |

| Catalog Listing | Thread Length (A) | Weight | |
|-----------------|-------------------|---------------|--|
| 3015HTB | 20 mm [0.8 in] | 28 g [1.0 oz] | |
| 3015HTB15 | 38 mm [1.5 in] | 42 g [1.5 oz] | |

High Temperature

1/4 INCH (M8*) MINIATURE SENSORS (All dimensions for reference only. mm/[in])

*Contact Honeywell for availability of metric mounting thread versions.

General Specifications

| Parameter | Characteristic | Parameter | Characteristic |
|-----------------------|-------------------------------------|--------------------------|--|
| Min. output voltage | 4.7 Vp-p | Inductance | 13 mH max. |
| Coil resistance | 137 Ohm max. | Gear pitch range | 36 DP (module 0.70) or coarser |
| Pole piece diameter | 1 mm [0.040 in] | Optimum actuator | 28 DP (Module 0.90) ferrous metal gear |
| Min. surface speed | 0,89 m/s [35 in/s] typ. | Max. operating frequency | 70 kHz typ. |
| Operating temp. range | -40 °C to 230 °C [-40 °F to 450 °F] | Vibration | Mil-Std 202F Method 204D |
| Mounting thread | 1/4-40 UNS-2A | Termination | 30 AWG Teflon-Insulated Leads |

Test Condition Specifications

| Parameter | Characteristic |
|-----------------|---------------------|
| Surface speed | 25 m/s [1000 in/s] |
| Gear | 20 DP (module 1.27) |
| Air gap | 0,127 mm [0.005 in] |
| Load resistance | 100 kOhm |

| Catalog Listing | Weight | |
|-----------------|---------------|---|
| 3055A | 14 g [0.5 oz] | <p>Technical drawing of the 3055A miniature sensor. The drawing shows a side view and a top view. Dimensions are provided in millimeters and inches in brackets. The top view shows a hexagonal shape with a diameter of 9.53 mm [0.375 in]. The side view shows a cylindrical body with a diameter of 7.70 mm [0.303 in] and a length of 15 mm [0.6 in]. The mounting thread has a diameter of 0.25 mm [0.010 in]. The leads have a diameter of 0.749 mm [0.295 in]. The total length of the sensor is 61.0 mm [24.00 in].</p> |

Industrial VRS Magnetic Speed Sensors

1/4 INCH SEALED FRONT-END SENSORS (All dimensions for reference only. mm/[in])

(No metric available.)

General Specifications

| Parameter | Characteristic | Parameter | Characteristic |
|-----------------------|--------------------------------------|--------------------------|--|
| Min. output voltage | 5.2 Vp-p | Inductance | 85 mH max. |
| Coil resistance | 20 Ohm to 45 Ohm | Gear pitch range | 36 DP (module 0.70) or coarser |
| Pole piece diameter | 1 mm [0.040 in] | Optimum actuator | 28 DP (module 0.90) ferrous metal gear |
| Min. surface speed | 0,89 m/s [35 in/s] typ. | Max. operating frequency | 70 kHz typ. |
| Operating temp. range | -73 °C to 230 °C [-100 °F to 450 °F] | Vibration | Mil-Std 202F Method 204D |
| Mounting Thread | 1/4-40 UNS-2A | Termination | 28 AWG Teflon-insulated leads |

Test Condition Specifications

| Parameter | Characteristic |
|-----------------|---------------------|
| Surface speed | 25 m/s [1000 in/s] |
| Gear | 20 DP (module 1.27) |
| Air gap | 0,127 mm [0.005 in] |
| Load resistance | 100 kOhm |

| Catalog Listing | Weight | |
|-----------------|-------------|--|
| MA3055 | 28 g [1 oz] | |

| Catalog Listing | Weight | |
|-----------------|-------------|--|
| MA3055S10 | 28 g [1 oz] | |

WARNING

PERSONAL INJURY

DO NOT USE these products as safety or emergency stop devices or in any other application where failure of the product could result in personal injury.

Failure to comply with these instructions could result in death or serious injury.

WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items it finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While we provide application assistance personally, through our literature and the Honeywell web site, it is up to the customer to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this printing. However, we assume no responsibility for its use.

WARNING

MISUSE OF DOCUMENTATION

- The information presented in this product sheet is for reference only. Do not use this document as a product installation guide.
- Complete installation, operation, and maintenance information is provided in the instructions supplied with each product.

Failure to comply with these instructions could result in death or serious injury.

SALES AND SERVICE

Honeywell serves its customers through a worldwide network of sales offices, representatives and distributors. For application assistance, current specifications, pricing or name of the nearest Authorized Distributor, contact your local sales office or:

E-mail: info.sc@honeywell.com

Internet: www.honeywell.com/sensing

Phone and Fax:

Asia Pacific +65 6355-2828
+65 6445-3033 Fax
Europe +44 (0) 1698 481481
+44 (0) 1698 481676 Fax
Latin America +1-305-805-8188
+1-305-883-8257 Fax
USA/Canada +1-800-537-6945
+1-815-235-6847
+1-815-235-6545 Fax

Automation and Control Solutions

Sensing and Control

Honeywell

1985 Douglas Drive North

Minneapolis, MN 55422

www.honeywell.com/sensing

005877-1-EN IL50 GLO Printed in USA
March 2007

Copyright © 2007 Honeywell International Inc. All rights reserved.

Honeywell

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Speed Sensors](#) category:

Click to view products by [Honeywell](#) manufacturer:

Other Similar products are found below :

[621405](#) [M3050A13](#) [MA215HT-96](#) [726324](#) [726446](#) [727033](#) [727440-08](#) [727440-28](#) [728265-02](#) [993AB18AT-J](#) [SNDJ-CNT-G03](#) [M3024](#)
[M3030](#) [M3040](#) [M3040AN25](#) [34.170.1001.0](#) [4953](#) [ZS-180-B55](#) [ZS-1963](#) [ZS-2048](#) [ZS-2147](#) [04.241.8053.0](#) [04.845.2253.0](#) [EN401B](#) [SNDH-](#)
[SPR-001](#) [70.331.1028.0](#) [70.331.2428.0](#) [70.377.2428.0](#) [725004](#) [725204](#) [725733](#) [725951](#) [727397](#) [727440-27](#) [728143-15](#) [728202-02](#) [PA11560](#)
[PA12D03](#) [ZS-1952](#) [ZS-1728-D](#) [SNDJ-CNT-G04](#) [SNDH-SPC-01M](#) [SNDH-H3C-G07](#) [4951957-8](#) [REVK](#) [722543](#) [LCZA460](#) [728098-07](#)
[SNDH-SPC-01P](#) [727470](#) [3040AN40](#)