
## ZT

## Immersion wells

#### for thermostats and temperature transmitters

Type Immersion depth L¹ (mm)	Overall length L <sup>2</sup> (mm)	Suitable for
------------------------------	---------------------------------------	--------------




R1/Ms	135	151	TAM
R2/Ms	220	236	
R3/Ms	500	516	
R10/Ms	135	151	TX
R20/Ms	220	236	

Stainless steel (1.4571 + 1.4401) G 1/2", permitted pressure 63 bar				
R1/Nst	135	151	TAM	
R2/Nst	220	236		
R10/Nst	135	151	TX	
R20/Nst	220	236		

Nickel-plated brass, 1/2" NPT, permitted pressure 25 bar				
RN1/Ms	135	151	TAM	
RN2/Ms	220	236		
RN10/Ms	135	151	TX	
RN20/Ms	220	236		

Stainless steel (	1.4571 + 1.440°	1) 1/2" NPT, per	mitted pressure 63 bar	
RN1/Nst	135	151	TAM	
RN2/Nst	220	236		
RN10/Nst	135	151	TX	
RN20/Nst	220	236		



Immersion wells G 1/2"


Immersion wells 1/2" NPT

... . B6 B7

## Immersion wells with fixing flange for air ducts

Туре	Immersion depth of sensor	Suitable for
Material: chromated st	eel	
R6	135 mm	TX
R7	220 mm	

### Immersion wells (screw-in thread G1/2")



Туре	Immersion depth (mm)	Connection	Max. perm. press. (bar)	
040 400	100	04/01	100	
G12-100	100	G1/2"	100	
G12-250	250	G1/2"	100	
N12-100	100	<b>1/2</b> " NPT	100	



# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sensor Fixings & Accessories category:

Click to view products by Honeywell manufacturer:

Other Similar products are found below:

F03-01 SUS304 BINIL 8000-5130 FH-AP1 PH-1-10M PH-1-20M PH-2-30M AC201 R4 ADI-LC3S EC18-WELL PBT420-100R PC
15015 K35-4 A-1923 SS-12143 STA12 AP4-T PH-1-50M R6 D01051301 43912557-020 MF-1 D=3.2 BGN-035 E39-L7 ZX-SB11

D01070602 606072 606075 Y92ES12PVC4A10ML Y92ES12PVC4S5ML SA9Z-F11 Z49-SF1 ZFV-XMF2 E4R-R12A-CS3M010 28810-2

ZX-SW11E V3 CCS-PL-LDR2-70 E4R-R12A-CS3M020 BS-1T CHITAN F03-01 CHITAN CCS-PD2-1012 ZX-SFW11E V3 PH-2-90M

PH-2-5M XMLZL008 AC244 28810-1 PH-1-40M SS-12225 32043-500