


# SD3443/5443

Silicon Phototransistor

## FEATURES

- TO-46 metal can package
- Choice of flat window or lensed package
- 90° or 18° (nominal) acceptance angle option
- Wide operating temperature range  
(- 55°C to +125°C)
- External base connection for added control
- High sensitivity
- Mechanically and spectrally matched to  
SE3450/5450, SE3455/5455 and SE3470/5470  
infrared emitting diodes



## DESCRIPTION


The SD3443/5443 series consists of an NPN silicon phototransistor mounted in a TO-46 metal can package. The SD3443 has flat window cans providing a wide acceptance angle, while the SD5443 has glass lensed cans providing a narrow acceptance angle. The TO-46 packages are ideally suited for operation in hostile environments.

The base is connected on all SD3443 and SD5443 standard products.


## OUTLINE DIMENSIONS in inches (mm)

Tolerance    3 plc decimals     $\pm 0.005(0.12)$   
              2 plc decimals     $\pm 0.020(0.51)$

### SD3443



### SD5443



# SD3443/5443

Silicon Phototransistor

ELECTRICAL CHARACTERISTICS (25°C unless otherwise noted)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	TEST CONDITIONS
Light Current SD3443-001	$I_L$		0.50		mA	$V_{CE}=5\text{ V}$ $H=5\text{ mW/cm}^2$ (1)
SD3443-002			1.00			
SD3443-003			2.00			
SD5443-001			1.00			
SD5443-002			4.00			
SD5443-003			8.00			
SD5443-004			16.0			
Collector Dark Current	$I_{CEO}$			100	nA	$V_{CE}=10\text{ V}, H=0$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	30			V	$I_C=100\text{ }\mu\text{A}$
Emitter-Collector Breakdown Voltage	$V_{(BR)ECO}$	5.0			V	$I_E=100\text{ }\mu\text{A}$
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$			0.4	V	$I_C=0.4\text{ mA}$ $H=5\text{ mW/cm}^2$ $I_F=\text{Constant}$
Angular Response (2)	$\emptyset$		90		degr.	
SD3443			18			
SD5443						
Rise And Fall Time	$t_r, t_f$		15		μs	$V_{CC}=5\text{ V}, I_L=1\text{ mA}$ $R_L=1000\text{ }\Omega$

Notes

1. The radiation source is a tungsten lamp operating at a color temperature of 2870°K.
2. Angular response is defined as the total included angle between the half sensitivity points.


ABSOLUTE MAXIMUM RATINGS

(25°C Free-Air Temperature unless otherwise noted)

Collector-Emitter Voltage	30 V
Emitter-Collector Voltage	5 V
Power Dissipation	150 mW (1)
Operating Temperature Range	-55°C to 125°C
Storage Temperature Range	-65°C to 150°C
Soldering Temperature (10 sec)	260°C

Notes

1. Derate linearly from 25°C free-air temperature at the rate of 1.43 mW/°C.



Honeywell reserves the right to make changes in order to improve design and supply the best products possible.

**Honeywell**

# SD3443/5443

## Silicon Phototransistor

**SWITCHING TIME TEST CIRCUIT**





Fig. 1 Responsivity vs Angular Displacement (SD3443) gra\_052.ds4



**SWITCHING WAVEFORM**




Fig. 2 Responsivity vs Angular Displacement (SD5443) gra\_053.ds4




Fig. 3 Dark Current vs Temperature gra\_303.ds4





Fig. 4 Non-Saturated Switching Time vs Load Resistance gra\_041.ds4



# SD3443/5443

## Silicon Phototransistor

Fig. 5 Spectral Responsivity




Fig. 6 Coupling Characteristics  
SE3450 with SD3443




Fig. 7 Coupling Characteristics  
SE5450 with SD5443





Fig. 8 Collector Current vs  
Ambient Temperature



All Performance Curves Show Typical Values

Honeywell reserves the right to make changes in order to improve design and supply the best products possible.

# Honeywell

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for Phototransistors category:***

***Click to view products by Honeywell manufacturer:***

Other Similar products are found below :

[LTR-5576D](#) [PT17-21B/L41/TR8](#) [PT908-7B-F](#) [QSD123A4R0](#) [ASDL-6620-C22](#) [OED-ST-8LR2](#) [OED-STR44B90-TR](#) [SD5410-109](#) [PT26-21C/CT](#) [PT15-21B-TR8](#) [PT-IC-AC-3528-520](#) [PT-IC-BC-3528-550](#) [MHT153PTBT](#) [MHS153PTBT](#) [PT5529B/L2/H2-F](#) [PT91-21C/TR10](#) [BP103-3/4](#) [BPX 38-3](#) [BPY 62](#) [KPS-3227SP1C](#) [L-53P3BT](#) [L-53P3C](#) [L-93DP3BT](#) [L-93DP3C](#) [LL-503PTC2E-1AD](#) [LL-S150PTC-1A](#) [LL-S150PTD-1A](#) [SFH 320](#) [SFH 320-3](#) [SFH 320 FA](#) [OP508FA](#) [TEMT1030](#) [LTR-301](#) [PGM5516-MP](#) [PGM5526-MP](#) [PGM5549](#) [PGM5637D](#) [VTT7125H](#) [VEMT4700F-GS08](#) [PT19-21B/L41/TR8](#) [KP-2012P3C](#) [TEKT5400S](#) [SD1410-128L](#) [SFH 313 FA-3/4](#) [SFH 313 FA-2/3](#) [SFH 320-4-Z](#) [SFH 309 FA-5/6](#) [PT4800FE000F](#) [SFH 309-5/6](#) [SFH 3410-1/2-Z](#)