CATALOG LISTING **MICRO SWITCH** V3-507 SWITCH-BASIC a Honeywell Division CK-E8250 FED.MFG.CODE 91929 -PLASTIC PLUNGER .089 DIA HOLE IN TERMINALS (3) -507 .165 .796 ± .010 -.114 +.002 -.001 DIA HOLE .047 MAX **PRETRAVEL** -.110 -.10 .578 .015 OPERATING .406 .003 .625 .015 .25 **POSITION** .76 сом REVISIONS .114 ^{+.002} _{-.001} DCS 2 DEC 93 .26-.126 ± .002 DIA-.875 2.003 -.27 **-**1.094±.015 **---**.27 NOTE 1 - TERMINALS ARE PLATED FOR SOLDERING THIRD ANGLE PROJECTION THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH. DO NOT SCALE PRINT CHARACTERISTICS ELECTRICAL DATA SCALE FULL CONTACT ARRANGEMENT UNLESS OTHERWISE SPECIFIED OPERATING FORCE -- -- 8 OZ MAX SPDT RELEASE FORCE -- -- -- 2 OZ MIN ±.030 ONE PLACE (.0) DIFFERENTIAL TRAVEL - - .006-.016 L156 11A 1/3HP 125, 250 OR 277 VAC DM/CAD TWO PLACE (.00) ±.015 OVERTRAVEL -- -- -- .040 MIN 1/2A 125 VDC, 1/4A 250 VDC FREE POSITION - - - - - .625 MAX 4A 125 VAC "L" THREE PLACE (.000) ±.005 В RELEASE TRAVEL - - - - - .010 MIN **ANGLES** മ weight .016 LB

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Basic / Snap Action Switches category:

Click to view products by Honeywell manufacturer:

Other Similar products are found below:

5SM901-S12 5SM9-S12N195 602EN532 602EN535-RB 602HE5-RB1 604HE162 604HE223-6B 624HE17-RB 6HM82 6HM89 6SE1
6SX1-H58 70500216 70599106 MBD5B1 MBH2731 73-316-0012 EXD-AR20 79211923 79218589 7AS12

MIL30126AB6BBMD4A12XAU ML-1155 ML-1376 831010C3.0 831090C2.EL 83131904 84212012 8AS239 8HM73-3 8SX26-H33
914CE1-6G PL-100 11SM1077-H4 11SM1077-H58 11SM1-TN107 11SM405 11SM8423-H2 11SX37-T 11SX48-H58 11SM2442-T
11SM76-T 11SM77-H58 11SM77-T 11SM863-T 11SM866 A7CN-1M-1-LEFT A831700C7.0 121EN187-R 121EN188-R