


S9015 TRANSISTOR (PNP)

FEATURES

Complementary to S9014



MARKING: M6

MAXIMUM RATINGS (T_A=25°C unless otherwise noted)

Symbol	Parameter	Value	Units
V _{CBO}	Collector-Base Voltage	-50	V
V _{CEO}	Collector-Emitter Voltage	-45	V
V _{EBO}	Emitter-Base Voltage	-5	V
lc	Collector Current -Continuous	-0.1	А
Pc	Collector Power Dissipation	0.2	W
Tj	Junction Temperature	150	°C
T _{stg}	Storage Temperature	-55-150	°C

ELECTRICAL CHARACTERISTICS (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	ТҮР	МАХ	UNIT
Collector-base breakdown voltage	V _{(BR)CBO}	I _C = -100μΑ, I _E =0	-50			V
Collector-emitter breakdown voltage	V _{(BR)CEO}	I _C = -0.1mA, I _B =0	-45			V
Emitter-base breakdown voltage	V _{(BR)EBO}	I _E =-100μA, I _C =0	-5			V
Collector cut-off current	I _{CBO}	V _{CB} =-50V, I _E =0			-0.1	μA
Emitter cut-off current	I _{EBO}	V _{EB} = -5V, I _C =0			-0.1	μA
DC current gain	h _{FE}	V _{CE} =-5V, I _C = -1mA	200		450	
Collector-emitter saturation voltage	V _{CE} (sat)	I _C =-100mA, I _B = -10mA			-0.3	V
Base-emitter saturation voltage	V _{BE} (sat)	I _C =-100mA, I _B =-10mA			-1	V
Transition frequency	f _T	V _{CE} =-5V, I _C = -10mA f=30MHz	150			MHz



he, DC CURRENT GAIN

-10 L -0.1

Typical Characteristics





Figure 1. Static Characteristic



Ic [mA], COLLECTOR CURRENT







Figure 5. Collector Output Capacitance



-10

Is [mA]. COLLECTOR CURRENT Figure 2. DC current Gain

-100

1000

S9015




Figure 4. Base-Emitter On Voltage





Figure 6. Current Gian Bandwidth Product



PACKAGE OUTLINE

Plastic surface mounted package; 3 leads

SOT-23



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Bipolar Transistors - BJT category:

Click to view products by Hong Kong Chuangji manufacturer:

Other Similar products are found below :

 619691C
 MCH4017-TL-H
 MMBT-2369-TR
 BC546/116
 BC557/116
 BSW67A
 NJVMJD148T4G
 NTE123AP-10
 NTE153MCP
 NTE16

 NTE195A
 NTE92
 2N4401-A
 2N6728
 2SA1419T-TD-H
 2SA2126-E
 2SB1204S-TL-E
 2SC2712S-GR,LF
 SP000011176
 2N2907A
 2N3904

 NS
 2N5769
 2SC2412KT146S
 CPH6501-TL-E
 MCH4021-TL-E
 MJE340
 Jantx2N5416
 US6T6TR
 NJL0281DG
 732314D
 CPH3121-TL-E

 CPH6021-TL-H
 873787E
 IMZ2AT108
 MMST8098T146
 UMX21NTR
 MCH6102-TL-E
 NJL0302DG
 30A02MH-TL-E
 NTE13
 NTE26

 NTE282
 NTE323
 NTE350
 NTE81
 STX83003-AP
 JANTX2N2920L
 JANSR2N2222AUB
 CMLT3946EG
 TR
 2SA1371D-AE