



件(通)用件叠记
插图

插 针

旧底图总号

底图总号

登 字

日 期

D	0.9	1.9	3.9	5.9	7.9	9.9	11.9	13.9	15.9	17.9	21.9	23.9	25.9	27.9	29.9
C	5.9	7.9	9.9	11.9	13.9	15.9	17.9	19.9	21.9	23.9	25.9	27.9	29.9	31.9	33.9
B	4.9	6.9	8.9	10.9	12.9	14.9	16.9	18.9	20.9	22.9	24.9	26.9	28.9	30.9	32.9
A	2.0	4.0	6.0	8.0	10.0	12.0	14.0	16.0	18.0	20.0	22.0	24.0	26.0	28.0	30.0
孔数	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16

技术要求

1. 产品无严重损伤、缺针、长短针、旋转针等现象;插针镀层无脱落、起皮、发黄现象。
2. 未注尺寸公差按SJ1372-78中7级执行。
3. 每一插针在针座上的固定力≥10N。
4. 相同规格产品不同厂家的应能互换。

带 针 插 座 PH-2WAP~16WAP (HX20007-2WAP~16WAP)		HXY5.566.003	
材 料	针座:尼龙U94V-2(0)	材 料	插针:黄铜(□0.5*12)
图 样 标 记	视图	重 量 比 例	8:1
审 计	审 定	审 批	审 批
工 艺	工 艺	日 期	2011.8.1
共 1 页		第 1 页	
浙江红星电业有限公司		PH-2WAP2~16WAP2	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Hongxing](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)