


### 技术参数 SPECIFICATIONS

- 线数 (Poles) : 2~15(30)
- 适用线规 (Applicable wires) : AWG30#~24#
- 适应基板厚度 (Applicable PC board thickness) : 1.2~1.6mm
- 温度范围 (Temperature range) : -25℃~85℃
- 额定电压 (Voltage rating) : 250V.Ac/Dc
- 额定电流 (Current rating) : 2A
- 接触电阻 (Contact resistance) :  $\leq 0.02\Omega$
- 绝缘电阻 (Insulation resistance) :  $\geq 1000M\Omega$
- 耐压 (Withstand voltage) : 800V.Ac/1min
- 材料 (Material) :  
 壳体 (Housing) : 尼龙 (Nylon) UL94V-2(0)  
 端子 (Terminal) : 磷青铜 (Phos.bronze Tin/plated)


### 端子 TERMINAL(SAN)

型号 Type	适用线规 Applicable wires	电线外径 O.D of wire ins	数量 Quantity
HX20008-PT	0.05~0.22	30~24	10000PCS/盘
HX20008-PTB	0.05~0.22	30~24	10000PCS/盘


### HX20008-PT (SAN)




### HX20008-PTB(SAN)



### HX20008-Y (SAN)



### 安装尺寸 MOUNTING MEASUREMENT



### 壳体 HOUSING(SAN)

线数 Poles	型号 Type	尺寸 Dimensions(mm)	
		A	B
2	HX20008-2Y	2.0	5.2
3	HX20008-3Y	4.0	7.2
4	HX20008-4Y	6.0	9.2
5	HX20008-5Y	8.0	11.2
6	HX20008-6Y	10.0	13.2
7	HX20008-7Y	12.0	15.2
8	HX20008-8Y	14.0	17.2
9	HX20008-9Y	16.0	19.2
10	HX20008-10Y	18.0	21.2
11	HX20008-11Y	20.0	23.2
12	HX20008-12Y	22.0	25.2
13	HX20008-13Y	24.0	27.2
14	HX20008-14Y	26.0	29.2
15	HX20008-15Y	28.0	31.2
...	...	...	...
30	HX20008-30Y	58.0	61.2

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Hongxing](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)