


技术参数 SPECIFICATIONS

- 线数 (Poles) : 2~15(30)
- 适用线规 (Applicable wires) : AWG30#~24#
- 适应基板厚度 (Applicable PC board thickness) : 1.2~1.6mm
- 温度范围 (Temperature range) : -25℃~85℃
- 额定电压 (Voltage rating) : 250V.Ac/Dc
- 额定电流 (Current rating) : 2A
- 接触电阻 (Contact resistance) : $\leq 0.02\Omega$
- 绝缘电阻 (Insulation resistance) : $\geq 1000M\Omega$
- 耐压 (Withstand voltage) : 800V.Ac/1min
- 材料 (Material) :
壳体 (Housing) : 尼龙 (Nylon) UL94V-2(0)
端子 (Terminal) : 磷青铜 (Phos.bronze Tin/plated)


端子 TERMINAL (SAN)

型号 Type	适用线规 Applicable wires	电线外径 O.D of wire ins	数量 Quantity
HX20008-PT	0.05~0.22	30~24	10000PCS/盘
HX20008-PTB	0.05~0.22	30~24	10000PCS/盘


HX20008-PT (SAN)




HX20008-PTB (SAN)



HX20008-Y (SAN)



安装尺寸 MOUNTING MEASUREMENT



壳体 HOUSING (SAN)

线数 Poles	型号 Type	尺寸 Dimensions (mm)	
		A	B
2	HX20008-2Y	2.0	5.2
3	HX20008-3Y	4.0	7.2
4	HX20008-4Y	6.0	9.2
5	HX20008-5Y	8.0	11.2
6	HX20008-6Y	10.0	13.2
7	HX20008-7Y	12.0	15.2
8	HX20008-8Y	14.0	17.2
9	HX20008-9Y	16.0	19.2
10	HX20008-10Y	18.0	21.2
11	HX20008-11Y	20.0	23.2
12	HX20008-12Y	22.0	25.2
13	HX20008-13Y	24.0	27.2
14	HX20008-14Y	26.0	29.2
15	HX20008-15Y	28.0	31.2
...
30	HX20008-30Y	58.0	61.2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminals](#) category:

Click to view products by [Hongxing](#) manufacturer:

Other Similar products are found below :

[HT-13-10](#) [71M-250-32-NB](#) [01-2065-1-0216](#) [00581P0075](#) [M10-10RX](#) [M10BCK](#) [60205-1](#) [604200-1](#) [60598-1-CUT-TAPE](#) [60617-1-C](#) [60873-1](#) [M14-516R/SK](#) [M14-6RSX](#) [M18-10FLX](#) [M18-8FBX](#) [M18-8R/LX](#) [M18BCK](#) [61314-6-C](#) [61-S](#) [61-SN-A](#) [62-NBM-A](#) [63-S](#) [640179-1](#) [640917-2-CUT-TAPE](#) [6501550002](#) [66107-2-C](#) [66107-4-C](#) [696683-1](#) [696834-1](#) [696861-1](#) [696931-1](#) [696999-1](#) [M8-516RK](#) [M86700006](#) [MA250DMFMX-A](#) [701-2007](#) [701-2307](#) [701-7761-03](#) [70F-110-32-PB](#) [718-N-A](#) [71M-187-20-NBL](#) [71M-250-32-NBL](#) [72F-187-20-NBL](#) [72M-250-32-NBL](#) [7310](#) [73F-250-32](#) [73F-250-32-NBL](#) [73F-250-32-NL](#) [F14-10C](#) [F-1M](#)