


## 技术参数 SPECIFICATIONS


- 线数 (Poles) : 2~16(28)
- 适用线规 (Applicable wires) : AWG30#~24#
- 适应基板厚度 (Applicable PC board thickness) : 1.2~1.6mm
- 温度范围 (Temperature range) : -25℃~85℃
- 额定电压 (Voltage rating) : 250V.Ac/Dc
- 额定电流 (Current rating) : 2A
- 接触电阻 (Contact resistance) :  $\leq 0.02\Omega$
- 绝缘电阻 (Insulation resistance) :  $\geq 1000M\Omega$
- 耐压 (Withstand voltage) : 800V.Ac/1min
- 材料 (Material) :
  - 壳体 (Housing) : 尼龙 (PA66) UL94V-2(0)
  - 端子 (Terminal) : 磷青铜 (Phos.bronze Tin/plated)




### 端子 TERMINAL(JC20)

型号 Type	适用线规 Applicable wires mm <sup>2</sup>	AWG#	电线外径 O.D of wire ins mm	数量 Quantity
HX20010-PT	0.05~0.22	30~24	0.9~1.4	10000PCS/盘


### HX20010-PT(JC20)



## 安装尺寸 MOUNTING MEASUREMENT



### HX20010-Y(JC20)



### 壳体 HOUSING(JC20)

线数 Poles	型号 Type	尺寸Dimensions(mm)	
		A	B
2	HX20010-2Y	2.0	4.5
3	HX20010-3Y	4.0	6.5
4	HX20010-4Y	6.0	8.5
5	HX20010-5Y	8.0	10.5
6	HX20010-6Y	10.0	12.5
7	HX20010-7Y	12.0	14.5
8	HX20010-8Y	14.0	16.5
9	HX20010-9Y	16.0	18.5
10	HX20010-10Y	18.0	20.5
11	HX20010-11Y	20.0	22.5
12	HX20010-12Y	22.0	24.5
13	HX20010-13Y	24.0	26.5
14	HX20010-14Y	26.0	28.5
15	HX20010-15Y	28.0	30.5
16	HX20010-16Y	30.0	32.5
...	...	...	...
28	HX20010-28Y	54.0	56.5

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Hongxing](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)