


□ 技术参数 SPECIFICATIONS


- 线数 (Poles) : 4~40
- 适用线规 (Applicable wires) : AWG28#~24#
- 适应基板厚度 (Applicable PC board thickness) : 1.6mm
- 温度范围 (Temperature range) : -25℃~85℃
- 额定电压 (Voltage rating) : 250V.Ac/Dc
- 额定电流 (Current rating) : 3A
- 接触电阻 (Contact resistance) : $\leq 0.02\Omega$
- 绝缘电阻 (Insulation resistance) : $\geq 1000M\Omega$
- 耐压 (Withstand voltage) : 1000V.Ac/1min
- 材料 (Material) :
 孔座 (Housing) : 尼龙 (PA66) UL94V-2(0)
 针座 (Wafer) : 尼龙 (PA66) UL94V-2(0)
 端子 (Terminal) : 磷青铜 (Phos.bronze Tin/plated)




端子 TERMINAL (PHD)

| 型号 Type | 适用线规 Applicable wires | | 电线外径 O.D of wire ins | 数量 Quantity |
|------------|--------------------------|-------|-------------------------|----------------|
| | mm ² | AWG# | mm | |
| HX20016-PT | 0.08~0.33 | 28~22 | 0.9~1.5 | 10000PCS/盘 |


HX20016-PT (PHD)



HX20017-WAP (PHDS)




HX20017-Y (PHDS)



□ 安装尺寸 MOUNTING MEASUREMENT



HX20017-A (PHDS)



孔座 HOUSING (PHDS)

针座 WAFER (PHDS)

| 线数 Poles | 型号 Type | 尺寸 Dimensions (mm) | | 线数 Poles | 型号 Type | 尺寸 Dimensions (mm) | |
|-------------|-------------|--------------------|------|-------------|-------------|--------------------|-----------|
| | | A | B | | | A | B |
| 4 | HX20017-4Y | 2.0 | 4.5 | 4 | HX20017-4A | HX20017-4WAP | 2.0 8.0 |
| 6 | HX20017-6Y | 4.0 | 6.5 | 6 | HX20017-6A | HX20017-6WAP | 4.0 10.0 |
| 8 | HX20017-8Y | 6.0 | 8.5 | 8 | HX20017-8A | HX20017-8WAP | 6.0 12.0 |
| 10 | HX20017-10Y | 8.0 | 10.5 | 10 | HX20017-10A | HX20017-10WAP | 8.0 14.0 |
| 12 | HX20017-12Y | 10.0 | 12.5 | 12 | HX20017-12A | HX20017-12WAP | 10.0 16.0 |
| 14 | HX20017-14Y | 12.0 | 14.5 | 14 | HX20017-14A | HX20017-14WAP | 12.0 18.0 |
| 16 | HX20017-16Y | 14.0 | 16.5 | 16 | HX20017-16A | HX20017-16WAP | 14.0 20.0 |
| 18 | HX20017-18Y | 16.0 | 18.5 | 18 | HX20017-18A | HX20017-18WAP | 16.0 22.0 |
| 20 | HX20017-20Y | 18.0 | 20.5 | 20 | HX20017-20A | HX20017-20WAP | 18.0 24.0 |
| 22 | HX20017-22Y | 20.0 | 22.5 | 22 | HX20017-22A | HX20017-22WAP | 20.0 26.0 |
| 24 | HX20017-24Y | 22.0 | 24.5 | 24 | HX20017-24A | HX20017-24WAP | 22.0 28.0 |
| 26 | HX20017-26Y | 24.0 | 26.5 | 26 | HX20017-26A | HX20017-26WAP | 24.0 30.0 |
| 28 | HX20017-28Y | 26.0 | 28.5 | 28 | HX20017-28A | HX20017-28WAP | 26.0 32.0 |
| 30 | HX20017-30Y | 28.0 | 30.5 | 30 | HX20017-30A | HX20017-30WAP | 28.0 34.0 |
| 32 | HX20017-32Y | 30.0 | 32.5 | 32 | HX20017-32A | HX20017-32WAP | 30.0 36.0 |
| 34 | HX20017-34Y | 32.0 | 34.5 | 34 | HX20017-34A | HX20017-34WAP | 32.0 38.0 |
| 36 | HX20017-36Y | 34.0 | 36.5 | 36 | HX20017-36A | HX20017-36WAP | 34.0 40.0 |
| 38 | HX20017-38Y | 36.0 | 38.5 | 38 | HX20017-38A | HX20017-38WAP | 36.0 42.0 |
| 40 | HX20017-40Y | 38.0 | 40.5 | 40 | HX20017-40A | HX20017-40WAP | 38.0 44.0 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Hongxing](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [M90C108951C](#)
[70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [80.063.4001.1](#)
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-024-10-](#)
[001000](#) [803-93-012-10-001000](#)