


技术参数 SPECIFICATIONS


- 线数 (Poles) : 2~15
- 适用线规 (Applicable wires) : AWG28#~22#
- 温度范围 (Temperature range) : -25°C~85°C
- 额定电压 (Voltage rating) : 250V.Ac/Dc
- 额定电流 (Current rating) : 3A
- 接触电阻 (Contact resistance) : $\leq 0.02\Omega$
- 绝缘电阻 (Insulation resistance) : $\geq 1000M\Omega$
- 耐压 (Withstand voltage) : 1000V.Ac/1min
- 材料 (Material) :
 - 插头 (Plug housing) : 尼龙 (PA66) UL94V-2(0)
 - 插座 (Receptacle housing) : 尼龙 (PA66) UL94V-2(0)
 - 插片 (Retainer) : 尼龙 (PA66) UL94V-2(0)
 - 端子 (Terminal) : 磷青铜 (Phos.bronze Tin/plated)




端子 TERMINAL (YST200-C/YDT200-C)

| 型号 Type | 适用线规 Applicable wires mm / AWG# | 电线外径 O.D of wire ins mm | 数量 Quantity |
|------------|---------------------------------------|-------------------------------|----------------|
| HX20022-PT | 0.08~0.33 | 28~22 | 10000PCS/盘 |
| HX20022-RT | 0.08~0.33 | 28~22 | 10000PCS/盘 |


HX20022-RT (YDT200-C)




HX20022-PT (YST200-C)




HX20022-R (SMH200-HPR)



HX20022-P (SMH200-H)



HX20022-S (SMH200-HRT)



针座 WAFER

针座与HX20020-A-WA (HY) 针座适用 (P36)
Wafer is interchangeable with HX20020-A-WA (P36)

插座 HOUSING (SMH200-H/SMH200-HPR)

| 线数 Poles | 型号 Type | 尺寸Dimensions(mm) | | | |
|-------------|---------------|------------------|------|------|------|
| | | A | B | C | D |
| 2 | HX20022-2P/R | 2.0 | 4.6 | 7.0 | 6.0 |
| 3 | HX20022-3P/R | 4.0 | 6.6 | 9.0 | 8.0 |
| 4 | HX20022-4P/R | 6.0 | 8.6 | 11.0 | 10.0 |
| 5 | HX20022-5P/R | 8.0 | 10.6 | 13.0 | 12.0 |
| 6 | HX20022-6P/R | 10.0 | 12.6 | 15.0 | 14.0 |
| 7 | HX20022-7P/R | 12.0 | 14.6 | 17.0 | 16.0 |
| 8 | HX20022-8P/R | 14.0 | 16.6 | 19.0 | 18.0 |
| 9 | HX20022-9P/R | 16.0 | 18.6 | 21.0 | 20.0 |
| 10 | HX20022-10P/R | 18.0 | 20.6 | 23.0 | 22.0 |
| 11 | HX20022-11P/R | 20.0 | 22.6 | 25.0 | 24.0 |
| 12 | HX20022-12P/R | 22.0 | 24.6 | 27.0 | 26.0 |
| 13 | HX20022-13P/R | 24.0 | 26.6 | 29.0 | 28.0 |
| 14 | HX20022-14P/R | 26.0 | 28.6 | 31.0 | 30.0 |
| 15 | HX20022-15P/R | 28.0 | 30.6 | 33.0 | 32.0 |

插片 RETAINER (SMH200-HRT)

| 线数 Poles | 型号 Type | 尺寸Dimensions(mm) | |
|-------------|-------------|------------------|------|
| | | A | B |
| 2 | HX20022-2S | 3.4 | 5.9 |
| 3 | HX20022-3S | 5.4 | 7.9 |
| 4 | HX20022-4S | 7.4 | 9.9 |
| 5 | HX20022-5S | 9.4 | 11.9 |
| 6 | HX20022-6S | 11.4 | 13.9 |
| 7 | HX20022-7S | 13.4 | 15.9 |
| 8 | HX20022-8S | 15.4 | 17.9 |
| 9 | HX20022-9S | 17.4 | 19.9 |
| 10 | HX20022-10S | 19.4 | 21.9 |
| 11 | HX20022-11S | 21.4 | 23.9 |
| 12 | HX20022-12S | 23.4 | 25.9 |
| 13 | HX20022-13S | 25.4 | 27.9 |
| 14 | HX20022-14S | 27.4 | 29.9 |
| 15 | HX20022-15S | 29.4 | 31.9 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Hongxing](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#)
[66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-](#)
[5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#) [800-90-001-](#)
[10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-001000](#)
[803-43-024-10-001000](#)