


技术参数 SPECIFICATIONS


- 线数 (Poles) : 2~15
- 适用线规 (Applicable wires) : AWG28#~24#
- 温度范围 (Temperature range) : -25℃~85℃
- 额定电压 (Voltage rating) : 250V.Ac/Dc
- 额定电流 (Current rating) : 2A
- 接触电阻 (Contact resistance) : $\leq 0.02\Omega$
- 绝缘电阻 (Insulation resistance) : $\geq 1000M\Omega$
- 耐压 (Withstand voltage) : 800V.Ac/1min
- 材料 (Material) :
 - 插头 (Plug housing) : 尼龙 (PA66) UL94V-2(0)
 - 插座 (Receptacle housing) : 尼龙 (PA66) UL94V-2(0)
 - 端子 (Terminal) : 磷青铜 (Phos.bronze Tin/plated)




端子 TERMINAL (20032)

| 型号 Type | 适用线规 Applicable wires mm ² AWG# | 电线外径 O.D of wire ins mm | 数量 Quantity |
|------------|--|-------------------------------|----------------|
| HX20032-PT | 0.08~0.22 28~24 | 0.9~1.5 | |
| HX20032-RT | 0.08~0.22 28~24 | 0.9~1.5 | |

HX20032-PT




HX20032-P




安装尺寸 MOUNTING MEASUREMENT



HX20032-RT



HX20032-R



插头 PLUG HOUSING (20032)

| 线数 Poles | 型号 Type | 尺寸 Dimensions(mm) | | |
|-------------|-------------|-------------------|------|------|
| | | A | B | C |
| 2 | HX20032-2P | 2.0 | 6.6 | 4.6 |
| 3 | HX20032-3P | 4.0 | 8.6 | 6.6 |
| 4 | HX20032-4P | 6.0 | 10.6 | 8.6 |
| 5 | HX20032-5P | 8.0 | 12.6 | 10.6 |
| 6 | HX20032-6P | 10.0 | 14.6 | 12.6 |
| 7 | HX20032-7P | 12.0 | 16.6 | 14.6 |
| 8 | HX20032-8P | 14.0 | 18.6 | 16.6 |
| 9 | HX20032-9P | 16.0 | 20.6 | 18.6 |
| 10 | HX20032-10P | 18.0 | 22.6 | 20.6 |
| 11 | HX20032-11P | 20.0 | 24.6 | 22.6 |
| 12 | HX20032-12P | 22.0 | 26.6 | 24.6 |
| 13 | HX20032-13P | 24.0 | 28.6 | 26.6 |
| 14 | HX20032-14P | 26.0 | 30.6 | 28.6 |
| 15 | HX20032-15P | 28.0 | 32.6 | 30.6 |

插座 RECEPTACLE HOUSING (20032)

| 线数 Poles | 型号 Type | 尺寸 Dimensions(mm) | | |
|-------------|-------------|-------------------|------|------|
| | | A | B | C |
| 2 | HX20032-2R | 2.0 | 8.0 | 4.6 |
| 3 | HX20032-3R | 4.0 | 10.0 | 6.6 |
| 4 | HX20032-4R | 6.0 | 12.0 | 8.6 |
| 5 | HX20032-5R | 8.0 | 14.0 | 10.6 |
| 6 | HX20032-6R | 10.0 | 16.0 | 12.6 |
| 7 | HX20032-7R | 12.0 | 18.0 | 14.6 |
| 8 | HX20032-8R | 14.0 | 20.0 | 16.6 |
| 9 | HX20032-9R | 16.0 | 22.0 | 18.6 |
| 10 | HX20032-10R | 18.0 | 24.0 | 20.6 |
| 11 | HX20032-11R | 20.0 | 26.0 | 22.6 |
| 12 | HX20032-12R | 22.0 | 28.0 | 24.6 |
| 13 | HX20032-13R | 24.0 | 30.0 | 26.6 |
| 14 | HX20032-14R | 26.0 | 32.0 | 28.6 |
| 15 | HX20032-15R | 28.0 | 34.0 | 30.6 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Hongxing](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#)
[66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#)
[80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-001000](#)
[803-43-024-10-001000](#)