


技术参数 SPECIFICATIONS

- ❑ 线数 (Poles) : 2~15(23)
- ❑ 适用线规 (Applicable wires) : AWG28#~22#
- ❑ 适应基板厚度 (Applicable PC board thickness) : 1.2~1.6mm
- ❑ 温度范围 (Temperature range) : -25℃~85℃
- ❑ 额定电压 (Voltage rating) : 250V.Ac/Dc
- ❑ 额定电流 (Current rating) : 2A
- ❑ 接触电阻 (Contact resistance) : $\leq 0.02\Omega$
- ❑ 绝缘电阻 (Insulation resistance) : $\geq 1000M\Omega$
- ❑ 耐压 (Withstand voltage) : 1000V.Ac/1min
- ❑ 材料 (Material) :
 - 壳体 (Housing) : 尼龙 (PA66) UL94V-2(0)
 - 端子 (Terminal) : 磷青铜 (Phos.bronze Tin/plated)

端子 TERMINAL(JC25)


型号 Type	适用线规 Applicable wires		电线外径 O.D of wire ins mm	数量 Quantity
	mm	AWG#		
HX25008-PT	0.08~0.3	28~22	1.0~1.8	7000PCS/盘

HX25008-PT(JC25)



安装尺寸 MOUNTING MEASUREMENT

HX25008-Y(JC25)



壳体 HOUSING(JC25)

线数 Poles	型号 Type	尺寸 Dimensions(mm)	
		A	B
2	HX25008-2Y	2.5	5.6
3	HX25008-3Y	5.0	8.1
4	HX25008-4Y	7.5	10.6
5	HX25008-5Y	10.0	13.1
6	HX25008-6Y	12.5	15.6
7	HX25008-7Y	15.0	18.1
8	HX25008-8Y	17.5	20.6
9	HX25008-9Y	20.0	23.1
10	HX25008-10Y	22.5	25.6
11	HX25008-11Y	25.0	28.1
12	HX25008-12Y	27.5	30.6
13	HX25008-13Y	30.0	33.1
14	HX25008-14Y	32.5	35.6
15	HX25008-15Y	35.0	38.1
...
23	HX25008-23Y	55.0	58.1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Hongxing](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)
[800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-001000](#) [803-43-024-10-001000](#)