


技术参数 SPECIFICATIONS


- 线数 (Poles) : 12、16、20、28
- 适用线规 (Applicable wires) : AWG30#~20#
- 适应基板厚度 (Applicable PC board thickness) : 1.6mm
- 温度范围 (Temperature range) : -25℃~85℃
- 额定电压 (Voltage rating) : 250V.Ac/Dc
- 额定电流 (Current rating) : 3A
- 接触电阻 (Contact resistance) : ≤0.02Ω
- 绝缘电阻 (Insulation resistance) : ≥800MQ
- 耐压 (Withstand voltage) : 1000V.Ac/1min
- 材料 (Material) :
 孔座 (Housing) : 尼龙 (PA66) UL94V-2(0)
 针座 (Wafer) : 尼龙 (PA66) UL94V-2(0)
 端子 (Terminal) : 磷青铜 (Phos.bronze Tin/plated)




端子 TERMINAL (SA)

型号 Type	适用线规 Applicable wires		电线外径 O.D of wire ins	数量 Quantity
	mm	AWG#	mm	
HX25412-01PT	0.05~0.14	30~26	0.8~1.2	5000PCS/盘
HX25412-21PT	0.18~0.5	24~20	1.1~1.6	5000PCS/盘

HX25412-01PT (SA)



HX25412-21PT (SA)



线数 (Poles)	插头 (Plug housing)	直针座 (Wafer)	弯针座 (Wafer)	安装尺寸 (Mounting measurement)
12	HX25412-12Y (SA) 	HX25413-12A 	HX25413-12WA (HZT) 	 (HX25413-12WA)
16	HX25412-16Y (SA) 	HX25413-16A 安装尺寸 	HX25413-16WA (HZT) HX25414-16WA 	 (HX25413-16WA) (HX25414-16WA)
20	HX25412-20Y (SA) 	HX25413-20A 	HX25413-20WA (HZT) 	 (HX25413-20WA)
28	HX25412-12Y (SA) 	HX25413-28A 	HX25413-28WA (HZT) 	 (HX25413-28A) (HX25413-28WA)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Hongxing](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)