


技术参数 SPECIFICATIONS

- 线数 (Poles) : 2、3、4、6、9
- 适用线规 (Applicable wires) : AWG22#~18#
- 温度范围 (Temperature range) : -25℃~85℃
- 额定电压 (Voltage rating) : 300V.Ac/Dc
- 额定电流 (Current rating) : 10A
- 接触电阻 (Contact resistance) : ≤0.01Ω
- 绝缘电阻 (Insulation resistance) : ≥1000MΩ
- 耐压 (Withstand voltage) : 1200V.Ac/1min
- 材料 (Material) :
 插头 (Plug housing) : 尼龙 (PA66) UL94V-2(0)
 插座 (Receptacle housing) : 尼龙 (PA66) UL94V-2(0)
 端子 (Terminal) 黄铜 (Brass Tin/plated)

端子 TERMINAL

型号 Type	适用线规 Applicable wires		电线外径 O.D of wire ins mm	数量 Quantity
	mm	AWG#		
HX28050-PT	0.33~0.82	22-18	1.7~3.0	4000PCS/盘
HX28050-RT	0.33~0.82	22-18	1.7~3.0	3000PCS/盘

HX28050-PT(DJ621-E2.8x0.5A-B)



HX28050-RT(DJ611-2.8x0.5A-B)



线数 (Poles)	额定电压 (Voltage rating)	额定电流 (Current rating)	插头 (Plug housing)		插座 (Receptacle housing)	
			型号	尺寸图	型号	尺寸图
2	300V	10A	HX28050-2P(DJ7021A-2.8-21)		HX28050-2R(DJ7021A-2.8-11)	
3	300V	10A	HX28050-3P(DJ7031A-2.8-21)		HX28050-3R(DJ7031A-2.8-11)	
4	300V	8A	HX28050-4P(DJ7041A-2.8-21)		HX28050-4R(DJ7041A-2.8-11)	
6	300V	8A	HX28050-6P(DJ7061A-2.8-21)		HX28050-6R(DJ7061A-2.8-11)	
9	300V	8A	HX28050-9P(DJ7091A-2.8-21)		HX28050-9R(DJ7090A-2.8-11)	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminals](#) category:

Click to view products by [Hongxing](#) manufacturer:

Other Similar products are found below :

[HT-13-10](#) [71M-250-32-NB](#) [01-2065-1-0216](#) [00581P0075](#) [M10-10RX](#) [M10BCK](#) [60205-1](#) [604200-1](#) [60598-1-CUT-TAPE](#) [60617-1-C](#) [60873-1](#) [M14-516R/SK](#) [M14-6RSX](#) [M18-10FLX](#) [M18-8FBX](#) [M18-8R/LX](#) [M18BCK](#) [61314-6-C](#) [61-S](#) [61-SN-A](#) [62-NBM-A](#) [63-S](#) [640179-1](#) [640917-2-CUT-TAPE](#) [6501550002](#) [66107-2-C](#) [66107-4-C](#) [696683-1](#) [696834-1](#) [696861-1](#) [696931-1](#) [696999-1](#) [M8-516RK](#) [M86700006](#) [MA250DMFMX-A](#) [701-2007](#) [701-2307](#) [701-7761-03](#) [70F-110-32-PB](#) [718-N-A](#) [71M-187-20-NBL](#) [71M-250-32-NBL](#) [72F-187-20-NBL](#) [72M-250-32-NBL](#) [7310](#) [73F-250-32](#) [73F-250-32-NBL](#) [73F-250-32-NL](#) [F14-10C](#) [F-1M](#)