


## ■ 技术参数 SPECIFICATIONS

- 适用线规 (Applicable wires) : AWG24#~16#
- 温度范围 (Temperature range) : -25℃~85℃
- 额定电压 (Voltage rating) : 300V.Ac/Dc
- 额定电流 (Current rating) : 15A max
- 接触电阻 (Contact resistance) : ≤0.01Ω
- 绝缘电阻 (Insulation resistance) : ≥1000MΩ
- 耐压 (Withstand voltage) : 2000V.Ac/1min
- 材料 (Material) :
  - 壳体 (Housing) : 尼龙 (PA66) UL94V-2 (0)
  - 端子 (Terminal) : 黄铜 (Brass Tin/plated)
  - 磷青铜 (phos.bronze Tin/plated)

### .187" /250# 端子 TERMINAL

型号 Type	适用线规 Applicable wires	材料 Material	尺寸 Dimensions (mm)				示意图 Sample	数量 Quantity		
			mm <sup>2</sup>	AWG#	W	L			E	材料厚度 Thickness
HX480N-01T	STO-01T-187N		0.2~0.5	24~20	5.7	15.0	6.5	0.35	A	10000PCS/卷
HX480N-41T	STO-41T-187N	黄铜 Brass	0.5~1.25	20~16	5.7	15.0	6.5	0.35	A	10000PCS/卷
HX480N-61T	STO-61T-187N		(UL1015) 20+18		5.7	15.0	6.5	0.35		10000PCS/卷
HX4.8Z-21T	730494-3	磷青铜 Phos.bronze	0.5~1.25	20~16	5.6	18.0	6.0	0.3	B	2500PCS/盒




型号 Type	尺寸 Dimensions (mm)				
	A	B	C	D	F
.187"	7.0	3.6	4.8	φ1.5	0.5

### HX480N-1T


(A)



### HX4.8Z-2A (610455-2P/35941-0200)




### HX4.8Z-3A (611191)




### HX4.8Z-21T

(B)



### HX4.8XZ-3P (610439-3P)



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Hongxing](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[820-22-008-30-001101](#) [821-22-002-10-001101](#)