


技术参数 SPECIFICATIONS

- 适用线规 (Applicable wires) : AWG24#~12#
- 温度范围 (Temperature range) : -20°C~85°C
- 额定电压 (Voltage rating) : 300V.Ac/Dc
- 额定电流 (Current rating) : 18A max
- 接触电阻 (Contact resistance) : $\leq 0.01\Omega$
- 绝缘电阻 (Insulation resistance) : $\geq 1000M\Omega$
- 耐压 (Withstand voltage) : 1500V.Ac/1min
- 材料 (Material) :
 - 壳体 (Housing) : 尼龙 (PA66) UL94V-2 (0)
 - 端子 (Terminal) : 磷青铜 (Phos.bronze Tin/plated)
 - 端子 (Terminal) : 黄铜 (Brass Tin/plated)

端子 TERMINAL

| 型号 Type | 适用线规 Applicable wires | | 材料 Material | 材料厚度 Thickness mm | 数量 Quantity | 型号 Type | 适用线规 Applicable wires | | 材料 Material | 材料厚度 Thickness mm | 数量 Quantity | |
|------------|--------------------------|----------|----------------|-------------------------|----------------|--------------|--------------------------|----------|----------------|-------------------------|----------------|-----------|
| | mm ² | AWG# | | | | | mm ² | AWG# | | | | |
| HX630N-21T | ST0-21-250N | 0.3~0.75 | 22~18 | 0.4 | 7000PCS/包 | HX63092-PT | 0.52~2.1 | 20~14 | 黄铜 | 0.35 | 6000PCS/包 | |
| HX630N-41T | ST0-61-250N | 0.75~2.0 | 18~14 | 0.4 | 6000PCS/包 | HX50008-01PT | 0.22~0.5 | 24~20 | 黄铜 | 0.3 | 2000PCS/包 | |
| HX630N-61T | ST0-81-250N | 2.0~3.5 | 14~12 | 0.4 | 5000PCS/包 | HX50008-21PT | 0.75~2.0 | 18~14 | 黄铜 | 0.3 | 1500PCS/包 | |
| | | | | | | HX630S-61TO | SFPS-61T-240 | 0.75~2.0 | 18~14 | 黄铜 | 0.43 | 4000PCS/包 |



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Hongxing](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)