



PIN	∅2.0	∅2.5
APPD.		

注力度要求: 插力11N-20N, 拔力12-20N.
(常规不带凹槽插头)

					CE	A3 2020.8.07 3 依据历史生产数据修正尺寸4.2至4.6	GYW		
						A2 2016.6.20 2 增加重点尺寸	liu		
						A1 2015.12.20 1 弹片增加骨位加大插拔力	liu		
6	DC005 PING	BRASS	1	Ni PLATED	ABOVE 5mm: ±0.2	ANGULAR ±1°			
5	DC005 4#FLAT PIECE	BRASS	1	Ag PLATED			NO	BY	APPD
4	DC005 2#CURVE PIECE	BRASS	1	Ag PLATED	TITLE:DC JACK		ROHS COMPLIANT	CHK'D	
3	DC005Q 3#SPRING	SUS	1	Ag PLATED	MODEL:DC-005Q 2.0-SU				
2	DC005 COVER	PBT	1	YELLOW/BLACK/RED	HAOYU(HONGKONG)LIMITED 皓宇(香港)有限公司		A		
1	DC005 CASE	PBT/PA66+PA6T	1	YELLOW/BLACK/RED					
NO.	PART NAME	MATERIAL	QTY	FINISHING					REV: A3

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Power Connectors](#) category:

Click to view products by [HOOYA](#) manufacturer:

Other Similar products are found below :

[163-0308-EX](#) [163-4012-EX](#) [163-4117-EX](#) [163-MJ22-EX](#) [171-0721-EX](#) [KLDX-SMT-0202-BPTR](#) [163-0179-EX](#) [163-4015-EX](#) [171-0722-E](#)
[K596](#) [KLD-0201-BC](#) [4C6831AX](#) [LCB60PW-M](#) [LCB30PW-M](#) [LCB60PB-M](#) [LCC30PB-M](#) [LCB50PW-M](#) [LCB50-M](#) [LCB60-F](#) [LCC30-M](#)
[LCB40PW-M](#) [LCC30PW-M](#) [LCB50-F](#) [LCB40-F](#) [LCC40-M](#) [LCC40PB-M](#) [LCB40PB-M](#) [LCC40-F](#) [LCB60-M](#) [LCC40PW-M](#) [LCB50PB-M](#)
[513820200](#) [DC-S014A-D025-20A](#) [DC007B-2.5-J](#) [DC005-2.5](#) [DC005-2.5-T](#) [DC-S019A-D025-10A](#) [DC007B-2.0](#) [DC-018-2.5A-2.5](#) [DC-005-](#)
[A25](#) [DC-005-A20](#) [DC-002-100](#) [DC-031A-130](#) [DC-031A-100](#) [DC-003A-130](#) [DC-045-130](#) [DC-192-130](#) [DC-033-130](#) [DC-011-100](#) [DC-002F-](#)
[130](#)