



技术要求:

- 1: 产品插拔力10-20N.
- 2: 盐雾测试48H.
- 3: 接触电阻<70毫欧.
- 4: "*"重点尺寸.
- 5: 产品外观无电镀脱皮, 红胶不满等不良.

| | | | | TOLERANCE | | A2 | 2017.04.11 | △ 重点尺寸1.7改为1.5 | | GYW |
|-----|-----------------------|-------------|-----|--------------------|---|----|------------|----------------|--------------------|---------|
| | | | | UNLESS SPECIFIED | | A1 | 2017.03.16 | 增加产品技术要求 | | GYW |
| | | | | UP TO 5mm: ±0.1 | ANGULAR | A0 | 2017.03.03 | 首次发行 | | GYW |
| | | | | ABOVE 5mm: ±0.2 | ±1° | NO | DATE | REVISIONS | | BY APPD |
| 5 | DC086 COVER | EPOXY RESIN | 1 | RED | TITLE:DC JACK | | UNIT : MM | ROHS COMPLIANT | DWN | |
| 4 | DC086 INSULATOR | PA66 | 1 | BRACK | MODEL:DC-086-2.1-PU | | SCALE: 4:1 | CHK'D | | |
| 3 | DC086 φ2.1PIN | BRASS | 1 | 80-120U" Ni PLATED | HAOYU(HONGKONG)LIMITED 皓宇(香港)有限公司 | | APPD | | PRO.AGL: REV :A2 | |
| 2 | DC086 SHELL | BRASS | 1 | 80-120U" Ni PLATED | | | | | | |
| 1 | DC086 SPRING TERMINAL | PHO-BRONZE | 1 | 80-120U" Ni PLATED | | | | | | |
| NO. | PART NAME | MATERIAL | QTY | FINISHING | | | | | | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Power Connectors](#) category:

Click to view products by [HOOYA](#) manufacturer:

Other Similar products are found below :

[KLDX-SMT-0202-BPTR](#) [171-0722-E](#) [K596](#) [KLD-0201-BC](#) [4C6831AX](#) [10073976-112LF](#) [LCB60PW-M](#) [LCB30PW-M](#) [LCB60PB-M](#)
[LCC30PB-M](#) [LCB50PW-M](#) [LCB50-M](#) [LCB60-F](#) [LCC30-M](#) [LCB40PW-M](#) [LCC30PW-M](#) [LCB50-F](#) [LCB40-F](#) [LCB30-F](#) [LCC40-M](#)
[LCC40PB-M](#) [LCB40PB-M](#) [LCC40-F](#) [LCB60-M](#) [LCC40PW-M](#) [LCB50PB-M](#) [DC-002-100](#) [DC-031A-130](#) [DC-031A-100](#) [DC-003A-130](#)
[DC-045-130](#) [DC-192-130](#) [DC-033-130](#) [DC-011-100](#) [DC-002F-130](#) [DC-002-130](#) [DB-14-2F](#) [DC-183B](#) [DC-060-04A](#) [DC-099-200](#) [DC-015-](#)
[250-A](#) [DC-016-200-A](#) [DC-005A-200](#) [DC-044A-200](#) [DC-088-200](#) [DC-022A-200](#) [DC-038-150](#) [DC-012A-250](#) [DC-005C-130](#) [DC-012A-200](#)