



电话 : 0769-82310511-867  
 邮箱 : hooya89@hooya.hk  
 V : hooya89

皓宇电子  
 HOYA ELECTRONICS

Rating: 3A 125V AC  
 Contact Resistance: 50m $\Omega$  Max  
 Insulation Resistance: DC 500V 100m $\Omega$  Min  
 Dielectric Strength: AC 1000V 1minute  
 Total travel: 1.4 $\pm$ 0.4mm  
 Operating Force: 200 $\pm$ 50gf  
 Operating Life: 10,000 cycles  
 Operating Temperature: 0 $^{\circ}$ C~85 $^{\circ}$ C  
 Function: OFF-(ON)

				TOLERANCE UNLESS SPECIFIED							
				UP TO 5mm: $\pm 0.1$	ANGULAR						
				ABOVE 5mm: $\pm 0.2$	$\pm 1^{\circ}$	NO	DATE	REVISIONS		BY	APPD
4	NUT	BRASS	1	Ni-Plating	TITLE: PUSH SWITCH		UNIT : MM	ROHS	DWN		
3	TERMINAL	BRASS	2	Ag/Sn-Plating	MODEL: PB-11D02-N-B		SCALE: 1:1	COMPLIANT	CHK'D		
2	CAP	PBT	1		 HAOYU(HONG KONG)LIMITED 皓宇(香港)有限公司		APPD		PRO.AGL: 		REV :A0
1	BASE	BRASS	1	Ni-Plating							
NO.	PART NAME	MATERIAL	QTY	FINISHING							

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [HOOYA](#) manufacturer:*

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE 01A](#)  
[MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#)  
[861K11911T01A07](#) [861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#)  
[A2PMA1X03EC56](#) [A3A-7310](#) [A3A-7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#)  
[1211500044](#) [121194](#) [1212MRA](#) [1232A6NF](#) [1241.1183.7047](#) [121489](#) [1223A2ULCSA](#) [1241.1183.8000](#) [1241.1183.8029](#) [D5P-MT4](#)  
[13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#)