


P.C.B. LAYOUT



SCHEMATIC

SPECIFICATION

1. Rating: DC 12V 0.3A
2. Function: 2P2T
3. Contact Resistance: <70mΩMAX
4. Operating Force: 180±80gf, 250±100gf
5. Life test: 10,000 cycles

S: 自锁

E: 操作力250±100gf

				TOLERANCE UNLESS SPECIFIED							
				UP TO 5mm: ±0.1	ANGULAR	1					
				ABOVE 5mm: ±0.2	±1°	NO	DATE	REVISIONS		BY	APPD
5	CAM STICK	SUS	1	NATURAL	TITLE:VERTICAL PUSH SWITCH		UNIT : MM	ROHS COMPLIANT	DWN		
4	SPRING	SUS	1	NATURAL	MODEL:PB-22E60PA-S-E		SCALE: 5:1	CHK'D			
3	CASE	PA66/0.3mm BRASS	1	GREY/Ag PLATED	HAOYU(HONGKONG)LIMITED 皓宇(香港)有限公司		APPD				
2	COVER	PA66	1	BLACK			PRO.AGL:		REV : A		
1	KNOB	PA66/0.045mm PBS	1	WHITE/BLACK/Ag CLAD							
NO.	PART NAME	MATERIAL	QTY	FINISHING							

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pushbutton Switches](#) category:

Click to view products by [HOOYA](#) manufacturer:

Other Similar products are found below :

[8971K1133](#) [LW1L-M1C10V-A](#) [LW2L-M1C20M-A](#) [M22-D-R-GB0/K11](#) [67081K512X](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#)
[FLT 2U EE 01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#)
[860K11911T01A](#) [861901](#) [861K11911T01A07](#) [861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [8646ABUL](#) [9533CD4+U574+U4922](#) [95-414.000](#) [99-453.837](#) [A22NZBGANGA](#) [A22NZBMMNGA](#) [A22NZBNANGA](#) [A22NZMPATRA](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-7340](#)
[12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#) [1211500044](#) [1211580012](#) [121194](#)
[1212MRA](#) [1241.1183.7047](#) [121489](#) [1223A2ULCSA](#) [1241.1183.8000](#)