

# SMD CRYSTAL UNITS



## • E2SB Series 2.5\*2.0 Seam Sealing Crystal



#### **FEATURES**


- Very Compact and thin (2.5\*2.0\*0.65mm max.)
- Frequency range of 12M to 62.5M with Fund
- Excellent electrical performance, ideal for OA (office automation), AV (audiovisual), Bluetooth and Wireless LAN applications
- Excellent heat resistance and shock resistance
- Lead-free. Meets the requirements for re-flow profiling using lead -free solder


### **Electrical Specifications**


Item	Type	E2SB			
Frequency Range	F0	12 to 15.999MHz	16 to 19.999MHz	20 to 25.999MHz	26 to 62.500MHz
Mode of Vibration		Fundamental			
Load Capacitance	CL	8 to 16pF			
Frequency Tolerance	△F/ F0	±10ppm,±15ppm,±30ppm(At 25℃)			
Equivalent Series Resistance	ESR	120 Ω max.	100 Ω max.	80 Ω max.	50 Ω max.
Temperature Stability	TC	$\pm 10$ ppm, $\pm 15$ ppm, $\pm 30$ ppm(Refer to $25$ °C)			
Operating Temperature Range	Topr	<b>-</b> 20~+70°C, <b>-</b> 30~+85°C Option			
Storage Temperature Range	Tstg	−55~+125°C			
Shunt Capacitance	C0	3pF max.			
Insulator Resistance	IR	500M Ω min. (At 100Vpc)			
Drive Level	DL	50μW <b>(</b> 100μW max. <b>)</b>			
Aging	Fa	±2ppm max. (At 25°C, First year)			
Packing Unit		3000pcs/reel			

<sup>\*\*</sup>Please contact us for inquiries regarding other Specifications


### **Mechanical Dimensions(mm)**







#### Recommended Solder Pattern



TAIWAN:

5

HOSONIC ELECTRONIC CO., LTD.
23-1 LANE 84. CHUN YING ST. SHULIN CHEN.
TAIPEI 23804. TAIWAN
WEB SITE:http://www.hosonic.com



#### CHINA:

HANGZHOU HOSONIC ELECTRONIC CO., LTD. NO.242 LIANGBO ROAD. LIANGZHU TOWN. YUHANG DISTRICT, HANGZHOU, ZHEJIANG, CHINA

WEB SITE:http://www.hosonic.com



Specifications are subject to change without notice

### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Crystals category:

Click to view products by Hosonic manufacturer:

Other Similar products are found below:

CX3225GB25000M0PPSZ1 718-13.2-1 MC405 32.0000K-R3:PURE SN 7A-40.000MAAE-T FL2000085 99-BU 9B-15.360MBBK-B 9C-7.680MBBK-T H10S-12.000-18-EXT-TR ABC2-6.000MHZ-D4Z-T ABLS-20.000MHZ-D2-T ABS071-32.768KHZ-6-T R38-32.768-12.5-5PPM-NPB BTD1062E05A-513 21U15A-21.4MHZ RTX-781DF1-S-20.950 LFXTAL066198Cutt 9C-14.31818MBBK-T A-11.000MHZ-27 ABL-27.000MHZ-B4Y-T ABM11-132-24.000MHZ-T3 ABM3B1-25.000MHZ-D2Y-T SPT2A-.032768B SPT2A.032768G SSPT7F-9PF20-R FX325BS-38.88EEM1201 LFXTAL065253Cutt LFXTAL066431Cutt XT9S20ANA14M7456 XT9SNLANA16M 7A-24.576MBBK-T 7B-30.000MBBK-T MMCC2R32.7680KHZ 7A-14.31818MBBK-T 6504-202-1501 6526-202-1501 ABLS-12.000MHZ-B2Y-T 7A-10.000MBBK-T SG636PCE-20.000MC 3404 E1SAA18-25.000M TR CM315D32768EZFT C1E-24.000-7-2020-R C1E-19.200-12-1530-X-R C1E-16.000-12-1530-X-R ABM11-16.000MHZ-9-B1U-T FL5000014 EUCA18-3.1872M FX0800015 425F35E027M0000