

FAST SWITCHING DIODES

1SS355

FEATURES

Small surface mounting type.

High Speed.(trr=1.2ns Typ.)

High reliability with high surge current handling capability.



MARKING: A

MAXIMUM RATINGS (TA=25 °C unless otherwise noted)


Parameter	Symbol	Value	Units	
Non-Repetitive Peak reverse voltage	V_{RM}	90	V	
DC Blocking	V _R	80	V	
Forward Continuous Current	I _{FM}	225	mA	
Average Rectified Output Current	lo	100	mA	
Surge current (1s)	I _{surge}	500	mA	
Junction temperature	Tj	125	$^{\circ}$	
Storage temperature	T _{STG}	55-125	$^{\circ}$ C	


ELECTRICAL CHARACTERISTICS (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Min	Тур	Max	Unit	Conditions
Forward voltage	V _F			1.2	V	I _F =100mA
Reverse current	I _R			0.1	μΑ	V _R =80 V
Capacitance between terminals	Ст			3	pF	V _R =0V,f=1MHz
Reverse Recovery Time	t _{rr}			4	ns	I _F = 10mA V=6 V R _L =100 Ω




1SS355 Typical Characteristics






Capacitance between terminals characteristics 10 2 4 8 12 14 Reverse Voltage, VR (V)



Surge Current Characteristics





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Diodes - General Purpose, Power, Switching category:

Click to view products by Hottech manufacturer:

Other Similar products are found below:

MMBD3004S-13-F RD0306T-H DSE010-TR-E BAV17-TR BAV19-TR 1N3611 NTE156A NTE574 NTE6244 1SS181-TP 1SS193,LF 1SS400CST2RA SDAA13 SHN2D02FUTW1T1G LS4151GS08 FC903-TR-E 1N4449 1N456A 1N4934-E3/73 1N914B 1N914BTR 1SS226-TP RFUH20TB3S D291S45T BAV300-TR BAW56DWQ-7-F BAW75-TAP MM230L-CAA IDW40E65D1 JAN1N3600 LL4151-GS18 053684A SMMSD4148T3G 707803H NSVDAN222T1G CDSZC01100-HF LL4150-M-08 1N4454-TR BAV199E6433HTMA1 BAS28-7 BAW56HDW-13 BAS28 TR VS-HFA04SD60STR-M3 NSVM1MA152WKT1G RGP30D-E3/73 BAV99TQ-13-F BAS21DWA-7 NTE6250 NTE582-4 NTE582-6