


SWITCHING DIODE

FEATURES

- Fast Switching Speed
- For General Purpose Switching Applications
- High Conductance

MARKING: A6





MAXIMUM RATINGS (TA=25°C unless otherwise noted)


Parameter	Symbol	Limit	Unit
Non-Repetitive Peak Reverse Voltage	V_{RM}	100	V
Peak Repetitive Peak ReverseVoltage Working Peak Reverse Voltage DC Blocking Voltage	V _{rrm} V _{rwm} V _r	75	V
RMS Reverse Voltage	V _{R(RMS)}	53	V
Forward Continuous Current	I_{FM}	300	mA
Average Rectified Output Current	Io	150	mA
Peak Forward Surge Current @t=1.0μs	I_{FSM}	2.0	A
@t=1.0s	_	1.0	222
Power Dissipation	P_{D}	225	mW
Thermal Resistance Junction to Ambient	$R_{ heta JA}$	556	°C/W
Junction Temperature	T_j	150	°C
Storage Temperature	T _{STG}	-55~+150	${\mathbb C}$


Electrical Ratings @TA=25°C


Parameter	Symbol	Test conditions	Min	Max	Unit
Reverse breakdown voltage	$V_{(BR)}$	$I_R=100\mu A$	75		V
Reverse voltage leakage current	I_R	$V_R=75V$		1	μΑ
Forward voltage	V_{F}	$I_F=1 \text{ mA}$ $I_F=10 \text{ mA}$ $I_F=50 \text{ mA}$		0.715 0.855 1	V
Diode capacitance	C_D	V _R =0, f=1MHz		2	pF
Reveres recovery time	t _{rr}	$I_F = I_R = 10 \text{mA}, I_{rr} = 0.1 \times I_{R,}$ $R_L = 100 \Omega$		6	ns




BAS16 Typical Characteristics









X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Diodes - General Purpose, Power, Switching category:

Click to view products by Hottech manufacturer:

Other Similar products are found below:

MMBD3004S-13-F RD0306T-H DSE010-TR-E BAV17-TR BAV19-TR 1N3611 NTE156A NTE574 NTE6244 1SS181-TP 1SS193,LF 1SS400CST2RA SDAA13 SHN2D02FUTW1T1G LS4151GS08 1N4449 1N456A 1N4934-E3/73 1N914B 1N914BTR 1SS226-TP RFUH20TB3S D291S45T BAV300-TR BAW56DWQ-7-F BAW75-TAP MM230L-CAA IDW40E65D1 JAN1N3600 LL4151-GS18 053684A SMMSD4148T3G 707803H NSVDAN222T1G CDSZC01100-HF LL4150-M-08 BAV199E6433HTMA1 BAS28-7 BAW56HDW-13 BAS28 TR VS-HFA04SD60STR-M3 NSVM1MA152WKT1G RGP30D-E3/73 BAV99TQ-13-F BAS21DWA-7 NTE6250 NTE582-4 NTE582-6 MMDB30-E28X VS-HFA04SD60SL-M3