

ALUBUTYL



- For use in waterproofing construction joints
- Excellent durability and water resistance
- Excellent UV and anti-aging resistance
- For waterproofing buildings
- Water vapor permeability: 0,5g/m² 24h

Art. No.	width	length	colour	Pack.	EAN code
HPX-SAB-5020BK	50 mm	20 m	alu-black	18	5407004561240

Adhesive: butyl Carrier: aluminium

Tensile strength: 164,8 N/25 mm Adhesive strength: 19,6 N/25 mm

Thickness: 0,50 mm



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Adhesive Tapes category:

Click to view products by HPX manufacturer:

Other Similar products are found below:

PF24.0W 4718 4516-1/4x36 56-YELLOW-34"X72YD 00-021200-13972-7 021200-64630 60 TAPE (1") 62-GRAY-12"X36YD 62-GRAY-12"X36YD 69-1"X36YD 764-1"x36yd-Red 764-1"x36yd-White PG ASSY 926-1/4X18YD 967454-1 1194-14"X36YD 1181 19MM X 16,5 METERS 1182-7.7X10 1245-34"X18YD 1267 130C-1X15FT 130-1x10FT 1345-3/8x18yrd 1380-2"X8" E39-RS1-CA 1900-48mm 22-1/2X36YD 2229-P-2-1/2x3-3/4 88-SUPER-34X44FT 890103N001 2670 SJ3527N-Black-1.5"x50yd EVK-TA-TM047NBH01 AD-UCUSB-DCAUD-SPL 20-1"X60YDS 2020-18mmx55m H150 3900-Blue 3939-24mmx55m 396-1"x36yd 4016-34"x36yd 4462W-12"x72yd 44-TAN-14"X90YD 4504-34x18 471-Trans-1"x36yd-Bulk 5414 34X36 C-22 35-Gray-1/2 371-Tan-48mmx50m 4008-12"X36YD