

## **STRETCH & FUSE**



- Permanent watertight sealing
- Insulation of electrical connections
- Suitable for all surfaces
- Leaves no residue
- Easy to use
- Pressure resistant up to 8 bar

Art. No.	width	length	colour	Pack.	EAN code
HPX-STF-251.8TR	25 mm	1,80 m	transparent	8	5425014225860
HPX-STF-2503TR	25 mm	3 m	transparent	6	5425014225884
HPX-STF-2503RD	25 mm	3 m	red	6	5425014225907
HPX-STF-2503BK	25 mm	3 m	black	6	5425014225921

Carrier: silicone

**Maximum temperature:** 200°C (up to 260°C for short periods)

Tensile strength: 4,82 mPa Thickness: 0,50 mm Breakdown voltage: 8 kV



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Adhesive Tapes category:

Click to view products by HPX manufacturer:

Other Similar products are found below:

PF24.0W 4718 4516-1/4x36 56-YELLOW-34"X72YD 00-021200-13972-7 021200-64630 60 TAPE (1") 62-GRAY-12"X36YD 62-GRAY-12"X36YD 69-1"X36YD 764-1"x36yd-Red 764-1"x36yd-White PG ASSY 926-1/4X18YD 967454-1 1194-14"X36YD 1181 19MM X 16,5 METERS 1182-7.7X10 1245-34"X18YD 1267 130C-1X15FT 130-1x10FT 1345-3/8x18yrd 1380-2"X8" E39-RS1-CA 1900-48mm 22-1/2X36YD 2229-P-2-1/2x3-3/4 88-SUPER-34X44FT 890103N001 2670 SJ3527N-Black-1.5"x50yd EVK-TA-TM047NBH01 AD-UCUSB-DCAUD-SPL 20-1"X60YDS 2020-18mmx55m H150 3900-Blue 3939-24mmx55m 396-1"x36yd 4016-34"x36yd 4462W-12"x72yd 44-TAN-14"X90YD 4504-34x18 471-Trans-1"x36yd-Bulk 5414 34X36 C-22 35-Gray-1/2 371-Tan-48mmx50m 4008-12"X36YD