



### SPECIFICATIONS:

- Voltage Rating: 250V AC Min
- Current Rating: 2.0A Min
- Dielectric Strength: 1000V AC For 1 Minute
- Insulation Resistance: 1000Megohms Min
- Contact Resistance: 30Milliohms Max
- Operation Temperature: -55°C To +125°C
- Product Withstanding Reflow Soldering: 260°C For 15s
- Durability :5000 Cycles
- Normal Force At Working Position: 80g Min
- Insertion Force:>3N
- Insulator: High Temperature Thermoplastic
- UL 94V-0 Black (LCP Black)
- Contact: Beryllium Copper,  
Gold Flash Over Nickel

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.																																																																													
	A		NEW																																																																																
<table border="1"> <tr> <td>②</td> <td>Terminal</td> <td>—</td> <td>4</td> <td>Phosphor Bronze</td> <td>Au Plated</td> <td>—</td> </tr> <tr> <td>①</td> <td>Housing</td> <td>—</td> <td>1</td> <td>LCP</td> <td>Black</td> <td>—</td> </tr> <tr> <td>ITEM</td> <td>PART NAME</td> <td>TER'NO.</td> <td>QTY.</td> <td>MATERIAL</td> <td>FINISHING</td> <td>REMARK</td> </tr> <tr> <td colspan="4">APPROVALS</td> <td>DATE</td> <td colspan="2"></td> </tr> <tr> <td colspan="4">DRAWN</td> <td>xu qi feng</td> <td>2014.12.05</td> <td></td> </tr> <tr> <td colspan="4">CHECKED</td> <td colspan="3">TITLE: 电池座</td> </tr> <tr> <td colspan="4">APPROVALS</td> <td colspan="3">PART NO. BC-12-4P</td> </tr> <tr> <td colspan="4">TOLERANCES ARE</td> <td>30~12.5 ±0.30</td> <td>ANGLE</td> <td>SCALE: 1:1</td> </tr> <tr> <td colspan="4"></td> <td>10~30 ±0.25</td> <td>UNIT: mm</td> <td>PROJ: ①</td> </tr> <tr> <td colspan="4"></td> <td>5~10 ±0.20</td> <td>DRAWING NO.</td> <td>SHEET 1 OF 1</td> </tr> <tr> <td colspan="4"></td> <td>~5 ±0.15</td> <td></td> <td></td> </tr> </table>							②	Terminal	—	4	Phosphor Bronze	Au Plated	—	①	Housing	—	1	LCP	Black	—	ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK	APPROVALS				DATE			DRAWN				xu qi feng	2014.12.05		CHECKED				TITLE: 电池座			APPROVALS				PART NO. BC-12-4P			TOLERANCES ARE				30~12.5 ±0.30	ANGLE	SCALE: 1:1					10~30 ±0.25	UNIT: mm	PROJ: ①					5~10 ±0.20	DRAWING NO.	SHEET 1 OF 1					~5 ±0.15		
②	Terminal	—	4	Phosphor Bronze	Au Plated	—																																																																													
①	Housing	—	1	LCP	Black	—																																																																													
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK																																																																													
APPROVALS				DATE																																																																															
DRAWN				xu qi feng	2014.12.05																																																																														
CHECKED				TITLE: 电池座																																																																															
APPROVALS				PART NO. BC-12-4P																																																																															
TOLERANCES ARE				30~12.5 ±0.30	ANGLE	SCALE: 1:1																																																																													
				10~30 ±0.25	UNIT: mm	PROJ: ①																																																																													
				5~10 ±0.20	DRAWING NO.	SHEET 1 OF 1																																																																													
				~5 ±0.15																																																																															
 <b>HONGSHI ELECTRONICS CO., LTD</b>																																																																																			

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Cylindrical Battery Contacts, Clips, Holders & Springs](#) category:*

*Click to view products by [HRO parts](#) manufacturer:*

Other Similar products are found below :

[753-00001](#) [12BH36A-GR](#) [273](#) [183](#) [270](#) [274](#) [QX3506](#) [5220](#) [5230](#) [1055](#) [1088](#) [1102](#) [1101](#) [5250](#) [166](#) [1044](#) [1194](#) [KT0008](#) [2134167-1](#) [1012](#)  
[1020](#) [1023](#) [1024C](#) [1025](#) [1027](#) [103](#) [1075](#) [1077](#) [1080](#) [1088](#) [1090](#) [1095](#) [1096](#) [1097](#) [1098](#) [1101](#) [1109](#) [1126](#) [1127](#) [1128](#) [1162](#) [1173](#) [BH383B](#)  
[1199](#) [147](#) [148](#) [149](#) [150](#) [151](#) [152](#)