



PCB Layout

**SPECIFICATIONS:**  
 Voltage Rating: 250V AC Min  
 Current Rating: 2.0A Min  
 Dielectric Strength: 500V AC For 1Minute  
 Insulation Resistance: 1000Megohms Min  
 Contact Resistance: 30Milliohms Max  
 Operation Temperature: -55°C To +125°C  
 Product Withstanding Reflow Soldering: 260°C  
 Durability : 5000 Cycles  
 Normal Force At Working Position: 80g Min  
 Packaging: 750pcs/Reel

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
③	Terminal	—	3	Phosphor Bronze	Au Plated	—
②	PIN-Strapped	—	2	Phosphor Bronze	Sn Plated	—
①	For Housing	—	1	LCP	Black	—

APPROVALS	DATE	TITLE:
DRAWN JKUNLU	2014.12.05	ELECTRONICS CO.,LTD
CHECKED		电池座
APPROVALS		BC-4-3PD

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	ANGLE	UNIT:	SCALE:	SHEET
	A		NEW				30~0.15 ±0.30	±2°	mm	1:1	1 OF 1
							10~30 ±0.25				
							5~10 ±0.20				
							~5 ±0.15				

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Cylindrical Battery Contacts, Clips, Holders & Springs](#) category:*

*Click to view products by [HRO parts](#) manufacturer:*

Other Similar products are found below :

[753-00001](#) [12BH36A-GR](#) [273](#) [183](#) [270](#) [274](#) [QX3506](#) [5220](#) [5230](#) [1055](#) [1088](#) [1102](#) [1101](#) [5250](#) [166](#) [1044](#) [1194](#) [KT0008](#) [2134167-1](#) [1012](#)  
[1020](#) [1023](#) [1024C](#) [1025](#) [1027](#) [103](#) [1075](#) [1077](#) [1080](#) [1088](#) [1090](#) [1095](#) [1096](#) [1097](#) [1098](#) [1101](#) [1109](#) [1126](#) [1127](#) [1128](#) [1162](#) [1173](#) [BH383B](#)  
[1199](#) [147](#) [148](#) [149](#) [150](#) [151](#) [152](#)