



Rating:5A 24V DC
 Contact Resistance:100 mΩ Max.
 Operating force:3-20N
 Operating Life:5,000cycles

②	Terminal	—	1	PA	Black	—
①	Housing	—	2	BARSS	Ni Plating	—
ITEM	PART NAME	TER.NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE	TITLE: PHONE JACKES			
DRAWN	J.X.Zhong	2020/6/1	ELECTRONICS CO.,LTD			
CHECKED			HROECS®			

APPROVALS		TITLE: PHONE JACKES	
DRAWN	J.X.Zhong	ELECTRONICS CO.,LTD	
CHECKED		HROECS®	
APPROVALS		PART NO.	DC-084
TOLERANCES ARE	30~80 [±] 10~30 ±0.20 5~10 ±0.15	ANGLE	±2°
~5 ±0.10		UNIT: mm	SCALE: 1:1
		DRAWING NO.	PROJ: 1 OF 1
ECN NO.	REV.	DATE.	DESCRIPTION.
	B		2018.11.05
	A		2016.12.12
			NEW

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Power Connectors](#) category:

Click to view products by [HRO parts](#) manufacturer:

Other Similar products are found below :

[KLDX-SMT-0202-BPTR](#) [171-0722-E](#) [K596](#) [KLD-0201-BC](#) [4C6831AX](#) [10073976-112LF](#) [LCB60PW-M](#) [LCB30PW-M](#) [LCB60PB-M](#)
[LCC30PB-M](#) [LCB50PW-M](#) [LCB50-M](#) [LCB60-F](#) [LCC30-M](#) [LCB40PW-M](#) [LCC30PW-M](#) [LCB50-F](#) [LCB40-F](#) [LCB30-F](#) [LCC40-M](#)
[LCC40PB-M](#) [LCB40PB-M](#) [LCC40-F](#) [LCB60-M](#) [LCC40PW-M](#) [LCB50PB-M](#) [DC-002-100](#) [DC-031A-130](#) [DC-031A-100](#) [DC-003A-130](#)
[DC-045-130](#) [DC-192-130](#) [DC-033-130](#) [DC-011-100](#) [DC-002F-130](#) [DC-002-130](#) [DB-14-2F](#) [DC-183B](#) [DC-060-04A](#) [DC-099-200](#) [DC-015-](#)
[250-A](#) [DC-016-200-A](#) [DC-005A-200](#) [DC-044A-200](#) [DC-088-200](#) [DC-022A-200](#) [DC-038-150](#) [DC-012A-250](#) [DC-005C-130](#) [DC-012A-200](#)