


从开关顶端2毫米的位置 往L以及R方向移动时 ON开始位置在 0.5 ± 0.35

技术要求:
 1. 零件表面应光洁, 注塑件无明显飞边及注塑缺陷, 插脚无毛刺及变形;
 2. 在P'切线方向测量动作力为 $\leq 0.50N$;
 3. 手柄左右转过 $\leq 7^\circ$ 必须不通电;
 4. 未注尺寸公差均按GB1804-m级精度要求



ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
NEW						

APPROVALS	DATE	DRAWN	J.X.Zhang	DATE	2018/8/1
CHECKED	TITLE:	DETECTOR SWITCHS			
APPROVALS	PART NO.	K5-1675DA-01			
APPROVALS	PART NO.	K5-1675DA-01			
ELECTRONICS CO.,LTD					

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
①	Knob	—	1	POM	Black	
②	Cover	—	1	SUS	Black	
③	Base	—	1	PA66	Black	
④	Terminal	—	4	Phosphor Bronze	Ag Plated	
⑤	Contact Spring	—	1	SUS	Natural	

ANGLE	DRAWING NO.	UNIT:	SCALE:	PROJ:
±2°		mm	1:1	—

TOLERANCES ARE	±	±2°	±0.10	±0.15	±0.20	±0.30	±0.50
30~以上	~5	5~10	10~30	30~以上	30~以上	30~以上	30~以上

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Basic / Snap Action Switches](#) category:

Click to view products by [HRO parts manufacturer](#):

Other Similar products are found below :

[83228001](#) [01.098.1358.1](#) [602EN1-6B](#) [602EN532](#) [602EN535-RB](#) [602HE5-RB1](#) [604HE162](#) [604HE223-6B](#) [624HE17-RB](#) [6HM89](#) [6PA78-JM](#)
[6SE1](#) [6SX1-H58](#) [70500840](#) [MBD5B1](#) [MBH2731](#) [73-316-0012](#) [79211759](#) [79211923](#) [79218589](#) [7AS12](#) [ML-1155](#) [ML-1376](#) [831010C3.0](#)
[831060C3.TL](#) [831090C2.EL](#) [83131904](#) [84212012](#) [8AS239](#) [8HM73-3](#) [903VB1-PG](#) [914CE1-6G](#) [PL-100](#) [11SM1077-H4](#) [11SM1077-H58](#)
[11SM1-TN107](#) [11SM405](#) [11SM703-T](#) [11SM8423-H2](#) [11SX37-T](#) [11SX48-H58](#) [11SX55-H58](#) [11SM2442-T](#) [11SM76-T](#) [11SM77-H58](#)
[11SM77-T](#) [11SM863-T](#) [11SM866](#) [11SX47-H58](#) [A7CN-1M-1-LEFT](#)