



Circuit Diagram

- NOTE:
1. Rating: AC125V 5A/250V 3A
 2. Operating force: 30 ± 15 gf
 3. Mechanical Life: 1,000,000
 3. Electrical Life: 60000-10,000

⑧	Shrapnel 2	1	Copper Alloy			
⑦	Shrapnel 1	1	Beryllium Copper			
⑥	Contact	1	Copper Alloy	Plating silver		
⑤	Lever	1	Copper Alloy			
④	Terminal	3	Copper Alloy	Plating silver		
③	Housing	1	PBT	Black		
②	Knob	1	PBT	Black		
①	Cover	1	PBT	Black		
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
APPROVALS		DATE		ELECTRONICS CO.,LTD		
DRAWN		2015.5.26		MICRO SWITCHS		
CHECKED				K9-1910A		
APPROVALS				PART NO.		
TOLERANCES ARE		30~120	±0.30	ANGLE	UNIT: mm	SCALE: 1:1
		10~20	±0.25			PROD.
		5~10	±0.20	±2'	DRAWING NO.	SHEET 1 OF 1
		~ 5	±0.20			

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Basic / Snap Action Switches](#) category:

Click to view products by [HRO parts manufacturer](#):

Other Similar products are found below :

[5SM901-S12](#) [5SM9-S12N195](#) [602EN532](#) [602EN535-RB](#) [602HE5-RB1](#) [604HE162](#) [604HE223-6B](#) [624HE17-RB](#) [6HM82](#) [6HM89](#) [6SE1](#)
[6SX1-H58](#) [70500216](#) [70599106](#) [71051](#) [MBH2731](#) [79211923](#) [79218589](#) [7AS12](#) [MIL30126AB6BBMD4A12XAU](#) [ML-1155](#) [ML-1376](#)
[831010C3.0](#) [831090C2.EL](#) [83131904](#) [84212012](#) [8AS239](#) [8HM73-3](#) [8SX26-H33](#) [914CE1-6G](#) [PL-100](#) [11SM1077-H4](#) [11SM1077-H58](#)
[11SM1-TN107](#) [11SM405](#) [11SM8423-H2](#) [11SX37-T](#) [11SX48-H58](#) [11SM2442-T](#) [11SM76-T](#) [11SM77-H58](#) [11SM863-T](#) [11SM866](#) [A7CN-](#)
[1M-1-LEFT](#) [A831700C7.0](#) [121EN188-R](#) [1245.0120](#) [125EN56-RB](#) [1267.0101](#) [1267.7101](#)