


P.C.B LAYOUT(copper-sided view)



Model NO	PJ-2102
Schematic	

Rating:0.5A 30V DC  
 Contact Resistance:100 mΩ Max.  
 Operating temperature:—20℃~70℃  
 Operating force:3—20N  
 Operating Life:5,000cycles

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
<p>Rating:0.5A 30V DC                  Contact Resistance:100 mΩ Max.                  Operating temperature:—20℃~70℃                  Operating force:3—20N                  Operating Life:5,000cycles</p>						
DRAWN		J.X.Zhang	DATE		2013/11/11	
CHECKED			TITLE:		PHONE JACKES	
APPROVALS			PART NO.		PJ-2102	
TOLERANCES ARE		30~0.1±	±0.30	ANGLE	UNIT: mm	SCALE: 1:1
		10~0.20	±0.20			PROJ:
		5~0.10	±0.15	±2'	DRAWING NO.	SHEET 1 OF 1
 ELECTRONICS CO.,LTD						

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [HDMI, Displayport & DVI Connectors](#) category:*

*Click to view products by [HRO parts manufacturer](#):*

Other Similar products are found below :

[1775247-3](#) [2-1932649-5](#) [30-1231](#) [30-528](#) [2069485-1](#) [30-504](#) [30-519](#) [30-542](#) [47648-2000](#) [2002-400](#) [TC142X](#) [1453G1](#) [769-103/021-000](#)  
[1932649-1](#) [233-368NFG6-17NH](#) [G45A19071083HR](#) [233-360NF00-17NH](#) [CP30200GM3B](#) [HYC02-DVI29-371](#) [P136-06NHDV4KBP](#)  
[CP30116](#) [LTWDID-29PFFS-SL8001](#) [46765-1301](#) [1211-0010-201-001](#) [47271-1004](#) [32-1121-BU](#) [DS1117-BN0-TME-002](#) [MHDR2A11004BP](#)  
[EHHDMI2PKG](#) [1903015-3](#) [DS1114-BN0](#) [WPUSBAF](#) [500254-1931](#) [HDMR-19-01-F-SM](#) [47151-1071](#) [1747981-1](#) [0480372000](#) [0482580001](#)  
[D121073-19](#) [472710111](#) [HDMI-S-RA6-SMT-MF-15](#) [P142-000-UP](#) [P134-003](#) [P120-08N](#) [KDMIX-FS1V-WS-B](#) [P142-000-UD](#) [10029449-](#)  
[101RLF](#) [P132-000](#) [P130-000](#) [P142-06N-MICRO](#)