


P C B Layout(Top view)



Rating:0.5A 30V DC
 Contact Resistance:100 mΩ Max.
 Operating temperature:—20℃~70℃
 Operating force:3—20N
 Operating Life:5,000cycles

Model NO	PJ-316C-A	PJ-316C-B	PJ-316C-C
Schematic			
Model NO	PJ-316C-D	PJ-316C-E	PJ-316C-F
Schematic			

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
DRAWN xu qi feng 2014/9/19 CHECKED APPROVALS TOLERANCES ARE 30~125 ±0.30 10~30 ±0.20 5~10 ±0.15 ~5 ±0.10						
DATE			TITLE: PHONE JACKES			
DATE			PART NO. PJ-316C(无头)			
DATE			SCALE: 1:1			
DATE			DRAWING NO.			
DATE			SHEET 1 OF 1			
ELECTRONICS CO.,LTD 						
MATERIAL PHOSPHOR BRONZE FINISHING PLATING Au REMARK BLACK						

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [HDMI, Displayport & DVI Connectors](#) category:

Click to view products by [HRO parts](#) manufacturer:

Other Similar products are found below :

[1775247-3](#) [2-1932649-5](#) [30-1231](#) [30-528](#) [2069485-1](#) [30-504](#) [30-519](#) [30-542](#) [47648-2000](#) [2002-400](#) [1453G1](#) [769-103/021-000](#) [1932649-1](#)
[233-368NFG6-17NH](#) [G45A19071083HR](#) [233-360NF00-17NH](#) [CP30200GM3B](#) [HYC02-DVI29-371](#) [P136-06NHDV4KBP](#) [CP30116](#)
[LTWDID-29PFFS-SL8001](#) [46765-1301](#) [1211-0010-201-001](#) [47271-1004](#) [32-1121-BU](#) [DS1117-BN0-TME-002](#) [MHDR2A11004BP](#)
[EHHDMI2PKG](#) [1903015-3](#) [DS1114-BN0](#) [WPUSBAF](#) [500254-1931](#) [UAD011FM](#) [HDMR-19-01-F-SM](#) [47151-1071](#) [1747981-1](#) [0480372000](#)
[0482580001](#) [D121073-19](#) [472710111](#) [HDMI-S-RA6-SMT-MF-15](#) [P142-000-UP](#) [P134-003](#) [P120-08N](#) [KDMIX-FS1V-WS-B](#) [P142-000-UD](#)
[P132-000](#) [P130-000](#) [P142-06N-MICRO](#) [P142-000-MINI](#)