


P.C.B LAYOUT(copper-sided view)



Model No.	L=3.0	PJ-3220-A	PJ-3220-B
	L=6.5	PJ-3220-C	PJ-3220-D
Schematic			

Rating:0.5A 30V DC
 Contact Resistance:100 mΩ Max.
 Operating temperature:-20℃~70℃
 Operating force:3-20N
 Operating Life:5,000cycles

DRAWN		J.X.Zhang		DATE		2013/11/11		TITLE:		PHONE JACKETS	
CHECKED				APPROVALS				PART NO.		PJ-3220	
APPROVALS				ITEM		Terminal		5		Phosphor bronze Au Plating	
TOLERANCES ARE		30 ^{±0.15}		±0.30		ANGLE		UNIT: mm		SCALE: 1:1	
±0.10		±0.20		±0.15		±2°		DRAWING NO.		PROJ. SHEET 1 OF 1	
ECN NO.		REV.		DATE.		DESCRIPTION.		CHANGE.		CHECK.	
A						NEW					

HRONICS
 ELECTRONICS CO.,LTD

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [HDMI, Displayport & DVI Connectors](#) category:

Click to view products by [HRO parts manufacturer](#):

Other Similar products are found below :

[1775247-3](#) [2-1932649-5](#) [30-1231](#) [30-528](#) [2069485-1](#) [30-504](#) [30-519](#) [30-542](#) [47648-2000](#) [2002-400](#) [TC142X](#) [1453G1](#) [769-103/021-000](#)
[1932649-1](#) [233-368NFG6-17NH](#) [G45A19071083HR](#) [233-360NF00-17NH](#) [CP30200GM3B](#) [HYC02-DVI29-371](#) [P136-06NHDV4KBP](#)
[CP30116](#) [LTWDID-29PFFS-SL8001](#) [46765-1301](#) [1211-0010-201-001](#) [47271-1004](#) [32-1121-BU](#) [DS1117-BN0-TME-002](#) [MHDR2A11004BP](#)
[EHHDMI2PKG](#) [1903015-3](#) [DS1114-BN0](#) [WPUSBAF](#) [500254-1931](#) [HDMR-19-01-F-SM](#) [47151-1071](#) [1747981-1](#) [0480372000](#) [0482580001](#)
[D121073-19](#) [472710111](#) [HDMI-S-RA6-SMT-MF-15](#) [P142-000-UP](#) [P134-003](#) [P120-08N](#) [KDMIX-FS1V-WS-B](#) [P142-000-UD](#) [10029449-](#)
[101RLF](#) [P132-000](#) [P130-000](#) [P142-06N-MICRO](#)