



Recommended PCB Layout

Ø0.92*4

规格说明: Specifications:
电气特性: Electrical:

- 1. 额定电流: Current Rating 1.5A/contact terminal
 - 2. 额定电压: Voltage Rating 30V DC
 - 3. 接触电阻: Contact Resistance 30 milliohms MAX
 - 4. 耐电压: Dielectric Withstanding Voltage: 500 V AC AT Sea Level
 - 5. 绝缘电阻: Insulation Resistance: 1000MEGA ohms MIN
- 物理性能: Mechanical:
- 1. 插拔力: Connector Mate and Unmate Force Mate force: 3.57kgf(MAX) Unmate force: 1.02kgf(MIN)
 - 2. 端子保持力: Terminal Retention 1.0kgf(MIN)



③	Base	—	1	NYLON		
②	Terminal	—	4	Phosphor Bronze	Ag Plated	
①	Housing	—	1	SPCC	Sn Plated	
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
APPROVALS		DATE				

DRAWN xu qi feng 2018/8/1
 TITLE: USB CONNECTOR
 ELECTRONICS CO.,LTD

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
TOLERANCES ARE		30~0.15	±0.30	ANGLE	PART NO.	SCALE: 1:1
		10~30	±0.25	UNIT: mm	U-A-24DD-W-10	PROJ: 10
		5~10	±0.20	±2'	DRAWING NO.	SHEET 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [HRO parts manufacturer](#):

Other Similar products are found below :

[950](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBC111M5](#) [MUSBD11135](#) [17-200721](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#)
[KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [A-USB](#)
[A-2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVSCCG](#) [4689-1](#) [1-1734084-2](#) [MUSBC11135](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#)
[MUSBB151341](#) [10135326-001LF](#) [M9177/3-1](#) [TJ-105](#) [USB-A-S-F-B-VT](#) [4198](#) [690-024-633-031](#) [UB-20PMFP-LC7001](#) [USBFTVC6MRG](#)
[UA-20BMFA-SL8001](#) [17-200011](#) [USBFTVC7ZC](#) [UB-20AFMM-LL7A01](#) [USBFTVC2MN](#) [CAP-WCCMLPB1](#) [1310-1031-01](#) [2041386-1](#)
[2274475-3](#) [UB-20BMFA-SL8001](#) [UB-20PMFP-SC8003](#)